

optimizing wastewater systems

Optimized Collection System Master Plan: Overview of SIAG Role and Participation

Outline

- Introductions
- Presentation Objectives
- Overview of Optimization Process
- Optimization Test Runs on a Hypothetical Bend Collection System Model
- Recent Case Study Example for City in Indiana
- Discussion

Objectives:

- Strengthen SIAG's understanding of the Optimization tool and how it will be used in developing the Master Plan.
- Communicate how SIAG can participate in and influence the optimization process.

Optimization Benefits (recap)

- Ability to evaluate thousands of possible options
 - Transparent
 - Identifies lowest life-cycle cost solutions
 - Identifies only solutions that provide capacity
- Unbiased when compared to traditional planning methods
- >\$100M of system improvements = opportunity to look for savings and prioritize investment



How Does Optimizer WCS™ Work?

Hydraulic Model

(input from SIAG, City of Bend, and MSA Team)

Improvement Options

(input from SIAG, City of Bend, and MSA Team)


Costs

(input from SIAG, City of Bend and MSA Team)

Performance Criteria

(input from SIAG, City of Bend and MSA Team)

Once initial Optimization
Formulation is processed, alternate
Scenarios as well as Sensitivity
Runs can be performed efficiently



Bend CSMP Optimization SIAG Input

Hydraulic Model (input from SIAG)

Land Use -Community values related to density and

in on location zoning preferences. preferences).

Options (reviewed by SIAG) (reviewed by SIAG) (input from SIAG) Pipes – Alignment Open-cut pipe costs Eliminate overflows alternatives (e.g., weigh Trenchless construction costs Land-use & geol. factors **Pumps** – Provide Capital costs for new/upgraded pumps guidance on location requirements preferences for new Energy / O&M costs **Energy costs** pumps and aesthetics Capital and O&M Site restoration Land acquisition Site specific costs

Capital / O&M Costs

Storage - Location preferences and review of storage type/technology

Improvement

Treatment – Location preferences, technologies (green and traditional)

Costs for different technologies

Constr / O&M costs

Performance Criteria

- System capacity goals

Pump operating

Siting requirements

Operating flexibility

Land use needs


Nuisance issues

Discharge requirements

Discharge location(s)

Effluent volume limitations

Summary of Optimization Milestones and Opportunity for SIAG Involvement



Key Optimization Tasks and SIAG Inputs

| Timing | Tasks | Date |
|-----------|--|---|
| February | Intro to Optimization Review Life Cycle, Design Criteria, Viability Criteria | Feb 7 SIAGFeb 21 SIAG |
| March | Present pipe/pump/storage options for consideration | Mar 7 SIAGMar 21 (as Req.) |
| April | Present sewer treatment options for consideration | April 4 SIAGApril 18 (as Req.) |
| June/July | Review location options for pumps, pipes, storage and treatment | Date TBD SIAG |
| August | Review unit cost assumptions for all options | August 15 SIAG |
| November | Present initial solutions to SIAG and review all options considered to date SIAG to provide feedback on initial solutions (e.g. options to be added/removed, detailed considerations, etc.) | • Nov 14 SIAG |

Key Optimization Tasks and SIAG Inputs

| Timing | Tasks | Date |
|-------------|---|------------|
| January '14 | Present intermediate solutions to SIAG SIAG to provide feedback on interim solutions (e.g. options to be added/removed, detailed considerations, etc.) | • Jan SIAG |
| March '14 | Review final solutions with SIAG | March SIAG |
| May '14 | Prioritize Capital Improvement Plan | May SIAG |




optimizing wastewater systems

Optimizer Test Runs Using Hypothetical Bend CS Model


Bend CS Model Prep. for Optimization


- Pipe and pump options shown in blue
- Storage options shown in purple (14 locations)



Optimization Progress for Initial 200 Trial Solution Evaluations

| Cost Item | Total Cost (\$ Arb) (Including O&M) |
|--------------------|--|
| Pipes | |
| Pumps | |
| Storage | |
| Total Project Cost | |







Generation 1 (200 Trial Solutions)

Best Solution in 1st Generation

| Cost Item | Total Cost (\$ Arb) (Including O&M) |
|--------------------|--|
| Pipes | 58.3 |
| Pumps | 5.4 |
| Storage | 8.3 |
| Total Project Cost | 72.0 |




- Actual processing time: 0.15 hours (cloud computing using 104 cores in parallel)
- Complete hydraulic analysis of each trial solution
- Detailed life-cycle cost analysis of each trial sol.
- All costs divided by arbitrary value for purpose of demonstration




Generation 2 (400 Trial Solutions)

Best Solution in 2nd Generation

| Cost Item | Total Cost (\$ Arb) (Including O&M) |
|--------------------|--|
| Pipes | 51.3 |
| Pumps | 4.3 |
| Storage | 8.7 |
| Total Project Cost | 64.3 |




- Actual processing time: 0.3 hours (cloud computing using 104 cores in parallel)
- Complete hydraulic analysis of each trial solution
- Detailed life-cycle cost analysis of each trial sol.
- All costs divided by arbitrary value for purpose of demonstration




Generation 5 (1,000 Trial Solutions)

Best Solution in 5th Generation

| Cost Item | Total Cost (\$ Arb) (Including O&M) |
|--------------------|--|
| Pipes | 49.4 |
| Pumps | 5.9 |
| Storage | 6.1 |
| Total Project Cost | 61.4 |




- Actual processing time: 0.75 hours (cloud computing using 104 cores in parallel)
- Complete hydraulic analysis of each trial solution
- Detailed life-cycle cost analysis of each trial sol.
- All costs divided by arbitrary value for purpose of demonstration




Generation 10 (2,000 Trial Solutions)

Best Solution in 10th Generation

| Cost Item | Total Cost (\$ Arb) (Including O&M) |
|--------------------|--|
| Pipes | 42.0 |
| Pumps | 4.3 |
| Storage | 9.3 |
| Total Project Cost | 55.6 |




- Actual processing time: 1.50 hours (cloud computing using 104 cores in parallel)
- Complete hydraulic analysis of each trial solution
- Detailed life-cycle cost analysis of each trial sol.
- All costs divided by arbitrary value for purpose of demonstration




Generation 25 (50,000 Trial Solutions)

Best Solution in 25th Generation

| Cost Item | Total Cost (\$ Arb) (Including O&M) |
|--------------------|--|
| Pipes | 31.2 |
| Pumps | 5.4 |
| Storage | 6.1 |
| Total Project Cost | 42.7 |




- Actual processing time: 3.75 hours (cloud computing using 104 cores in parallel)
- Complete hydraulic analysis of each trial solution
- Detailed life-cycle cost analysis of each trial sol.
- All costs divided by arbitrary value for purpose of demonstration




Generation 50 (100,000 Trial Solutions)

Best Solution in 50th Generation

| Cost Item | Total Cost (\$ Arb) (Including O&M) |
|--------------------|--|
| Pipes | 21.7 |
| Pumps | 3.5 |
| Storage | 10.1 |
| Total Project Cost | 35.3 |




- Actual processing time: 7.50 hours (cloud computing using 104 cores in parallel)
- Complete hydraulic analysis of each trial solution
- Detailed life-cycle cost analysis of each trial sol.
- All costs divided by arbitrary value for purpose of demonstration




Generation 75 (150,000 Trial Solutions)

Best Solution in 75th Generation

| Cost Item | Total Cost (\$ Arb) (Including O&M) |
|--------------------|--|
| Pipes | 21.7 |
| Pumps | 3.5 |
| Storage | 10.1 |
| Total Project Cost | 35.3 |




- Actual processing time: 11.25 hours (cloud computing using 104 cores in parallel)
- Complete hydraulic analysis of each trial solution
- Detailed life-cycle cost analysis of each trial sol.
- All costs divided by arbitrary value for purpose of demonstration




Generation 100 (200,000 Trial Solutions)

Best Solution in 100th Generation

| Cost Item | Total Cost (\$ Arb) (Including O&M) |
|--------------------|--|
| Pipes | 10.4 |
| Pumps | 2.7 |
| Storage | 10.7 |
| Total Project Cost | 23.8 |




- Actual processing time: 15.00 hours (cloud computing using 104 cores in parallel)
- Complete hydraulic analysis of each trial solution
- Detailed life-cycle cost analysis of each trial sol.
- All costs divided by arbitrary value for purpose of demonstration




Generation 125 (250,000 Trial Solutions)

Best Solution in 125th Generation

| Cost Item | Total Cost (\$ Arb) (Including O&M) |
|--------------------|--|
| Pipes | 7.6 |
| Pumps | 5.9 |
| Storage | 9.1 |
| Total Project Cost | 22.6 |




- Actual processing time: 18.75 hours (cloud computing using 104 cores in parallel)
- Complete hydraulic analysis of each trial solution
- Detailed life-cycle cost analysis of each trial sol.
- All costs divided by arbitrary value for purpose of demonstration




Example Sensitivity Analysis on Loadings

Option 1: \$13.7 M in Pipe Improvements (for Base loading)



Example Sensitivity Analysis on Loadings

Option 2, \$20.2 M in Pipe Improvements (for Base loading + 20%)





optimizing wastewater systems

Discussion






optimizing water systems

CSO LTCP Optimization for South Bend, Indiana

Baseline LTCP Solution Agreed with EPA


| Cost Item | Baseline Solution (\$M) | | |
|-------------------------|----------------------------|--|--|
| Conveyance | 149.83 | | |
| Pump Station | 0.00 | | |
| Linear Storage | 42.66 | | |
| Storage Tank | 99.81 | | |
| Relining | 13.04 | | |
| RTC | 0.00 | | |
| Green Technology | 0.00 | | |
| Total Construction Cost | 305.34 | | |
| Eng/Leg/Adm. (20%) | 61.07 | | |
| Total Capital Cost | 366.41 | | |
| Present Worth O&M | 45.61 | | |
| TOTAL PROJECT COST | 412.02 | | |



Comparison of Baseline and Optimized Solutions

| Cost Item | Baseline Solution (\$M) | Optimized Solutions | | | | | |
|-------------------------------|-------------------------------|---------------------|---------------------|-------------------------------------|---------------------|---------------------|--|
| | | Solution 1 (\$M) | Solution 2 (\$M) | Solution 3 Optimized Solution | Solution 4 (\$M) | Solution 5 (\$M) | |
| Conveyance | 149.83 | 114.40 | 114.40 | 114.40 | 114.40 | 114.40 | |
| Pump Station | - | 1.25 | 1.25 | 1.25 | 1.25 | 1.25 | |
| Linear Storage | 42.66 | 13.96 | 13.96 | 13.96 | 13.96 | 13.96 | |
| Storage Tank | 99.80 | 123.62 | 116.82 | 63.28 | 95.81 | 96.68 | |
| Relining | 13.04 | 3.51 | 3.51 | 2.18 | 2.67 | 2.56 | |
| RTC | - | - | 2.67 | 2.67 | 2.67 | 2.67 | |
| Green Technology | - | | - | 27.39 | 19.04 | 15.06 | |
| Total Construction Cost | 305.34 | 256.75 | 252.62 | 225.13 | 249.80 | 246.58 | |
| Engineering/Legal/Admin (20%) | 61.07 | 51.35 | 50.52 | 45.03 | 49.96 | 49.32 | |
| Total Capital Cost | <u>366.40</u> | 308.10 | 303.14 | <u>270.16</u> | 299.76 | 295.90 | |
| Present Worth O&M | 45.61 | 42.02 | 40.84 | 29.40 | 37.45 | 35.92 | |
| TOTAL PROJECT COST | 412.01 | 350.11 | 343.98 | 299.56 | 337.21 | 331.82 | |
| Savings | | 61.90 | 68.04 | 112.46 | 74.80 | 80.19 | |
| | | 15% | 17% | 27% | 18% | 19% | |

Prioritization of Projects for Maximum Impact





optimizing wastewater systems

Discussion