

**APPENDIX A**

---

**Street Inventory**

**APPENDIX A  
BEND CENTRAL AREA PLAN  
STREET SYSTEM INVENTORY**

Street Name	Begin	End	Jurisdiction	Functional Classification	ROW Width (feet)	Paved Width (feet)	Number of Lanes	Pavement Type	Pavement Condition (PCI)	Curb	Bike Lane	Sidewalk	Data Source
US 97	Cooley Road	Highway 20	ODOT	Expressway	100-210	74	5	AC	VG	Y	Y	N	TSP
US 97	Highway 20	South of study area	ODOT	Expressway	160	80	5	AC	P-F	N	Y	N	TSP
Highway 20	Empire Avenue	Division Street	ODOT	Principal Arterial	100-130	72-86	5	AC	VG	Y	Y	P	TSP
Highway 20	Division Street	Revere Avenue	ODOT	Principal Arterial	80-135	54-64	4-5	AC	VG	P	N	P	TSP
Highway 20	Revere Avenue	Greenwood Avenue	ODOT	Principal Arterial	80	64	5	AC	VG	Y	N	Y	TSP
Highway 20	3rd Street	4th Street	ODOT	Principal Arterial	80	66	5	AC	VP	Y	N	Y	TSP
Highway 20	4th Street	8th Street	ODOT	Principal Arterial	80	66	5	AC	F	Y	Y	Y	TSP
3rd Street	Greenwood Avenue	Franklin Avenue	ODOT	Principal Arterial	80	64	5	AC	VG	Y	N	Y	TSP
3rd Street	Franklin Avenue	Wilson Avenue	ODOT	Principal Arterial	80-110	64	5	AC	VG	Y	N	Y	TSP
4th Street	Butler Market Road	Addison Avenue	City	Minor Arterial	60-70	40	2-3	AC	67	N	N	N	TSP&Database
4th Street	Addison Avenue	Xerxes Avenue	City	Minor Arterial	60	36	2	AC	67	P	Y	P	TSP&Database
4th Street	Xerxes Avenue	Webster Avenue	City	Minor Arterial	60	40	2	AC	42	P	Y	P	TSP&Database
4th Street	Webster Avenue	Webster Avenue	City	Minor Arterial	60	40	2	AC	69	P	Y	P	TSP&Database
4th Street	Webster Avenue	Vail Avenue	City	Minor Arterial	60	40	2	AC	57	P	Y	P	TSP&Database
4th Street	Vail Avenue	Underwood Avenue	City	Minor Arterial	60	40	2	AC	37	P	Y	P	TSP&Database
4th Street	Underwood Avenue	Studio Road	City	Minor Arterial	60	40	2	AC	58	P	Y	P	TSP&Database
4th Street	Studio Road	Seward Avenue	City	Minor Arterial	60	40	2-3	AC	36	P	Y	P	TSP&Database
4th Street	Seward Avenue	Revere Avenue	City	Minor Arterial	60	40	2-3	AC	19	P	Y	P	TSP&Database
4th Street	Revere Avenue	Quimby Avenue	City	Minor Arterial	60	40	2	AC	71	Y	N	P	TSP&Database
4th Street	Quimby Avenue	Penn Avenue	City	Minor Arterial	60	40	2	AC	83	Y	N	P	TSP&Database
4th Street	Penn Avenue	Olney Avenue	City	Minor Arterial	60	40	2	AC	89	Y	N	P	TSP&Database
4th Street	Olney Avenue	Norton Avenue	City	Minor Arterial	60	40	2	AC	80	Y	N	P	TSP&Database
4th Street	Norton Avenue	Marshall Avenue	City	Minor Arterial	60	40	2	AC	80	Y	N	P	TSP&Database
4th Street	Marshall Avenue	Lafayette Avenue	City	Minor Arterial	60	40	2	AC	73	Y	N	P	TSP&Database
4th Street	Lafayette Avenue	Kearney Avenue	City	Minor Arterial	60	40	2	AC	85	Y	N	P	TSP&Database
4th Street	Kearney Avenue	Greenwood Avenue	City	Minor Arterial	60	40	2	AC	80	Y	N	P	TSP&Database
4th Street	Greenwood Avenue	Irving Avenue	City	Minor Arterial	60	30	2	AC	80	Y	N	P	TSP&Database
4th Street	Irving Avenue	Hawthorne Avenue	City	Minor Arterial	60	40	2-3	AC	79	Y	N	P	TSP&Database
4th Street	Hawthorne Avenue	Greeley Avenue	City	Minor Arterial	60	40	2-3	AC	81	Y	N	P	TSP&Database
4th Street	Greeley Avenue	Franklin Avenue	City	Minor Arterial	60	40	2-3	AC	74	Y	N	P	TSP&Database
4th Street	Franklin Avenue	Emerson Avenue	City	Major Collector	60	37	2	AC	85	Y	N	N	TSP&Database
4th Street	Emerson Avenue	Dekalb Avenue	City	Major Collector	60	37	2	AC	77	Y	N	N	TSP&Database
4th Street	Dekalb Avenue	Clay Avenue	City	Major Collector	60	37	2	AC	76	Y	N	N	TSP&Database
4th Street	Clay Avenue	Burnside Avenue	City	Major Collector	60	37	2	AC	83	Y	N	N	TSP&Database
4th Street	Burnside Avenue	Alden Avenue	City	Major Collector	60	34	2	PCC	80	Y	N	N	TSP&Database
Bond Street	Wall Street	Greenwood Avenue	City	Minor Arterial	80	58	2	AC	75	Y	N	Y	TSP&Database

Street Name	Begin	End	Jurisdiction	Functional Classification	ROW Width (feet)	Paved Width (feet)	Number of Lanes	Pavement Type	Pavement Condition (PCI)	Curb	Bike Lane	Sidewalk	Data Source
Bond Street	Greenwood Avenue	Oregon Avenue	City	Major Collector	80	56	2-3	AC/AC	90	Y	N	Y	TSP&Database
Bond Street	Oregon Avenue	Minnesota Avenue	City	Major Collector	80	56	2-3	AC/AC	90	Y	N	Y	TSP&Database
Bond Street	Minnesota Avenue	Franklin Avenue	City	Major Collector	80	56	2-3	AC/AC	92	Y	N	Y	TSP&Database
Bond Street	Franklin Avenue	Louisiana Avenue	City	Major Collector	60-80	36	2-3	AC	72	Y	N	Y	TSP&Database
Bond Street	Louisiana Avenue	Kansas Avenue	City	Major Collector	60-80	56	2-3	AC	81	Y	N	Y	TSP&Database
Bond Street	Kansas Avenue	Idaho Avenue	City	Major Collector	60-80	36	2-3	AC	81	Y	N	Y	TSP&Database
Bond Street	Idaho Avenue	Georgia Avenue	City	Major Collector	60-80	36	2-3	AC	80	Y	N	Y	TSP&Database
Bond Street	Georgia Avenue	Florida Avenue	City	Major Collector	60-80	36	2-3	AC	81	Y	N	Y	TSP&Database
Bond Street	Florida Avenue	Delaware Avenue	City	Major Collector	60-80	36	2-3	AC	80	Y	N	Y	TSP&Database
Bond Street	Delaware Avenue	Colorado Avenue	City	Major Collector	60-80	36	2-3	AC	85	Y	N	Y	TSP&Database
Bond Street	Colorado Avenue	Arizona Avenue	City	Major Collector		36	2-3	AC	89	Y	N	Y	TSP&Database
Bond Street	Arizona Avenue	Industrial Way	City	Major Collector		36	2-3	AC	90	Y	N	Y	TSP&Database
Colorado Avenue	Simpson Avenue	Industrial Way	City	Minor Arterial	80	32	2	AC	80	Y	P	P	TSP&Database
Colorado Avenue	Industrial Way	Wall Street	City	Minor Arterial	80	40	3	AC	83	Y	P	P	TSP&Database
Colorado Avenue	Wall Street	Sisemore Street	City	Minor Arterial	60	42	2	AC	77	Y	N	Y	TSP&Database
Colorado Avenue	Sisemore Street	US 97 Off-Ramp	City	Minor Arterial	60	42	2	AC	74	Y	N	Y	TSP&Database
Colorado Avenue	Harriman Street	Dead End West	City	Minor Arterial	60	40	2	AC	75	Y	N	Y	TSP&Database
Division Street	US 97	576 ft. s/o US 97	City	Minor Arterial	60-100	36	3	AC	76	Y	Y	P	TSP&Database
Division Street	576 ft. s/o US 97	Yale Avenue	City	Minor Arterial	60-100	48	3	AC	75	Y	Y	P	TSP&Database
Division Street	Yale Avenue	Xerxes Avenue	City	Minor Arterial	60-100	48	3	AC	83	Y	Y	P	TSP&Database
Division Street	Xerxes Avenue	Webster Avenue	City	Minor Arterial	60-100	48	3	AC	80	Y	Y	P	TSP&Database
Division Street	Webster Avenue	Vail Avenue	City	Minor Arterial	60-100	48	3	AC	79	Y	Y	P	TSP&Database
Division Street	Vail Avenue	Underwood Avenue	City	Minor Arterial	60-100	48	3	AC	77	Y	Y	P	TSP&Database
Division Street	Underwood Avenue	Thurston Avenue	City	Minor Arterial	60-100	48	3	AC	80	Y	Y	Y	TSP&Database
Division Street	Thurston Avenue	Revere Avenue	City	Minor Arterial	60-100	48	3	AC	61	Y	Y	Y	TSP&Database
Franklin Avenue	Broadway Street	Wall Street	City	Minor Arterial		45	2	AC	55	Y	N	Y	TSP&Database
Franklin Avenue	Wall Street	Bond Street	City	Minor Arterial	80	45	3-4	AC	56	Y	N	Y	TSP&Database
Franklin Avenue	Bond Street	Lava Road	City	Minor Arterial	80	45	3-4	AC/AC	75	Y	N	Y	TSP&Database
Franklin Avenue	Lava Road	Sisemore Street	City	Minor Arterial	80	43	3-4	AC/AC	81	Y	N	Y	TSP&Database
Franklin Avenue	Sisemore Street	Harriman Street	City	Minor Arterial	80	43	3-4	AC/AC	81	Y	N	Y	TSP&Database
Franklin Avenue	Harriman Street	Hill Street	City	Minor Arterial	80	56	3-4	AC	78	Y	N	Y	TSP&Database
Franklin Avenue	Hill Street	Division Street	City	Minor Arterial	80	44	3-4	AC	71	Y	N	Y	TSP&Database
Franklin Avenue	Division Street	1st Street	City	Minor Arterial	80	43	3-4	AC	80	Y	N	Y	TSP&Database
Franklin Avenue	1st Street	2nd Street	City	Minor Arterial	80	44	3-4	AC	73	Y	N	Y	TSP&Database
Franklin Avenue	2nd Street	3rd Street	City	Minor Arterial	80	44	3-4	AC	71	Y	N	Y	TSP&Database
Franklin Avenue	3rd Street	4th Street	City	Minor Arterial	80	44	3	AC	80	Y	N	Y	TSP&Database
Greenwood Avenue	Wall Street	Bond Street	City	Minor Arterial	80	64	4	AC	41	Y	N	Y	TSP&Database
Greenwood Avenue	Bond Street	Harriman Street	City	Minor Arterial	80	64	4	AC	39	Y	N	Y	TSP&Database

Street Name	Begin	End	Jurisdiction	Functional Classification	ROW Width (feet)	Paved Width (feet)	Number of Lanes	Pavement Type	Pavement Condition (PCI)	Curb	Bike Lane	Sidewalk	Data Source
Greenwood Avenue	Harriman Street	Hill Street	City	Minor Arterial	80	64	4	AC	33	Y	N	Y	TSP&Database
Greenwood Avenue	Hill Street	Parkway	City	Minor Arterial	80	64	4	AC	64	Y	N	Y	TSP&Database
Greenwood Avenue	Parkway	3rd Street	City	Minor Arterial	80	56	4	AC		Y	N	Y	TSP&Database
Hill Street	Revere Avenue	Portland Avenue	City	Minor Arterial	60-80	60	3-4	AC	83	Y	Y	P	TSP&Database
Hill Street	Portland Avenue	Norton Avenue	City	Minor Arterial	80-85	60	2-3	AC	84	Y	Y	P	TSP&Database
Newport Avenue	3rd Street	Awbrey Road	City	Minor Arterial	60-80	36	2-3	AC	84	Y	Y	Y	TSP&Database
Newport Avenue	Awbrey Road	Drake Road	City	Minor Arterial	60	36	2-3	AC	78	Y	Y	Y	TSP&Database
Newport Avenue	Drake Road	Brooks Street	City	Minor Arterial	60	36	2-3	AC	15	Y	Y	Y	TSP&Database
Newport Avenue	Brooks Street	Walls Street	City	Minor Arterial	60	56	2-3	AC	40	Y	Y	Y	TSP&Database
Olney Avenue	Hill Street	1st Street	City	Minor Arterial	60	48	2-3	AC	73	Y	Y	Y	TSP&Database
Olney Avenue	1st Street	2nd Street	City	Minor Arterial	60	46	2-3	AC	74	Y	Y	Y	TSP&Database
Olney Avenue	2nd Street	3rd Street	City	Minor Arterial	60	46	2-3	AC	90	Y	Y	Y	TSP&Database
Olney Avenue	3rd Street	4th Street	City	Minor Arterial	60	36	2	AC	89	Y	Y	N	TSP&Database
Olney Avenue	4th Street	5th Street	City	Minor Arterial	60	36	2	AC	89	Y	Y	N	TSP&Database
Portland Avenue	Steidl Road	Hill Street	City	Major Collector	60-80	36	2	AC/AC	70	Y	N	P	TSP&Database
Revere Avenue	Beginning of Pvmt	Harriman Street	City	Minor Arterial		16	2	AC	83	N	N	N	TSP&Database
Revere Avenue	Harriman Street	Hill Street	City	Minor Arterial		36	2	AC	21	N	N	N	TSP&Database
Revere Avenue	Hill Street	Parkway	City	Minor Arterial	80	65	4	AC	70	Y	Y	Y	TSP&Database
Revere Avenue	Parkway	Division Street	City	Minor Arterial	80	65	4	AC	74	Y	Y	Y	TSP&Database
Revere Avenue	Division Street	Lytle Street	City	Minor Arterial	80	48	4-5	AC	72	Y	N	Y	TSP&Database
Revere Avenue	Lytle Street	2nd Street	City	Minor Arterial	80	60	4-5	AC	83	Y	N	Y	TSP&Database
Revere Avenue	2nd Street	3rd Street	City	Minor Arterial	80	60	4-5	AC	81	Y	N	Y	TSP&Database
Revere Avenue	3rd Street	4th Street	City	Minor Arterial	80	60	4-5	AC	83	Y	N	Y	TSP&Database
Revere Avenue	4th Street	5th Street	City	Minor Arterial	80	36	2	AC	87	N	Y	P	TSP&Database
Riverside Avenue	Broadway Street	Louisiana Avenue	City	Minor Arterial	80	40	2	AC	84	P	Y	P	TSP&Database
Riverside Avenue	Louisiana Avenue	Kansas Avenue	City	Minor Arterial	80	40	2	AC	81	P	Y	P	TSP&Database
Riverside Avenue	Kansas Avenue	Idaho Avenue	City	Minor Arterial	80	40	2	AC	83	P	Y	P	TSP&Database
Riverside Avenue	Idaho Avenue	Tumalo Avenue	City	Minor Arterial	80	40	2	AC	81	P	Y	P	TSP&Database
Wall Street	Norton Avenue	Lafayette Avenue	City	Minor Arterial	80-85	56	2-3	AC/AC	91	Y	Y	P	TSP&Database
Wall Street	Lafayette Avenue	Bond Street	City	Minor Arterial	80-85	56	2-3	AC/AC	92	Y	Y	P	TSP&Database
Wall Street	Bond Street	Greenwood Avenue	City	Minor Arterial	80-85	56	2-3	AC/AC	93	Y	Y	P	TSP&Database
Wall Street	Greenwood Avenue	Oregon Avenue	City	Minor Arterial	80	56	2-3	AC/AC	91	Y	N	Y	TSP&Database
Wall Street	Oregon Avenue	Minnesota Avenue	City	Minor Arterial	80	56	2-3	AC/AC	91	Y	N	Y	TSP&Database
Wall Street	Minnesota Avenue	Franklin Avenue	City	Minor Arterial	80	56	2-3	AC/AC	90	Y	N	Y	TSP&Database
Wall Street	Franklin Avenue	Louisiana Avenue	City	Major Collector	60-80	56	2	AC	83	Y	N	Y	TSP&Database
Wall Street	Louisiana Avenue	Kansas Avenue	City	Major Collector	60-80	56	2	AC	89	Y	N	Y	TSP&Database
Wall Street	Kansas Avenue	Idaho Avenue	City	Major Collector	60-80	56	2	AC	89	Y	N	Y	TSP&Database
Wall Street	Idaho Avenue	Georgia Avenue	City	Major Collector	60-80	30	2	AC	89	Y	N	Y	TSP&Database

Street Name	Begin	End	Jurisdiction	Functional Classification	ROW Width (feet)	Paved Width (feet)	Number of Lanes	Pavement Type	Pavement Condition (PCI)	Curb	Bike Lane	Sidewalk	Data Source
Wall Street	Georgia Avenue	Florida Avenue	City	Major Collector	60-80	30	2	AC	85	Y	N	Y	TSP&Database
Wall Street	Florida Avenue	Delaware Avenue	City	Major Collector	60-80	36	2	AC	85	Y	N	Y	TSP&Database
Wall Street	Delaware Avenue	Colorado Avenue	City	Major Collector	60-80	36	2	AC	78	Y	N	Y	TSP&Database
Wall Street	Colorado Avenue	Arizona Avenue	City	Major Collector	60-80	36	2	AC	90	Y	N	Y	TSP&Database
Wall Street	Arizona Avenue	Industrial Way	City	Major Collector	60-80	36	2	AC	95	Y	N	Y	TSP&Database

**APPENDIX B**

---


**Existing Intersection Geometrics**

# LANE GEOMETRY


Date: 1/9/07

Time: \_\_\_\_\_

Intersection Name: US 97/20 and Butler Market Road



**Staging:**



**Queuing Problems:**


Blank area for identifying queuing problems.

**Saturation Flow Check**

Direction	Vehicles	Seconds	Lanes

Cycle Length: green 53.63      red 41.74  
 Cycle Length: 44.06      38.28  
 Cycle Length: 48.68      52.86

**ROR per cycle**



**Perceived LOS**


**A B C D E F**

# LANE GEOMETRY

Date: 1/9/07

Time: \_\_\_\_\_

Intersection Name: Parkway SB Ramp and Revere Avenue



**Staging:**



**Queuing Problems:**

**Saturation Flow Check**

Direction	Vehicles	Seconds	Lanes

Cycle Length: \_\_\_\_\_  
 Cycle Length: \_\_\_\_\_  
 Cycle Length: \_\_\_\_\_

**ROR per cycle**




Perceived LOS					
A	B	C	D	E	F

# LANE GEOMETRY


Date: 1/8/07

Time: \_\_\_\_\_

Intersection Name: Parkway NB Ramp and Revere Avenue



**Staging:**




**Queuing Problems:**

**Saturation Flow Check**

Direction	Vehicles	Seconds	Lanes

Cycle Length: \_\_\_\_\_  
 Cycle Length: \_\_\_\_\_  
 Cycle Length: \_\_\_\_\_

**ROR per cycle**





Perceived LOS					
A	B	C	D	E	F

# LANE GEOMETRY

Date: 1/9/07

Time: \_\_\_\_\_

Intersection Name: 3rd Street and Revere Avenue




**Queuing Problems:**

**Saturation Flow Check**

Direction	Vehicles	Seconds	Lanes

Cycle Length: \_\_\_\_\_  
 Cycle Length: \_\_\_\_\_  
 Cycle Length: \_\_\_\_\_

**ROR per cycle**



Perceived LOS					
A	B	C	D	E	F




# LANE GEOMETRY


Date: 1/9/07

Time: \_\_\_\_\_

Intersection Name: 3rd Street and Olney Avenue



**Staging:**




**Queuing Problems:**

**Saturation Flow Check**

Direction	Vehicles	Seconds	Lanes

Cycle Length: \_\_\_\_\_  
 Cycle Length: \_\_\_\_\_  
 Cycle Length: \_\_\_\_\_

**ROR per cycle**



**Perceived LOS**


**A B C D E F**

# LANE GEOMETRY


Date: 1/9/07

Time: \_\_\_\_\_

Intersection Name: Greenwood Avenue and Wall Street



## Staging:



## Queuing Problems:


Blank area for describing queuing problems.

## Saturation Flow Check

Direction	Vehicles	Seconds	Lanes

Cycle Length: \_\_\_\_\_  
 Cycle Length: \_\_\_\_\_  
 Cycle Length: \_\_\_\_\_

## ROR per cycle



## Perceived LOS


**A B C D E F**

# LANE GEOMETRY


Date: 1/9/07

Time: \_\_\_\_\_

Intersection Name: Greenwood Avenue and Bond Street



**Staging:**



**Queuing Problems:**

**Saturation Flow Check**


Direction	Vehicles	Seconds	Lanes

Cycle Length: \_\_\_\_\_

Cycle Length: \_\_\_\_\_

Cycle Length: \_\_\_\_\_

**ROR per cycle**



**Perceived LOS**

**A B C D E F**








# LANE GEOMETRY


Date: 1/9/07

Time: \_\_\_\_\_

Intersection Name: Franklin Avenue and Wall Street



**Staging:**




**Queuing Problems:**

**Saturation Flow Check**

Direction	Vehicles	Seconds	Lanes

Cycle Length: \_\_\_\_\_  
 Cycle Length: \_\_\_\_\_  
 Cycle Length: \_\_\_\_\_

**ROR per cycle**




Perceived LOS					
A	B	C	D	E	F

# LANE GEOMETRY


Date: 1/8/07

Time: \_\_\_\_\_

Intersection Name: Franklin Avenue and Bond Street



### Staging:



### Queuing Problems:


Blank area for queuing problems.

### Saturation Flow Check

Direction	Vehicles	Seconds	Lanes

Cycle Length: green red  
 25.44 53.44  
 Cycle Length: 24.39 53.79  
 Cycle Length: 25.12 53.99

### ROR per cycle



### Perceived LOS


**A B C D E F**

# LANE GEOMETRY


Date: 1/8/07

Time: \_\_\_\_\_

Intersection Name: Franklin Avenue and 3rd Street



**Staging:**



**Queuing Problems:**




**Saturation Flow Check**

Direction	Vehicles	Seconds	Lanes

Cycle Length: green red  
 52.73 1:21.69  
 Cycle Length: 54.07 1:10.70  
 Cycle Length: 54.87 1:18.69

**ROR per cycle**



**Perceived LOS**


<b>A</b>	<b>B</b>	<b>C</b>	<b>D</b>	<b>E</b>	<b>F</b>
----------	----------	----------	----------	----------	----------

# LANE GEOMETRY


Date: 1/8/07

Time: \_\_\_\_\_

Intersection Name: Colorado Avenue and Wall Street



**Staging:**




**Queuing Problems:**

**Saturation Flow Check**

Direction	Vehicles	Seconds	Lanes

Cycle Length: \_\_\_\_\_  
 Cycle Length: \_\_\_\_\_  
 Cycle Length: \_\_\_\_\_

**ROR per cycle**




Perceived LOS					
A	B	C	D	E	F

# LANE GEOMETRY


Date: 1/8/07

Time: \_\_\_\_\_

Intersection Name: Colorado Avenue and Bowd Street



**Staging:**



**Queuing Problems:**

**Saturation Flow Check**


Direction	Vehicles	Seconds	Lanes

Cycle Length: \_\_\_\_\_

Cycle Length: \_\_\_\_\_

Cycle Length: \_\_\_\_\_

**ROR per cycle**




Perceived LOS					
A	B	C	D	E	F

# LANE GEOMETRY


Date: 1/8/07

Time: \_\_\_\_\_

Intersection Name: Arizona Avenue and Wall Street



**Staging:**




**Queuing Problems:**

**Saturation Flow Check**

Direction	Vehicles	Seconds	Lanes

Cycle Length: \_\_\_\_\_  
 Cycle Length: \_\_\_\_\_  
 Cycle Length: \_\_\_\_\_

**ROR per cycle**




Perceived LOS					
A	B	C	D	E	F

# LANE GEOMETRY


Date: 1/8/07

Time: \_\_\_\_\_

Intersection Name: Arizona Avenue and Bond Street



**Staging:**




**Queuing Problems:**

**Saturation Flow Check**

Direction	Vehicles	Seconds	Lanes

Cycle Length: \_\_\_\_\_  
 Cycle Length: \_\_\_\_\_  
 Cycle Length: \_\_\_\_\_

**ROR per cycle**




Perceived LOS					
A	B	C	D	E	F

# LANE GEOMETRY


Date: 1/8/07

Time: \_\_\_\_\_

Intersection Name: Parkway SB Ramp and Colorado Avenue



**Staging:**




**Queuing Problems:**

**Saturation Flow Check**

Direction	Vehicles	Seconds	Lanes

Cycle Length: \_\_\_\_\_  
 Cycle Length: \_\_\_\_\_  
 Cycle Length: \_\_\_\_\_

**ROR per cycle**




Perceived LOS					
A	B	C	D	E	F

# LANE GEOMETRY

Date: 1/8/07

Time: \_\_\_\_\_

Intersection Name: Butler Market Road and Parkway SB Ramp



**Staging:**


**Queuing Problems:**

**Saturation Flow Check**


Direction	Vehicles	Seconds	Lanes

Cycle Length: \_\_\_\_\_

Cycle Length: \_\_\_\_\_

Cycle Length: \_\_\_\_\_

**ROR per cycle**



**Perceived LOS**


<b>A</b>	<b>B</b>	<b>C</b>	<b>D</b>	<b>E</b>	<b>F</b>
----------	----------	----------	----------	----------	----------

# LANE GEOMETRY

Date: 1/9/07

Time: \_\_\_\_\_

Intersection Name: Parkway NB Ramp and Butler Market Road



**Staging:**


**Queuing Problems:**

**Saturation Flow Check**


Direction	Vehicles	Seconds	Lanes

Cycle Length: \_\_\_\_\_

Cycle Length: \_\_\_\_\_

Cycle Length: \_\_\_\_\_

**ROR per cycle**



**Perceived LOS**


**A B C D E F**

# LANE GEOMETRY

Date: 1/9/07

Time: \_\_\_\_\_

Intersection Name: 4th Street and Butler Market Road



**Staging:**


**Queuing Problems:**

**Saturation Flow Check**


Direction	Vehicles	Seconds	Lanes

Cycle Length: \_\_\_\_\_

Cycle Length: \_\_\_\_\_

Cycle Length: \_\_\_\_\_

**ROR per cycle**



**Perceived LOS**


A	B	C	D	E	F
---	---	---	---	---	---

# LANE GEOMETRY

Date: 1/9/07

Time: \_\_\_\_\_

Intersection Name: 4th Street and Studio Road



**Staging:**



**Queuing Problems:**

**Saturation Flow Check**

Direction	Vehicles	Seconds	Lanes

Cycle Length: \_\_\_\_\_  
 Cycle Length: \_\_\_\_\_  
 Cycle Length: \_\_\_\_\_

**ROR per cycle**



**Perceived LOS**


A	B	C	D	E	F
---	---	---	---	---	---

# LANE GEOMETRY

Date: 1/9/07

Time: \_\_\_\_\_

Intersection Name: 4th Street and Revere Avenue



**Staging:**



**Queuing Problems:**

**Saturation Flow Check**

Direction	Vehicles	Seconds	Lanes

Cycle Length: \_\_\_\_\_  
 Cycle Length: \_\_\_\_\_  
 Cycle Length: \_\_\_\_\_

**ROR per cycle**



**Perceived LOS**


**A B C D E F**

# LANE GEOMETRY

Date: 1/9/07

Time: \_\_\_\_\_

Intersection Name: 4th Street and Olney Avenue



**Staging:**


**Queuing Problems:**

**Saturation Flow Check**


Direction	Vehicles	Seconds	Lanes

Cycle Length: \_\_\_\_\_

Cycle Length: \_\_\_\_\_

Cycle Length: \_\_\_\_\_

**ROR per cycle**



**Perceived LOS**


A B C D E F

# LANE GEOMETRY

Date: 1/4/07

Time: \_\_\_\_\_

Intersection Name: Parkway SB and Lafayette Avenue



**Staging:**


**Queuing Problems:**

**Saturation Flow Check**


Direction	Vehicles	Seconds	Lanes

Cycle Length: \_\_\_\_\_

Cycle Length: \_\_\_\_\_

Cycle Length: \_\_\_\_\_

**ROR per cycle**



**Perceived LOS**


A B C D E F

# LANE GEOMETRY

Date: 1/9/07

Time: \_\_\_\_\_

Intersection Name: Wall Street and Bond Street



**Staging:**


**Queuing Problems:**

**Saturation Flow Check**


Direction	Vehicles	Seconds	Lanes

Cycle Length: \_\_\_\_\_

Cycle Length: \_\_\_\_\_

Cycle Length: \_\_\_\_\_

**ROR per cycle**




Perceived LOS					
A	B	C	D	E	F

# LANE GEOMETRY

Date: 1/8/07

Time: \_\_\_\_\_

Intersection Name: Greenwood Avenue and 4th Street



**Staging:**



**Queuing Problems:**

**Saturation Flow Check**

Direction	Vehicles	Seconds	Lanes

Cycle Length: \_\_\_\_\_  
 Cycle Length: \_\_\_\_\_  
 Cycle Length: \_\_\_\_\_

**ROR per cycle**



**Perceived LOS**

A	B	C	D	E	F
---	---	---	---	---	---




# LANE GEOMETRY

Date: 1/9/07

Time: \_\_\_\_\_

Intersection Name: Wall Street and Bond Street



**Staging:**


**Queuing Problems:**

**Saturation Flow Check**


Direction	Vehicles	Seconds	Lanes

Cycle Length: \_\_\_\_\_

Cycle Length: \_\_\_\_\_

Cycle Length: \_\_\_\_\_

**ROR per cycle**




Perceived LOS					
A	B	C	D	E	F

# LANE GEOMETRY

Date: 1/8/07

Time: \_\_\_\_\_

Intersection Name: Greenwood Avenue and 4th Street



**Staging:**


**Queuing Problems:**

**Saturation Flow Check**

Direction	Vehicles	Seconds	Lanes

Cycle Length: \_\_\_\_\_  
 Cycle Length: \_\_\_\_\_  
 Cycle Length: \_\_\_\_\_

**ROR per cycle**


**Perceived LOS**


**A B C D E F**

# LANE GEOMETRY

Date: 1/8/07

Time: \_\_\_\_\_

Intersection Name: Hawthorne Avenue and 3rd Street



**Staging:**



**Queuing Problems:**

**Saturation Flow Check**

Direction	Vehicles	Seconds	Lanes

Cycle Length: \_\_\_\_\_  
 Cycle Length: \_\_\_\_\_  
 Cycle Length: \_\_\_\_\_

**ROR per cycle**




Perceived LOS					
A	B	C	D	E	F

# LANE GEOMETRY

Date: 1/8/07

Time: \_\_\_\_\_

Intersection Name: Hawthorne Avenue and 4th Street



**Staging:**


**Queuing Problems:**

**Saturation Flow Check**

Direction	Vehicles	Seconds	Lanes

Cycle Length: \_\_\_\_\_  
 Cycle Length: \_\_\_\_\_  
 Cycle Length: \_\_\_\_\_

**ROR per cycle**


**Perceived LOS**


<b>A</b>	<b>B</b>	<b>C</b>	<b>D</b>	<b>E</b>	<b>F</b>
----------	----------	----------	----------	----------	----------

# LANE GEOMETRY

Date: 1/8/09

Time: \_\_\_\_\_

Intersection Name: SB Parkway and Hawthorne Avenue



**Staging:**



**Queuing Problems:**

**Saturation Flow Check**

Direction	Vehicles	Seconds	Lanes

Cycle Length: \_\_\_\_\_  
 Cycle Length: \_\_\_\_\_  
 Cycle Length: \_\_\_\_\_

**ROR per cycle**



**Perceived LOS**


A B C D E F

# LANE GEOMETRY

Date: 1/8/07

Time: \_\_\_\_\_

Intersection Name: NE 4th Street and NE Franklin Avenue



**Staging:**


**Queuing Problems:**

**Saturation Flow Check**


Direction	Vehicles	Seconds	Lanes

Cycle Length: \_\_\_\_\_

Cycle Length: \_\_\_\_\_

Cycle Length: \_\_\_\_\_

**ROR per cycle**



**Perceived LOS**


A	B	C	D	E	F
---	---	---	---	---	---

# LANE GEOMETRY

Date: 1/2/07

Time: \_\_\_\_\_

Intersection Name: Riverside Drive and Tumalo Avenue




**Staging:**


**Saturation Flow Check**

Direction	Vehicles	Seconds	Lanes

Cycle Length: \_\_\_\_\_  
 Cycle Length: \_\_\_\_\_  
 Cycle Length: \_\_\_\_\_

**ROR per cycle**



**Queuing Problems:**

**Perceived LOS**


**A B C D E F**

# LANE GEOMETRY

Date: 1/8/07

Time: \_\_\_\_\_

Intersection Name: Parkway NB Ramp and Colorado Avenue



**Staging:**



**Queuing Problems:**

**Saturation Flow Check**

Direction	Vehicles	Seconds	Lanes

Cycle Length: \_\_\_\_\_  
 Cycle Length: \_\_\_\_\_  
 Cycle Length: \_\_\_\_\_

**ROR per cycle**



Perceived LOS					
A	B	C	D	E	F

**APPENDIX C**

---

**Existing Intersection Photographs**



**Arizona Avenue @ Wall Street:**  
Looking north through intersection from  
the west side of Wall Street.  
*bend 057.jpg*



**Arizona Avenue @ Wall Street:**  
Looking south through intersection from  
northwest corner.  
*bend 058.jpg*



**Arizona Avenue @ Wall Street:**  
Looking east through intersection from south side  
of Arizona Avenue.  
*bend 059.jpg*



**Arizona Avenue @ Wall Street:**  
Looking east through intersection along north  
side of Arizona Avenue.  
*bend 060.jpg*



**Arizona Avenue @ Bond Street:**  
Looking north through intersection from  
along Bond Street.  
*bend 045.jpg*



**Arizona Avenue @ Bond Street:**  
Looking west along north side of Arizona Avenue.  
*bend 046.jpg*



**Arizona Avenue @ Bond Street:**  
Looking east through intersection from  
northwest corner.  
*bend 047.jpg*



**Arizona Avenue @ Bond Street:**  
Looking north through intersection from  
southeast corner.  
*bend 048.jpg*



**Butler Market Road @ US 97/20:**  
Looking north through intersection from east side  
of US 97/20.  
*bend 069.jpg*



**Butler Market Road @ US 97/20:**  
Looking west along Butler Market Road from  
north side.  
*bend 070.jpg*



**Butler Market Road @ US 97/20:**  
Looking south through intersection from  
northwest side of US 97/20.  
*bend 071.jpg*



**Butler Market Road @ US 97/20:**  
Looking east through intersection from  
south side of Butler Market Road.  
*bend 072.jpg*



**Butler Market Road @ Parkway SB Ramp:**  
Looking west through intersection from south east corner of intersection.  
*bend 065.jpg*




**Butler Market Road @ Parkway SB Ramp:**  
Looking north through intersection from south side of Butler Market Road.  
*bend 066.jpg*



**Butler Market Road @ Parkway SB Ramp:**  
Looking east through intersection from north side of Butler Market Road.  
*bend 067.jpg*



**Butler Market Road @ US 97/20:**  
Looking west through intersection from southeast corner.  
*bend 068.jpg*



**Butler Market Road @ Parkway NB Ramp:**  
Looking north through intersection from south of intersection.  
*bend 061.jpg*



**Butler Market Road @ Parkway NB Ramp:**  
Looking east through intersection from south side of Butler Market Road.  
*bend 062.jpg*



**Butler Market Road @ Parkway NB Ramp:**  
Looking east through intersection from the northwest corner.  
*bend 063.jpg*



**Butler Market Road @ Parkway NB Ramp:**  
Close-up looking east through intersection the northwest corner.  
*bend 064.jpg*



**Butler Market Road @ 4<sup>th</sup> Street:**  
Looking south through intersection along  
4<sup>th</sup> Street.  
*bend 085.jpg*



**Butler Market Road @ 4<sup>th</sup> Street:**  
Looking east through intersection from  
north side of Butler Market Road.  
*bend 086.jpg*



**Butler Market Road @ 4<sup>th</sup> Street:**  
Looking south through intersection from  
northeast corner.  
*bend 084.jpg*



**Colorado Avenue @ Wall Street:**  
Looking east through intersection from  
south side of Colorado Avenue.  
*bend 053.jpg*



**Colorado Avenue @ Wall Street:**  
Looking west through intersection from southeast corner.  
*bend 054.jpg*




**Colorado Avenue @ Wall Street:**  
Looking north through intersection along west side of Wall Street.  
*bend 055.jpg*



**Colorado Avenue @ Wall Street:**  
Looking south through intersection from northwest corner.  
*bend 056.jpg*



**Colorado Avenue @ Bond Street:**  
Looking north through intersection from east side of Bond Street.  
*bend 049.jpg*



**Colorado Avenue @ Bond Street:**  
Looking west through intersection from south side of Colorado Avenue.  
*bend 050.jpg*



**Colorado Avenue @ Bond Street:**  
Looking north through intersection from southeast corner.  
*bend 051.jpg*



**Colorado Avenue @ Bond Street:**  
Looking east through intersection from south side of Colorado Avenue.  
*bend 052.jpg*



**Colorado Avenue @ Parkway SB Ramp:**  
Looking south into intersection from west side ramp.  
*bend 038.jpg*



**Colorado Avenue @ Parkway SB Ramp:**  
Looking west into intersection from north side of Colorado Avenue.  
*bend 039.jpg*



**Colorado Avenue @ Parkway SB Ramp:**  
Looking north into intersection from southeast corner.  
*bend 040.jpg*



**Colorado Avenue @ Parkway SB Ramp:**  
Looking east through intersection along south side of Colorado Avenue.  
*bend 041.jpg*



**Colorado Avenue @ Parkway NB Ramp:**  
Looking north through intersection from south side of Colorado Avenue.  
*bend 042.jpg*



**Colorado Avenue @ Parkway NB Ramp:**  
Looking east through intersection from southwest corner.  
*bend 044.jpg*



**Colorado Avenue @ Parkway NB Ramp:**  
Looking west through intersection from northwest corner.  
*bend 043.jpg*



**Franklin Avenue @ Wall Street:**  
Looking south through intersection from west side of Wall Street.  
*bend 136.jpg*



**Franklin Avenue @ Wall Street:**  
Looking west through intersection from northeast corner.  
*bend 137.jpg*



**Franklin Avenue @ Wall Street:**  
Looking south into intersection from east side of Wall Street.  
*bend 138.jpg*



**Franklin Avenue @ Wall Street:**  
Looking east into intersection from south side of Franklin Avenue.  
*bend 139.jpg*



**Franklin Avenue @ Bond Street:**  
Looking west across intersection from northeast side of Franklin Avenue.  
*bend 029.jpg*



**Franklin Avenue @ Bond Street:**  
Looking north through intersection from southwest corner.  
*bend 030.jpg*



**Franklin Avenue @ Bond Street:**  
Looking east through intersection along southwest side of Franklin Avenue.  
*bend 031.jpg*



**Franklin Avenue @ Bond Street:**  
Looking north across intersection from east side of Bond Street.  
*bend 032.jpg*



**Franklin Avenue @ 3<sup>rd</sup> Street:**  
Looking south through intersection from northwest corner.  
*bend 001.jpg*



**Franklin Avenue @ 3<sup>rd</sup> Street:**  
Looking west through intersection from northeast corner.  
*bend 002.jpg*



**Franklin Avenue @ 3<sup>rd</sup> Street:**  
Looking north through intersection from  
southeast corner.  
*bend 003.jpg*



**Franklin Avenue @ 3<sup>rd</sup> Street:**  
Looking east through intersection from  
southwest corner.  
*bend 004.jpg*



**Franklin Avenue @ 3<sup>rd</sup> Street:**  
Looking east at right turn lane from  
southwest corner.  
*bend 005.jpg*



**Franklin Avenue @ 4<sup>th</sup> Street:**  
Looking west through intersection from  
northeast corner.  
*bend 006.jpg*



**Franklin Avenue @ 4<sup>th</sup> Street:**  
Looking south through intersection from north of intersection.  
*bend 007.jpg*



**Franklin Avenue @ 4<sup>th</sup> Street:**  
Looking south through intersection from northwest corner.  
*bend 008.jpg*



**Franklin Avenue @ 4<sup>th</sup> Street:**  
Looking west through intersection from southwest corner.  
*bend 009.jpg*



**Franklin Avenue @ 4<sup>th</sup> Street:**  
Looking north through intersection from the south.  
*bend 010.jpg*



**Greenwood Avenue @ Wall Street:**  
Looking east through intersection from southwest side of Greenwood Avenue.  
*bend 128.jpg*



**Greenwood Avenue @ Wall Street:**  
Looking south through intersection from northwest side of Wall Street.  
*bend 129.jpg*



**Greenwood Avenue @ Wall Street:**  
Looking west through intersection from north side of Greenwood Avenue.  
*bend 130.jpg*



**Greenwood Avenue @ Wall Street:**  
Looking north through intersection from east side of Wall Street.  
*bend 131.jpg*



**Greenwood Avenue @ Bond Street:**  
Looking northwest through intersection from  
east side of Bond Street.  
*bend 119.jpg*



**Greenwood Avenue @ Bond Street:**  
Looking north through intersection from  
east side of Bond Street.  
*bend 120.jpg*



**Greenwood Avenue @ Bond Street:**  
Looking west through intersection from  
north side of Greenwood Avenue.  
*bend 121.jpg*



**Greenwood Avenue @ Bond Street:**  
Looking east into intersection from south side of  
Greenwood Avenue.  
*bend 122.jpg*



**Greenwood Avenue @ Bond Street:**  
Looking north into intersection from west side of intersection.  
*bend 123.jpg*



**Greenwood Avenue @ 3<sup>rd</sup> Street:**  
Looking north through intersection from east side of 3<sup>rd</sup> Street.  
*bend 023.jpg*



**Greenwood Avenue @ 3<sup>rd</sup> Street:**  
Looking east through intersection along south side of Greenwood Avenue.  
*bend 024.jpg*



**Greenwood Avenue @ 3<sup>rd</sup> Street:**  
Sidewalk obstruction looking east along Greenwood Avenue.  
*bend 025.jpg*



**Greenwood Avenue @ 3<sup>rd</sup> Street:**  
Side walk obstruction looking west along  
Greenwood Avenue.  
*bend 026.jpg*



**Greenwood Avenue @ 3<sup>rd</sup> Street:**  
Sidewalk obstruction looking south through  
intersection from northwest side of 3<sup>rd</sup> Street.  
*bend 027.jpg*




**Greenwood Avenue @ 3<sup>rd</sup> Street:**  
Looking west through intersection from  
northeast side of Greenwood Avenue.  
*bend 028.jpg*



**Greenwood Avenue @ 4<sup>th</sup> Street:**  
Looking south through intersection from  
the north corner.  
*bend 019.jpg*



**Greenwood Avenue @ 4<sup>th</sup> Street:**  
Looking west through intersection along north side of Greenwood Avenue.  
*bend 020.jpg*



**Greenwood Avenue @ 4<sup>th</sup> Street:**  
Looking north through intersection from the south.  
*bend 021.jpg*



**Greenwood Avenue @ 4<sup>th</sup> Street:**  
Looking east through intersection along south side of Greenwood Avenue  
*bend 022.jpg*



**Hawthorne Avenue @ SB Parkway:**  
Looking east through intersection from south side of Hawthorne Avenue.  
*bend 073.jpg*



**Hawthorne Avenue @ SB Parkway:**  
Looking north through intersection from southwest corner.  
*bend 074.jpg*



**Hawthorne Avenue @ SB Parkway:**  
Looking south through intersection from northwest corner.  
*bend 075.jpg*



**Hawthorne Avenue @ 3<sup>rd</sup> Street:**  
Looking west through intersection along Hawthorne Avenue.  
*bend 015.jpg*



**Hawthorne Avenue @ 3<sup>rd</sup> Street:**  
Looking north through intersection along east side of 3<sup>rd</sup> Street.  
*bend 016.jpg*



**Hawthorne Avenue @ 3<sup>rd</sup> Street:**  
Looking east through intersection from west of intersection.  
*bend 017.jpg*




**Hawthorne Avenue @ 3<sup>rd</sup> Street:**  
Looking southeast through intersection from northwest corner.  
*bend 018.jpg*



**Hawthorne Avenue @ 4<sup>th</sup> Street:**  
Looking north through intersection from the south.  
*bend 011.jpg*



**Hawthorne Avenue @ 4<sup>th</sup> Street:**  
Looking east through intersection along 4<sup>th</sup> Street.  
*bend 012.jpg*



**Hawthorne Avenue @ 4<sup>th</sup> Street:**  
Looking south through intersection from the north.  
*bend 013.jpg*



**Hawthorne Avenue @ 4<sup>th</sup> Street:**  
Looking west through intersection along Hawthorne Avenue.  
*bend 014.jpg*




**Lafayette Avenue @ Parkway SB Ramp:**  
Looking south through intersection from west side of the Parkway.  
*bend 112.jpg*



**Lafayette Avenue @ Parkway SB Ramp:**  
Looking south through intersection from northwest corner of Lafayette Avenue.  
*bend 113.jpg*



**Lafayette Avenue @ Parkway SB Ramp**  
**Lafayette Avenue:**  
Looking east into intersection from south side of Lafayette Avenue.  
*bend 114.jpg*



**Olney Avenue @ BNSF Railroad Crossing:**  
Looking east through crossing along Olney Avenue.  
*bend 143.jpg*



**Olney Avenue @ 3<sup>rd</sup> Street:**  
Looking west through intersection from north side of Olney Avenue.  
*bend 104.jpg*



**Olney Avenue @ 3<sup>rd</sup> Street:**  
Looking south through intersection from northwest side of 3<sup>rd</sup> Street.  
*bend 105.jpg*



**Olney Avenue @ 3<sup>rd</sup> Street:**  
Looking east into intersection from south side  
Olney Avenue.  
*bend 106.jpg*



**Olney Avenue @ 3<sup>rd</sup> Street:**  
Looking north into intersection from east side of  
Olney Avenue.  
*bend 107.jpg*



**Olney Avenue @ 4<sup>th</sup> Street:**  
Looking north into intersection from southeast  
side of 4<sup>th</sup> Street.  
*bend 100.jpg*



**Olney Avenue @ 4<sup>th</sup> Street:**  
Looking west through intersection along  
north side of Olney Avenue.  
*bend 101.jpg*



**Olney Avenue @ 4<sup>th</sup> Street:**  
Looking south through intersection from west side of 4<sup>th</sup> Street.  
*bend 102.jpg*



**Olney Avenue @ 4<sup>th</sup> Street:**  
Looking east through intersection from south side of Olney Avenue.  
*bend 103.jpg*



**Oregon Avenue @ Wall Street:**  
Looking west into intersection from northeast corner.  
*bend 132.jpg*



**Oregon Avenue @ Wall Street:**  
Looking south through intersection from northeast corner.  
*bend 133.jpg*



**Oregon Avenue @ Wall Street:**  
Looking east through intersection from southwest corner.  
*bend 134.jpg*



**Oregon Avenue @ Wall Street:**  
Looking north through intersection from southwest corner.  
*bend 135.jpg*



**Oregon Avenue @ Bond Street:**  
Looking west into intersection from north side of Oregon Avenue.  
*bend 115.jpg*



**Oregon Avenue @ Bond Street:**  
Looking west into intersection from northeast corner.  
*bend 116.jpg*



**Oregon Avenue @ Bond Street:**  
Looking south through intersection from east side of Oregon Avenue.  
*bend 117.jpg*



**Oregon Avenue @ Bond Street:**  
Looking north through intersection from southwest corner of Oregon Avenue.  
*bend 140.jpg*



**Oregon Avenue @ Bond Street:**  
Looking north through intersection from southwest corner of Oregon Avenue.  
*bend 118.jpg*



**Portland Avenue @ Hill Street:**  
Looking east into intersection from south side of Portland Avenue.  
*bend 108.jpg*



**Portland Avenue @ Hill Street:**  
Looking north through intersection from the south.  
*bend 142.jpg*



**Portland Avenue @ Hill Street:**  
Looking north through intersection along east side of Hill Street.  
*bend 109.jpg*



**Portland Avenue @ Hill Street:**  
Looking east along Olney Avenue approaching the Parkway.  
*bend 141.jpg*



**Portland Avenue @ Hill Street:**  
Looking west through intersection from the median of Portland Avenue.  
*bend 110.jpg*



**Portland Avenue @ Hill Street:**  
Looking south through intersection from west side of Hill Street.  
*bend 111.jpg*



**Parkway SB Ramp @ Revere Avenue:**  
Looking west toward intersection while approaching the Parkway.  
*bend 144.jpg*



**Revere Avenue @ Parkway SB Ramp:**  
Looking west into intersection from north side of Revere Avenue.  
*bend 099.jpg*



**Revere Avenue @ Parkway SB Ramp:**  
Looking south through intersection from west of ramp.  
*bend 096.jpg*



**Revere Avenue @ Parkway SB Ramp:**  
Looking east through intersection from southwest side of Revere Avenue.  
*bend 097.jpg*



**Revere Avenue @ Parkway SB Ramp:**  
Looking north into intersection from east side.  
*bend 098.jpg*



**Revere Avenue @ Parkway NB Ramp:**  
Looking west into intersection from north side of Revere Avenue.  
*bend 091.jpg*



**Revere Avenue @ Parkway NB Ramp:**  
Looking south into ramp from northeast corner.  
*bend 092.jpg*



**Revere Avenue @ Parkway NB Ramp:**  
Looking south through intersection from the north.  
*bend 093.jpg*



**Revere Avenue @ Parkway NB Ramp:**  
Looking east through intersection from south side of Revere Avenue.  
*bend 094.jpg*



**Revere Avenue @ Parkway NB Ramp:**  
Looking south through intersection from ramp.  
*bend 095.jpg*



**Revere Avenue @ Parkway NB Ramp:**  
Looking west toward BNSF Railroad Crossing from north side of Revere Avenue.  
*bend 145.jpg*



**Revere Avenue @ 3<sup>rd</sup> Street:**  
Looking west through intersection from  
north side of Revere Avenue.  
*bend 087.jpg*



**Revere Avenue @ 3<sup>rd</sup> Street:**  
Looking north through intersection from  
east side of 3<sup>rd</sup> Street.  
*bend 088.jpg*



**Revere Avenue @ 3<sup>rd</sup> Street:**  
Looking east through intersection from  
south side of Revere Avenue.  
*bend 089.jpg*



**Revere Avenue @ 3<sup>rd</sup> Street:**  
Looking south into intersection from west side 3<sup>rd</sup>  
Street.  
*bend 090.jpg*



**Revere Avenue @ 4<sup>th</sup> Street:**  
Looking north through intersection from  
along Revere Avenue.  
*bend 081.jpg*



**Revere Avenue @ 4<sup>th</sup> Street:**  
Looking west through intersection from north side  
of Revere Avenue.  
*bend 082.jpg*



**Revere Avenue @ 4<sup>th</sup> Street:**  
Looking east through intersection from south side  
of Revere Avenue.  
*bend 083.jpg*



**Revere Avenue @ 4<sup>th</sup> Street:**  
Looking south through intersection along west  
side 4<sup>th</sup> Street.  
*bend 080.jpg*



**Riverside Boulevard @ Tumalo Avenue:**  
Looking north through intersection along  
Riverside Boulevard.  
*bend 033.jpg*



**Riverside Boulevard @ Tumalo Avenue:**  
Looking east along east side of Tumalo Avenue.  
*bend 034.jpg*



**Riverside Boulevard @ Tumalo Avenue:**  
Looking west through intersection along south  
side of Tumalo Avenue.  
*bend 035.jpg*



**Riverside Boulevard @ Tumalo Avenue:**  
Looking south through intersection along west  
side Riverside Boulevard.  
*bend 036.jpg*



**Riverside Boulevard @ Tumalo Avenue:**

Looking east through intersection from northwest side of Tumalo Avenue.

*bend 037.jpg*



**Studio Road @ 4<sup>th</sup> Street:**

Looking south through intersection from west side of 4<sup>th</sup> Street.

*bend 076.jpg*



**Studio Road @ 4<sup>th</sup> Street:**

Looking southwest through intersection along Studio Road.

*bend 077.jpg*




**Studio Road @ 4<sup>th</sup> Street:**

Looking north through intersection along east side of 4<sup>th</sup> Street.

*bend 078.jpg*



**Studio Road @ 4<sup>th</sup> Street:**  
Looking northeast through intersection from southeast corner.  
*bend 079.jpg*



**Wall Street @ Bond Avenue:**  
Looking north into intersection from southwest corner.  
*bend 124.jpg*



**Wall Street @ Bond Avenue:**  
Looking east through intersection from pedestrian crossing.  
*bend 125.jpg*





**Wall Street @ Bond Avenue:**  
Looking south through intersection from west side of Wall Street.  
*bend 126.jpg*



**Wall Street @ Bond Avenue:**

Looking west through intersection from east side of intersection.

*bend 127.jpg*



**APPENDIX D**

---

**2006 PM Peak Hour Traffic Counts**



## Intersection Turning Movement Summary Report

**Location** BUTLER MARKET ROAD AT US 97/20  
**Date** 1/2/2007  
**Day of Week** Tuesday  
**Time Begin** 16:00  
**Reviewed By:** JW

Time Period	Eastbound			Westbound			Northbound			Southbound			Totals
	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	
16:00 - 16:15	24	290	33	33	161	18	25	36	10	32	15	67	744
16:15 - 16:30	14	270	30	25	207	18	28	20	18	32	24	74	760
16:30 - 16:45	15	252	46	24	145	16	38	29	17	30	29	76	717
16:45 - 17:00	22	216	38	24	183	25	19	21	15	42	20	66	691
17:00 - 17:15	11	227	39	39	171	25	21	31	11	29	35	75	714
17:15 - 17:30	27	215	38	30	180	19	27	19	13	23	21	47	659
17:30 - 17:45	12	188	32	31	130	18	20	15	9	30	20	60	565
17:45 - 18:00	16	169	21	26	127	20	14	14	16	23	16	52	514
<b>Movement Totals</b>	<b>141</b>	<b>1827</b>	<b>277</b>	<b>232</b>	<b>1304</b>	<b>159</b>	<b>192</b>	<b>185</b>	<b>109</b>	<b>241</b>	<b>180</b>	<b>517</b>	<b>5364</b>
Enter Totals	2245			1695			486			938			
Exit Totals	2536			1654			694			480			

### Two-Hour Totals

Light Trucks	1	23	0	2	17	0	4	4	0	0	0	7	58
Medium Trucks	1	4	1	1	0	0	0	0	0	1	0	0	8
Heavy Trucks	0	16	4	1	4	0	1	0	0	1	0	5	32
% Trucks	1.4%	2.4%	1.8%	1.7%	1.6%	0.0%	2.6%	2.2%	0.0%	0.8%	0.0%	2.3%	1.8%
Stopped Buses	0	0	0	0	0	0	0	0	0	0	0	0	0
Bicycles	0	2	1	0	0	0	0	0	0	0	1	0	4

	South	West	East	North	
Pedestrians	7	0	0	0	7

### Peak Hour Information

**Peak Hour 16:00 17:00**

	Eastbound			Westbound			Northbound			Southbound			Totals
	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	
Movement Total	75	1028	147	106	696	77	110	106	60	136	88	283	2912
Peak Hour Factor	0.78	0.89	0.80	0.80	0.84	0.77	0.72	0.74	0.83	0.81	0.76	0.93	0.96

Enter Totals	1250	879	276	507
Peak Hour Factor	0.90	0.88	0.82	0.94

Exit Totals	1421	892	359	240
Peak Hour Factor	0.93	0.87	0.88	0.90

Light Trucks	0	13	0	1	7	0	1	2	0	0	0	6	30
Medium Trucks	0	2	1	0	0	0	0	0	0	1	0	0	4
Heavy Trucks	0	10	1	1	1	0	1	0	0	1	0	2	17
% Trucks	0.0%	2.4%	1.4%	1.9%	1.1%	0.0%	1.8%	1.9%	0.0%	1.5%	0.0%	2.8%	1.8%
Stopped Buses	0	0	0	0	0	0	0	0	0	0	0	0	0
Bicycles	0	1	1	0	0	0	0	0	0	0	1	0	3

	South	West	East	North	
Pedestrians	5	0	0	0	5

## Intersection Turning Movement Peak Hour Diagram


**Location** BUTLER MARKET ROAD AT US 97/20

**Date** 1/2/2007

**Day of Week** Tuesday

**Time Begin** 16:00

**Reviewed By:** JW





## Intersection Turning Movement Summary Report

**Location** NE REVERE AVENUE AT BEND PARKWAY SB RAMPS

**Date** 1/2/2007

**Day of Week** Tuesday

**Time Begin** 16:00

**Reviewed By:** BM

Time Period	Eastbound			Westbound			Northbound			Southbound			Totals
	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	
16:00 - 16:15	0	7	1	68	11	102	126	26	0	2	37	41	421
16:15 - 16:30	2	4	4	68	6	98	119	24	2	4	49	30	410
16:30 - 16:45	1	1	4	58	5	139	99	16	1	0	47	29	400
16:45 - 17:00	1	1	1	57	3	87	113	21	4	0	37	34	359
17:00 - 17:15	2	4	0	69	2	109	164	21	4	0	31	47	453
17:15 - 17:30	4	3	3	58	9	85	132	30	2	4	53	30	413
17:30 - 17:45	1	2	1	55	2	77	114	16	4	0	45	31	348
17:45 - 18:00	2	7	0	31	15	94	81	8	11	0	52	22	323
<b>Movement Totals</b>	<b>13</b>	<b>29</b>	<b>14</b>	<b>464</b>	<b>53</b>	<b>791</b>	<b>948</b>	<b>162</b>	<b>28</b>	<b>10</b>	<b>351</b>	<b>264</b>	<b>3127</b>
Enter Totals	56			1308			1138			625			
Exit Totals	1241			91			640			1155			

**Two-Hour Totals**

Light Trucks	0	0	0	4	0	7	9	1	0	0	1	2	24
Medium Trucks	0	0	0	0	0	0	0	0	0	0	0	1	1
Heavy Trucks	0	0	0	0	0	0	0	0	0	0	0	2	2
% Trucks	0.0%	0.0%	0.0%	0.9%	0.0%	0.9%	0.9%	0.6%	0.0%	0.0%	0.3%	1.9%	0.9%
Stopped Buses	0	0	0	0	0	0	0	0	0	0	0	0	0
Bicycles	0	2	0	0	4	0	0	0	0	0	0	0	6

	South	West	East	North	
Pedestrians	0	2	2	5	9

### Peak Hour Information

**Peak Hour 16:30 17:30**

	Eastbound			Westbound			Northbound			Southbound			Totals
	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	
Movement Total	8	9	8	242	19	420	508	88	11	4	168	140	1625
Peak Hour Factor	0.50	0.56	0.50	0.88	0.53	0.76	0.77	0.73	0.69	0.25	0.79	0.74	0.90

Enter Totals	25			681			607			312		
Peak Hour Factor	0.63			0.84			0.80			0.90		

Exit Totals	657			34			338			596		
Peak Hour Factor	0.76			0.57			0.93			0.80		

Light Trucks	0	0	0	3	0	2	4	0	0	0	0	1	10
Medium Trucks	0	0	0	0	0	0	0	0	0	0	0	1	1
Heavy Trucks	0	0	0	0	0	0	0	0	0	0	0	0	0
% Trucks	0.0%	0.0%	0.0%	1.2%	0.0%	0.5%	0.8%	0.0%	0.0%	0.0%	0.0%	1.4%	0.7%
Stopped Buses	0	0	0	0	0	0	0	0	0	0	0	0	0
Bicycles	0	0	0	0	1	0	0	0	0	0	0	0	1

	South	West	East	North	
Pedestrians	0	0	2	1	3

## Intersection Turning Movement Peak Hour Diagram


**Location** NE REVERE AVENUE AT BEND PARKWAY SB RAMPS

**Date** 1/2/2007

**Day of Week** Tuesday

**Time Begin** 16:00

**Reviewed By:** BM





## Intersection Turning Movement Summary Report

**Location** NE REVERE AVENUE AT BEND PARKWAY NB RAMPS

**Date** 1/2/2007

**Day of Week** Tuesday

**Time Begin** 16:00

**Reviewed By:** TM

Time Period	Eastbound			Westbound			Northbound			Southbound			Totals
	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	
16:00 - 16:15	63	82	26	13	92	12	85	40	20	56	2	21	512
16:15 - 16:30	71	59	33	17	81	4	88	31	19	53	3	21	480
16:30 - 16:45	72	66	21	20	97	13	98	46	32	60	2	23	550
16:45 - 17:00	66	59	33	26	70	9	98	52	16	50	0	22	501
17:00 - 17:15	107	81	34	25	100	9	116	72	15	52	0	22	633
17:15 - 17:30	67	75	18	24	99	8	93	65	16	37	1	21	524
17:30 - 17:45	53	63	32	19	61	5	68	46	15	47	2	10	421
17:45 - 18:00	52	43	21	12	55	4	54	40	14	57	1	6	359
<b>Movement Totals</b>	<b>551</b>	<b>528</b>	<b>218</b>	<b>156</b>	<b>655</b>	<b>64</b>	<b>700</b>	<b>392</b>	<b>147</b>	<b>412</b>	<b>11</b>	<b>146</b>	<b>3980</b>
Enter Totals	1297			875			1239			569			
Exit Totals	1374			1214			766			626			

**Two-Hour Totals**

Light Trucks	12	9	12	8	12	0	17	16	0	9	1	5	101
Medium Trucks	0	2	0	0	1	0	4	0	0	0	0	0	7
Heavy Trucks	0	2	0	0	0	0	0	1	0	0	1	0	4
% Trucks	2.2%	2.5%	5.5%	5.1%	2.0%	0.0%	3.0%	4.3%	0.0%	2.2%	18.2%	3.4%	2.8%
Stopped Buses	0	0	0	0	0	0	0	0	0	0	0	0	0
Bicycles	0	0	0	1	0	0	1	0	0	0	0	0	2

Pedestrians	South 0	West 0	East 0	North 0	0
-------------	------------	-----------	-----------	------------	---

### Peak Hour Information

**Peak Hour 16:30 17:30**

	Eastbound			Westbound			Northbound			Southbound			Totals
	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	
Movement Total	312	281	106	95	366	39	405	235	79	199	3	88	2208
Peak Hour Factor	0.73	0.87	0.78	0.91	0.92	0.75	0.87	0.82	0.62	0.83	0.38	0.96	0.87

Enter Totals	699			500			719			290		
Peak Hour Factor	0.79			0.93			0.89			0.85		

Exit Totals	774			644			436			354		
Peak Hour Factor	0.88			0.85			0.83			0.76		

Light Trucks	2	7	7	4	6	0	11	8	0	3	0	3	51
Medium Trucks	0	1	0	0	1	0	2	0	0	0	0	0	4
Heavy Trucks	0	0	0	0	0	0	0	1	0	0	1	0	2
% Trucks	0.6%	2.8%	6.6%	4.2%	1.9%	0.0%	3.2%	3.8%	0.0%	1.5%	33.3%	3.4%	2.6%
Stopped Buses	0	0	0	0	0	0	0	0	0	0	0	0	0
Bicycles	0	0	0	1	0	0	1	0	0	0	0	0	2

Pedestrians	South 0	West 0	East 0	North 0	0
-------------	------------	-----------	-----------	------------	---

## Intersection Turning Movement Peak Hour Diagram


**Location** NE REVERE AVENUE AT BEND PARKWAY NB RAMPS

**Date** 1/2/2007

**Day of Week** Tuesday

**Time Begin** 16:00

**Reviewed By:** TM





## Intersection Turning Movement Summary Report

**Location** NE REVERE AVENUE AT NE 3RD STREET

**Date** 1/2/2007

**Day of Week** Tuesday

**Time Begin** 16:00

**Reviewed By:** JW

Time Period	Eastbound			Westbound			Northbound			Southbound			Totals
	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	
16:00 - 16:15	46	98	53	8	61	38	31	261	25	17	187	14	839
16:15 - 16:30	34	89	53	11	71	44	11	256	22	13	149	13	766
16:30 - 16:45	51	86	46	14	65	37	18	226	25	8	154	13	743
16:45 - 17:00	44	91	38	15	65	38	18	213	17	14	131	16	700
17:00 - 17:15	48	128	53	6	61	51	24	214	24	11	145	12	777
17:15 - 17:30	42	101	48	9	54	29	25	235	22	16	98	12	691
17:30 - 17:45	41	52	44	9	47	44	25	199	17	8	103	7	596
17:45 - 18:00	20	58	32	12	39	31	22	166	14	6	90	11	501
<b>Movement Totals</b>	<b>326</b>	<b>703</b>	<b>367</b>	<b>84</b>	<b>463</b>	<b>312</b>	<b>174</b>	<b>1770</b>	<b>166</b>	<b>93</b>	<b>1057</b>	<b>98</b>	<b>5613</b>
Enter Totals	1396			859			2110			1248			
Exit Totals	975			722			2221			1695			

### Two-Hour Totals

Light Trucks	1	5	2	1	5	2	0	24	2	0	20	0	62
Medium Trucks	1	1	0	0	0	0	0	1	1	0	2	0	6
Heavy Trucks	1	4	0	0	0	1	0	15	0	0	16	0	37
% Trucks	0.9%	1.4%	0.5%	1.2%	1.1%	1.0%	0.0%	2.3%	1.8%	0.0%	3.6%	0.0%	1.9%
Stopped Buses	0	0	0	0	0	0	0	0	0	0	0	0	0
Bicycles	0	2	0	0	2	0	0	0	0	0	0	0	4

	South 9	West 3	East 3	North 4	19
--	------------	-----------	-----------	------------	----

### Peak Hour Information

**Peak Hour 16:00 17:00**

	Eastbound			Westbound			Northbound			Southbound			Totals
	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	
Movement Total	175	364	190	48	262	157	78	956	89	52	621	56	3048
Peak Hour Factor	0.86	0.93	0.90	0.80	0.92	0.89	0.63	0.92	0.89	0.76	0.83	0.88	0.91

Enter Totals	729			467			1123			729		
Peak Hour Factor	0.93			0.93			0.89			0.84		

Exit Totals	498			403			1194			953		
Peak Hour Factor	0.87			0.95			0.93			0.88		

Light Trucks	1	3	2	1	1	2	0	14	1	0	10	0	35
Medium Trucks	1	1	0	0	0	0	0	1	1	0	1	0	5
Heavy Trucks	1	2	0	0	0	1	0	8	0	0	10	0	22
% Trucks	1.7%	1.6%	1.1%	2.1%	0.4%	1.9%	0.0%	2.4%	2.2%	0.0%	3.4%	0.0%	2.0%
Stopped Buses	0	0	0	0	0	0	0	0	0	0	0	0	0
Bicycles	0	2	0	0	1	0	0	0	0	0	0	0	3

	South 9	West 3	East 2	North 3	17
--	------------	-----------	-----------	------------	----

## Intersection Turning Movement Peak Hour Diagram


**Location** NE REVERE AVENUE AT NE 3RD STREET

**Date** 1/2/2007

**Day of Week** Tuesday

**Time Begin** 16:00

**Reviewed By:** JW





## Intersection Turning Movement Summary Report

**Location** NW PORTLAND AVENUE AT NW HILL STREET

**Date** 1/2/2007

**Day of Week** Tuesday

**Time Begin** 16:00

**Reviewed By:** JW

Time Period	Eastbound			Westbound			Northbound			Southbound			Totals
	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	
16:00 - 16:15	24	50	41	21	48	9	27	81	20	59	72	12	464
16:15 - 16:30	23	47	61	17	54	17	25	86	28	61	65	5	489
16:30 - 16:45	22	31	47	12	45	15	24	73	23	87	73	8	460
16:45 - 17:00	17	30	51	20	34	17	18	86	32	70	56	7	438
17:00 - 17:15	19	48	67	25	78	7	12	122	30	70	54	7	539
17:15 - 17:30	10	46	59	20	52	19	15	90	23	67	62	8	471
17:30 - 17:45	11	38	31	16	51	8	12	80	14	59	51	7	378
17:45 - 18:00	13	27	28	11	56	14	12	62	21	70	60	9	383
Movement Totals	139	317	385	142	418	106	145	680	191	543	493	63	3622
Enter Totals	841			666			1016			1099			
Exit Totals	525			1152			1207			738			

**Two-Hour Totals**

Light Trucks	0	0	4	1	0	0	3	4	0	1	4	0	17
Medium Trucks	0	1	0	0	0	0	0	0	0	0	0	0	1
Heavy Trucks	0	0	0	0	0	0	1	0	0	0	0	0	1
% Trucks	0.0%	0.3%	1.0%	0.7%	0.0%	0.0%	2.8%	0.6%	0.0%	0.2%	0.8%	0.0%	0.5%
Stopped Buses	0	0	0	0	0	0	0	0	0	0	0	0	0
Bicycles	0	2	0	0	5	0	1	1	0	2	3	0	14

Pedestrians	South 6	West 8	East 3	North 5	22
-------------	------------	-----------	-----------	------------	----

### Peak Hour Information

**Peak Hour 16:15 17:15**

	Eastbound			Westbound			Northbound			Southbound			Totals
	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	
Movement Total	81	156	226	74	211	56	79	367	113	288	248	27	1926
Peak Hour Factor	0.88	0.81	0.84	0.74	0.68	0.82	0.79	0.75	0.88	0.83	0.85	0.84	0.89

Enter Totals	463			341			559			563		
Peak Hour Factor	0.86			0.78			0.85			0.84		

Exit Totals	262			612			667			385		
Peak Hour Factor	0.85			0.86			0.78			0.88		

Light Trucks	0	0	2	1	0	0	2	2	0	0	2	0	9
Medium Trucks	0	1	0	0	0	0	0	0	0	0	0	0	1
Heavy Trucks	0	0	0	0	0	0	0	0	0	0	0	0	0
% Trucks	0.0%	0.6%	0.9%	1.4%	0.0%	0.0%	2.5%	0.5%	0.0%	0.0%	0.8%	0.0%	0.5%
Stopped Buses	0	0	0	0	0	0	0	0	0	0	0	0	0
Bicycles	0	1	0	0	4	0	1	1	0	1	2	0	10

Pedestrians	South 4	West 6	East 3	North 4	17
-------------	------------	-----------	-----------	------------	----

## Intersection Turning Movement Peak Hour Diagram


**Location** NW PORTLAND AVENUE AT NW HILL STREET

**Date** 1/2/2007

**Day of Week** Tuesday

**Time Begin** 16:00

**Reviewed By:** JW





## Intersection Turning Movement Summary Report

**Location** NE OLNEY AVENUE AT NE 3RD STREET

**Date** 1/2/2007

**Day of Week** Tuesday

**Time Begin** 16:00

**Reviewed By:** BM

Time Period	Eastbound			Westbound			Northbound			Southbound			Totals
	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	
16:00 - 16:15	21	299	14	4	218	21	18	40	26	14	42	27	744
16:15 - 16:30	15	273	16	5	206	25	20	74	28	11	55	30	758
16:30 - 16:45	20	260	13	6	223	15	19	52	24	20	45	22	719
16:45 - 17:00	20	250	21	4	184	29	21	43	20	12	37	16	657
17:00 - 17:15	27	251	19	1	169	30	18	60	21	18	62	24	700
17:15 - 17:30	11	320	17	4	178	27	17	62	21	15	45	31	748
17:30 - 17:45	17	253	21	5	152	15	14	43	23	18	38	15	614
17:45 - 18:00	21	201	17	7	142	13	25	43	17	9	37	12	544
<b>Movement Totals</b>	<b>152</b>	<b>2107</b>	<b>138</b>	<b>36</b>	<b>1472</b>	<b>175</b>	<b>152</b>	<b>417</b>	<b>180</b>	<b>117</b>	<b>361</b>	<b>177</b>	<b>5484</b>
Enter Totals	2397			1683			749			655			
Exit Totals	2436			1769			591			688			

### Two-Hour Totals

Light Trucks	6	25	0	0	24	1	0	1	7	0	2	1	67
Medium Trucks	0	1	0	0	0	0	0	0	0	0	0	0	1
Heavy Trucks	0	15	0	0	22	0	0	0	0	0	0	1	38
% Trucks	3.9%	1.9%	0.0%	0.0%	3.1%	0.6%	0.0%	0.2%	3.9%	0.0%	0.6%	1.1%	1.9%
Stopped Buses	0	0	0	0	0	0	0	0	0	0	0	0	0
Bicycles	0	0	0	0	1	0	0	1	0	0	4	0	6

Pedestrians	South 4	West 0	East 5	North 2	11
-------------	------------	-----------	-----------	------------	----

### Peak Hour Information

**Peak Hour 16:00 17:00**

	Eastbound			Westbound			Northbound			Southbound			Totals
	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	
Movement Total	76	1082	64	19	831	90	78	209	98	57	179	95	2878
Peak Hour Factor	0.90	0.90	0.76	0.79	0.93	0.78	0.93	0.71	0.88	0.71	0.81	0.79	0.95

Enter Totals	1222			940			385			331		
Peak Hour Factor	0.91			0.96			0.79			0.86		

Exit Totals	1255			986			292			345		
Peak Hour Factor	0.91			0.92			0.77			0.91		

Light Trucks	2	15	0	0	14	0	0	0	4	0	1	1	37
Medium Trucks	0	0	0	0	0	0	0	0	0	0	0	0	0
Heavy Trucks	0	7	0	0	15	0	0	0	0	0	0	1	23
% Trucks	2.6%	2.0%	0.0%	0.0%	3.5%	0.0%	0.0%	0.0%	4.1%	0.0%	0.6%	2.1%	2.1%
Stopped Buses	0	0	0	0	0	0	0	0	0	0	0	0	0
Bicycles	0	0	0	0	1	0	0	1	0	0	4	0	6

Pedestrians	South 2	West 0	East 0	North 1	3
-------------	------------	-----------	-----------	------------	---

## Intersection Turning Movement Peak Hour Diagram


**Location** NE OLNEY AVENUE AT NE 3RD STREET

**Date** 1/2/2007

**Day of Week** Tuesday

**Time Begin** 16:00

**Reviewed By:** BM





## Intersection Turning Movement Summary Report

**Location** NEWPORT AVE-GREENWOOD AVENUE AT WALL STREET

**Date** 1/4/2007

**Day of Week** Thursday

**Time Begin** 16:00

**Reviewed By:** BV

Time Period	Eastbound			Westbound			Northbound			Southbound			Totals
	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	
16:00 - 16:15	15	52	22	6	49	40	0	0	0	20	49	6	259
16:15 - 16:30	28	61	33	8	73	51	0	0	0	23	88	14	379
16:30 - 16:45	37	70	25	8	92	47	0	0	0	25	96	24	424
16:45 - 17:00	22	78	29	6	82	45	0	0	0	37	75	22	396
17:00 - 17:15	25	81	20	2	112	63	0	0	0	39	75	22	439
17:15 - 17:30	24	67	23	3	110	52	0	0	0	36	65	18	398
17:30 - 17:45	29	63	24	4	86	47	0	0	0	29	65	14	361
17:45 - 18:00	24	59	15	1	94	46	0	0	0	27	62	11	339
<b>Movement Totals</b>	<b>204</b>	<b>531</b>	<b>191</b>	<b>38</b>	<b>698</b>	<b>391</b>	<b>0</b>	<b>0</b>	<b>0</b>	<b>236</b>	<b>575</b>	<b>131</b>	<b>2995</b>
Enter Totals	926			1127			0			942			
Exit Totals	662			934			229			1170			

### Two-Hour Totals

Light Trucks	0	16	1	1	10	2	0	0	0	1	5	0	36
Medium Trucks	0	0	0	0	0	0	0	0	0	0	0	0	0
Heavy Trucks	0	0	0	0	0	0	0	0	0	0	0	0	0
% Trucks	0.0%	3.0%	0.5%	2.6%	1.4%	0.5%	NA	NA	NA	0.4%	0.9%	0.0%	1.2%
Stopped Buses	0	0	0	0	0	0	0	0	0	0	0	0	0
Bicycles	0	0	0	0	0	0	0	0	0	0	0	0	0

	South	West	East	North	
Pedestrians	5	10	13	15	43

### Peak Hour Information

**Peak Hour 16:30 17:30**

	Eastbound			Westbound			Northbound			Southbound			Totals
	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	
Movement Total	108	296	97	19	396	207	0	0	0	137	311	86	1657
Peak Hour Factor	0.73	0.91	0.84	0.59	0.88	0.82	NA	NA	NA	0.88	0.81	0.90	0.94

Enter Totals	501			622			0			534		
Peak Hour Factor	0.95			0.88			NA			0.92		

Exit Totals	382			533			116			626		
Peak Hour Factor	0.93			0.88			0.83			0.87		

Light Trucks	0	8	0	1	4	0	0	0	0	1	1	0	15
Medium Trucks	0	0	0	0	0	0	0	0	0	0	0	0	0
Heavy Trucks	0	0	0	0	0	0	0	0	0	0	0	0	0
% Trucks	0.0%	2.7%	0.0%	5.3%	1.0%	0.0%	NA	NA	NA	0.7%	0.3%	0.0%	0.9%
Stopped Buses	0	0	0	0	0	0	0	0	0	0	0	0	0
Bicycles	0	0	0	0	0	0	0	0	0	0	0	0	0

	South	West	East	North	
Pedestrians	1	6	2	6	15

## Intersection Turning Movement Peak Hour Diagram


**Location** NEWPORT AVE-GREENWOOD AVENUE AT WALL STREET

**Date** 1/4/2007

**Day of Week** Thursday

**Time Begin** 16:00

**Reviewed By:** BV





## Intersection Turning Movement Summary Report

**Location** GREENWOOD AVENUE AT BOND STREET  
**Date** 1/3/2007  
**Day of Week** Wednesday  
**Time Begin** 16:00  
**Reviewed By:** JW

Time Period	Eastbound			Westbound			Northbound			Southbound			Totals
	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	
16:00 - 16:15	0	70	2	14	114	0	66	79	41	0	0	0	386
16:15 - 16:30	0	87	3	12	116	0	66	86	44	0	0	0	414
16:30 - 16:45	0	76	2	10	134	0	60	76	37	0	0	0	395
16:45 - 17:00	0	97	0	14	100	0	59	73	44	0	0	0	387
17:00 - 17:15	0	86	4	8	141	0	66	73	45	0	0	0	423
17:15 - 17:30	0	71	2	12	101	0	57	63	45	0	0	0	351
17:30 - 17:45	0	78	1	11	98	0	50	40	38	0	0	0	316
17:45 - 18:00	0	49	1	4	93	0	46	42	48	0	0	0	283
Movement Totals	0	614	15	85	897	0	470	532	342	0	0	0	2955
Enter Totals	629			982			1344			0			
Exit Totals	1084			1239			632			0			

### Two-Hour Totals

Light Trucks	0	8	0	0	8	0	4	5	1	0	0	0	26
Medium Trucks	0	2	0	0	0	0	0	1	0	0	0	0	3
Heavy Trucks	0	0	0	0	0	0	0	0	0	0	0	0	0
% Trucks	NA	1.6%	0.0%	0.0%	0.9%	NA	0.9%	1.1%	0.3%	NA	NA	NA	1.0%
Stopped Buses	0	0	0	0	0	0	0	0	0	0	0	0	0
Bicycles	0	0	0	0	0	0	0	0	0	0	0	0	0

	South 11	West 5	East 18	North 5	39
--	-------------	-----------	------------	------------	----

### Peak Hour Information

**Peak Hour 16:15 17:15**

	Eastbound			Westbound			Northbound			Southbound			Totals
	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	
Movement Total	0	346	9	44	491	0	251	308	170	0	0	0	1619
Peak Hour Factor	NA	0.89	0.56	0.79	0.87	NA	0.95	0.90	0.94	NA	NA	NA	0.96

Enter Totals	355			535			729			0		
Peak Hour Factor	0.91			0.90			0.93			NA		

Exit Totals	597			661			361			0		
Peak Hour Factor	0.96			0.89			0.89			NA		

Light Trucks	0	5	0	0	5	0	4	3	0	0	0	0	17
Medium Trucks	0	1	0	0	0	0	0	0	0	0	0	0	1
Heavy Trucks	0	0	0	0	0	0	0	0	0	0	0	0	0
% Trucks	NA	1.7%	0.0%	0.0%	1.0%	NA	1.6%	1.0%	0.0%	NA	NA	NA	1.1%
Stopped Buses	0	0	0	0	0	0	0	0	0	0	0	0	0
Bicycles	0	0	0	0	0	0	0	0	0	0	0	0	0

	South 8	West 4	East 11	North 5	28
--	------------	-----------	------------	------------	----

## Intersection Turning Movement Peak Hour Diagram


**Location** GREENWOOD AVENUE AT BOND STREET

**Date** 1/3/2007

**Day of Week** Wednesday

**Time Begin** 16:00

**Reviewed By:** JW





## Intersection Turning Movement Summary Report

**Location** NE GREENWOOD AVENUE AT NE 3RD STREET

**Date** 1/4/2007

**Day of Week** Thursday

**Time Begin** 16:00

**Reviewed By:** BV

Time Period	Eastbound			Westbound			Northbound			Southbound			Totals
	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	
16:00 - 16:15	21	121	50	59	100	60	51	167	21	30	152	62	894
16:15 - 16:30	25	123	58	57	100	66	50	163	28	25	128	47	870
16:30 - 16:45	27	129	48	61	99	48	46	170	32	17	148	56	881
16:45 - 17:00	23	138	54	41	99	48	60	169	32	19	110	56	849
17:00 - 17:15	21	178	59	50	116	49	47	156	15	15	118	60	884
17:15 - 17:30	18	136	55	53	93	55	37	155	32	10	108	43	795
17:30 - 17:45	20	113	39	62	107	40	42	142	24	18	113	50	770
17:45 - 18:00	16	94	33	64	89	32	48	117	19	20	119	46	697
<b>Movement Totals</b>	<b>171</b>	<b>1032</b>	<b>396</b>	<b>447</b>	<b>803</b>	<b>398</b>	<b>381</b>	<b>1239</b>	<b>203</b>	<b>154</b>	<b>996</b>	<b>420</b>	<b>6640</b>
Enter Totals	1599			1648			1823			1570			
Exit Totals	1833			1160			2082			1565			

### Two-Hour Totals

Light Trucks	3	23	8	5	5	3	3	20	4	1	20	13	108
Medium Trucks	0	0	1	0	2	2	0	1	0	0	1	1	8
Heavy Trucks	0	1	1	11	0	2	2	3	0	0	0	10	30
% Trucks	1.8%	2.3%	2.5%	3.6%	0.9%	1.8%	1.3%	1.9%	2.0%	0.6%	2.1%	5.7%	2.2%
Stopped Buses	0	0	0	0	0	0	0	0	0	0	0	0	0
Bicycles	0	0	0	0	0	0	0	0	0	0	0	0	0

	South	West	East	North	
Pedestrians	5	1	4	1	11

### Peak Hour Information

**Peak Hour 16:00 17:00**

	Eastbound			Westbound			Northbound			Southbound			Totals
	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	
Movement Total	96	511	210	218	398	222	207	669	113	91	538	221	3494
Peak Hour Factor	0.89	0.93	0.91	0.89	1.00	0.84	0.86	0.98	0.88	0.76	0.88	0.89	0.98

Enter Totals	817			838			989			850		
Peak Hour Factor	0.95			0.94			0.95			0.87		

Exit Totals	939			602			1097			856		
Peak Hour Factor	0.92			0.98			0.98			0.92		

Light Trucks	3	14	5	2	5	2	2	11	2	1	11	6	64
Medium Trucks	0	0	0	0	1	2	0	1	0	0	0	0	4
Heavy Trucks	0	1	1	5	0	1	1	3	0	0	0	2	14
% Trucks	3.1%	2.9%	2.9%	3.2%	1.5%	2.3%	1.4%	2.2%	1.8%	1.1%	2.0%	3.6%	2.3%
Stopped Buses	0	0	0	0	0	0	0	0	0	0	0	0	0
Bicycles	0	0	0	0	0	0	0	0	0	0	0	0	0

	South	West	East	North	
Pedestrians	4	1	2	1	8

## Intersection Turning Movement Peak Hour Diagram


**Location** NE GREENWOOD AVENUE AT NE 3RD STREET

**Date** 1/4/2007

**Day of Week** Thursday

**Time Begin** 16:00

**Reviewed By:** BV





## Intersection Turning Movement Summary Report

**Location** NW OREGON AVENUE AT NW WALL STREET

**Date** 1/3/2007

**Day of Week** Wednesday

**Time Begin** 16:00

**Reviewed By:** TM

Time Period	Eastbound			Westbound			Northbound			Southbound			Totals
	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	
16:00 - 16:15	3	3	0	0	7	40	1	0	0	13	134	17	218
16:15 - 16:30	1	7	0	0	13	30	0	0	0	10	132	30	223
16:30 - 16:45	6	6	0	0	15	36	0	0	0	6	152	17	238
16:45 - 17:00	4	2	0	0	8	52	0	0	0	11	145	28	250
17:00 - 17:15	7	3	0	0	12	33	0	0	0	9	164	17	245
17:15 - 17:30	6	3	0	0	12	38	0	0	0	11	119	16	205
17:30 - 17:45	6	7	0	0	4	26	0	0	0	9	101	11	164
17:45 - 18:00	7	5	0	0	9	20	0	0	0	10	97	16	164
<b>Movement Totals</b>	<b>40</b>	<b>36</b>	<b>0</b>	<b>0</b>	<b>80</b>	<b>275</b>	<b>1</b>	<b>0</b>	<b>0</b>	<b>79</b>	<b>1044</b>	<b>152</b>	<b>1707</b>
Enter Totals	76			355			1			1275			
Exit Totals	189			159			0			1359			

### Two-Hour Totals

Light Trucks	0	0	0	0	0	9	0	0	0	2	25	4	40
Medium Trucks	0	0	0	0	0	0	0	0	0	0	0	0	0
Heavy Trucks	0	0	0	0	0	0	0	0	0	0	0	0	0
% Trucks	0.0%	0.0%	NA	NA	0.0%	3.3%	0.0%	NA	NA	2.5%	2.4%	2.6%	2.3%
Stopped Buses	0	0	0	0	0	0	0	0	0	0	0	0	0
Bicycles	0	0	0	0	0	0	0	0	0	0	0	0	0

	South	West	East	North	
Pedestrians	0	1	0	0	1

### Peak Hour Information

**Peak Hour 16:15 17:15**

	Eastbound			Westbound			Northbound			Southbound			Totals
	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	
Movement Total	18	18	0	0	48	151	0	0	0	36	593	92	956
Peak Hour Factor	0.64	0.64	NA	NA	0.80	0.73	NA	NA	NA	0.82	0.90	0.77	0.96

Enter Totals	36			199			0			721		
Peak Hour Factor	0.75			0.83			NA			0.95		

Exit Totals	110			84			0			762		
Peak Hour Factor	0.74			0.91			NA			0.93		

Light Trucks	0	0	0	0	0	7	0	0	0	1	11	1	20
Medium Trucks	0	0	0	0	0	0	0	0	0	0	0	0	0
Heavy Trucks	0	0	0	0	0	0	0	0	0	0	0	0	0
% Trucks	0.0%	0.0%	NA	NA	0.0%	4.6%	NA	NA	NA	2.8%	1.9%	1.1%	2.1%
Stopped Buses	0	0	0	0	0	0	0	0	0	0	0	0	0
Bicycles	0	0	0	0	0	0	0	0	0	0	0	0	0

	South	West	East	North	
Pedestrians	0	0	0	0	0

## Intersection Turning Movement Peak Hour Diagram


**Location** NW OREGON AVENUE AT NW WALL STREET

**Date** 1/3/2007

**Day of Week** Wednesday

**Time Begin** 16:00

**Reviewed By:** TM





## Intersection Turning Movement Summary Report

**Location** NW OREGON AVENUE AT NW BOND STREET

**Date** 1/3/2007

**Day of Week** Wednesday

**Time Begin** 16:00

**Reviewed By:** BV

Time Period	Eastbound			Westbound			Northbound			Southbound			Totals
	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	
16:00 - 16:15	0	15	20	25	19	0	27	144	29	0	0	0	279
16:15 - 16:30	0	24	23	27	16	0	27	152	26	0	0	0	295
16:30 - 16:45	0	18	17	27	12	0	13	147	42	0	0	0	276
16:45 - 17:00	0	26	25	31	19	0	20	139	37	0	0	0	297
17:00 - 17:15	0	14	12	35	22	0	17	137	23	0	0	0	260
17:15 - 17:30	0	7	15	19	24	0	8	125	35	0	0	0	233
17:30 - 17:45	0	8	27	26	9	0	9	102	17	0	0	0	198
17:45 - 18:00	0	9	15	24	13	0	3	116	20	0	0	0	200
<b>Movement Totals</b>	0	121	154	214	134	0	124	1062	229	0	0	0	2038
Enter Totals	275			348			1415			0			
Exit Totals	245			363			1430			0			

### Two-Hour Totals

Light Trucks	0	0	0	6	0	0	1	10	0	0	0	0	17
Medium Trucks	0	0	0	0	0	0	0	1	0	0	0	0	1
Heavy Trucks	0	0	0	0	0	0	0	0	0	0	0	0	0
% Trucks	NA	0.0%	0.0%	2.8%	0.0%	NA	0.8%	1.0%	0.0%	NA	NA	NA	0.9%
Stopped Buses	0	0	0	0	0	0	0	0	0	0	0	0	0
Bicycles	0	0	0	0	0	0	0	0	0	0	0	0	0

	South 49	West 56	East 89	North 32	226
--	-------------	------------	------------	-------------	-----

### Peak Hour Information

**Peak Hour 16:00 17:00**

	Eastbound			Westbound			Northbound			Southbound			Totals
	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	
Movement Total	0	83	85	110	66	0	87	582	134	0	0	0	1147
Peak Hour Factor	NA	0.80	0.85	0.89	0.87	NA	0.81	0.96	0.80	NA	NA	NA	0.97

Enter Totals	168			176			803			0		
Peak Hour Factor	0.82			0.88			0.98			NA		

Exit Totals	170			200			777			0		
Peak Hour Factor	0.83			0.89			0.96			NA		

Light Trucks	0	0	0	4	0	0	0	9	0	0	0	0	13
Medium Trucks	0	0	0	0	0	0	0	1	0	0	0	0	1
Heavy Trucks	0	0	0	0	0	0	0	0	0	0	0	0	0
% Trucks	NA	0.0%	0.0%	3.6%	0.0%	NA	0.0%	1.7%	0.0%	NA	NA	NA	1.2%
Stopped Buses	0	0	0	0	0	0	0	0	0	0	0	0	0
Bicycles	0	0	0	0	0	0	0	0	0	0	0	0	0

	South 32	West 33	East 56	North 13	134
--	-------------	------------	------------	-------------	-----

## Intersection Turning Movement Peak Hour Diagram


**Location** NW OREGON AVENUE AT NW BOND STREET

**Date** 1/3/2007

**Day of Week** Wednesday

**Time Begin** 16:00

**Reviewed By:** BV





## Intersection Turning Movement Summary Report

**Location** NW FRANKLIN AVENUE AT NW WALL STREET

**Date** 1/3/2007

**Day of Week** Wednesday

**Time Begin** 16:00

**Reviewed By:** JW

Time Period	Eastbound			Westbound			Northbound			Southbound			Totals
	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	
16:00 - 16:15	1	87	0	0	58	49	0	0	0	47	85	36	363
16:15 - 16:30	5	76	0	0	69	30	0	0	0	42	81	36	339
16:30 - 16:45	5	99	0	0	66	30	0	0	0	41	73	39	353
16:45 - 17:00	6	76	0	0	66	30	0	0	0	67	91	36	372
17:00 - 17:15	5	78	0	0	77	34	0	0	0	43	104	49	390
17:15 - 17:30	2	87	0	0	68	35	0	0	0	39	72	35	338
17:30 - 17:45	8	59	0	0	69	34	0	0	0	40	62	32	304
17:45 - 18:00	7	63	0	0	43	30	0	0	0	37	54	22	256
<b>Movement Totals</b>	<b>39</b>	<b>625</b>	<b>0</b>	<b>0</b>	<b>516</b>	<b>272</b>	<b>0</b>	<b>0</b>	<b>0</b>	<b>356</b>	<b>622</b>	<b>285</b>	<b>2715</b>
Enter Totals	664			788			0			1263			
Exit Totals	910			872			0			933			

### Two-Hour Totals

Light Trucks	1	10	0	0	6	5	0	0	0	4	3	2	31
Medium Trucks	0	1	0	0	0	0	0	0	0	0	0	0	1
Heavy Trucks	0	0	0	0	1	1	0	0	0	0	0	0	2
% Trucks	2.6%	1.8%	NA	NA	1.4%	2.2%	NA	NA	NA	1.1%	0.5%	0.7%	1.3%
Stopped Buses	0	0	0	0	0	0	0	0	0	0	0	0	0
Bicycles	0	0	0	0	2	0	0	0	0	1	2	0	5

	South 22	West 10	East 56	North 79	167
--	-------------	------------	------------	-------------	-----

### Peak Hour Information

**Peak Hour 16:15 17:15**

	Eastbound			Westbound			Northbound			Southbound			Totals
	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	
Movement Total	21	329	0	0	278	124	0	0	0	193	349	160	1454
Peak Hour Factor	0.88	0.83	NA	NA	0.90	0.91	NA	NA	NA	0.72	0.84	0.82	0.93

Enter Totals	350			402			0			702		
Peak Hour Factor	0.84			0.91			NA			0.90		

Exit Totals	489			471			0			494		
Peak Hour Factor	0.89			0.89			NA			0.86		

Light Trucks	1	7	0	0	3	2	0	0	0	2	1	1	17
Medium Trucks	0	1	0	0	0	0	0	0	0	0	0	0	1
Heavy Trucks	0	0	0	0	1	1	0	0	0	0	0	0	2
% Trucks	4.8%	2.4%	NA	NA	1.4%	2.4%	NA	NA	NA	1.0%	0.3%	0.6%	1.4%
Stopped Buses	0	0	0	0	0	0	0	0	0	0	0	0	0
Bicycles	0	0	0	0	0	0	0	0	0	0	0	0	0

	South 15	West 5	East 30	North 38	88
--	-------------	-----------	------------	-------------	----

## Intersection Turning Movement Peak Hour Diagram


**Location** NW FRANKLIN AVENUE AT NW WALL STREET

**Date** 1/3/2007

**Day of Week** Wednesday

**Time Begin** 16:00

**Reviewed By:** JW





## Intersection Turning Movement Summary Report

**Location** NE FRANKLIN AVENUE AT NW BOND STREET

**Date** 1/3/2007

**Day of Week** Wednesday

**Time Begin** 16:00

**Reviewed By:** JW

Time Period	Eastbound			Westbound			Northbound			Southbound			Totals
	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	
16:00 - 16:15	0	65	52	20	98	0	62	118	14	0	0	0	429
16:15 - 16:30	0	71	45	23	85	0	52	122	10	0	0	0	408
16:30 - 16:45	0	89	46	23	86	0	55	128	8	0	0	0	435
16:45 - 17:00	0	66	51	17	84	0	42	101	18	0	0	0	379
17:00 - 17:15	0	81	40	19	103	0	54	126	8	0	0	0	431
17:15 - 17:30	0	76	47	11	88	0	46	96	13	0	0	0	377
17:30 - 17:45	0	59	34	15	88	0	33	83	10	0	0	0	322
17:45 - 18:00	0	52	26	11	67	0	30	78	12	0	0	0	276
<b>Movement Totals</b>	0	559	341	139	699	0	374	852	93	0	0	0	3057
Enter Totals	900			838			1319			0			
Exit Totals	933			792			1332			0			

### Two-Hour Totals

Light Trucks	0	8	2	0	11	0	8	4	0	0	0	0	33
Medium Trucks	0	1	0	0	0	0	0	1	0	0	0	0	2
Heavy Trucks	0	0	0	0	1	0	0	0	0	0	0	0	1
% Trucks	NA	1.6%	0.6%	0.0%	1.7%	NA	2.1%	0.6%	0.0%	NA	NA	NA	1.2%
Stopped Buses	0	0	0	0	0	0	0	0	0	0	0	0	0
Bicycles	0	0	0	0	1	0	0	0	0	0	0	0	1

	South 16	West 38	East 45	North 32	131
--	-------------	------------	------------	-------------	-----

### Peak Hour Information

**Peak Hour 16:15 17:15**

	Eastbound			Westbound			Northbound			Southbound			Totals
	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	
Movement Total	0	307	182	82	358	0	203	477	44	0	0	0	1653
Peak Hour Factor	NA	0.86	0.89	0.89	0.87	NA	0.92	0.93	0.61	NA	NA	NA	0.95

Enter Totals	489			440			724			0		
Peak Hour Factor	0.91			0.90			0.95			NA		

Exit Totals	510			402			741			0		
Peak Hour Factor	0.89			0.91			0.94			NA		

Light Trucks	0	5	1	0	5	0	5	3	0	0	0	0	19
Medium Trucks	0	1	0	0	0	0	0	0	0	0	0	0	1
Heavy Trucks	0	0	0	0	1	0	0	0	0	0	0	0	1
% Trucks	NA	2.0%	0.5%	0.0%	1.7%	NA	2.5%	0.6%	0.0%	NA	NA	NA	1.3%
Stopped Buses	0	0	0	0	0	0	0	0	0	0	0	0	0
Bicycles	0	0	0	0	0	0	0	0	0	0	0	0	0

	South 9	West 18	East 19	North 13	59
--	------------	------------	------------	-------------	----

## Intersection Turning Movement Peak Hour Diagram


**Location** NE FRANKLIN AVENUE AT NW BOND STREET

**Date** 1/3/2007

**Day of Week** Wednesday

**Time Begin** 16:00

**Reviewed By:** JW





## Intersection Turning Movement Summary Report

**Location** NE FRANKLIN AVENUE AT NE 3RD STREET

**Date** 1/4/2007

**Day of Week** Thursday

**Time Begin** 16:00

**Reviewed By:** TM

Time Period	Eastbound			Westbound			Northbound			Southbound			Totals
	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	
16:00 - 16:15	24	93	64	9	75	41	14	176	26	26	203	16	767
16:15 - 16:30	20	110	64	12	70	21	5	147	33	24	197	17	720
16:30 - 16:45	23	102	67	17	66	32	5	244	26	27	230	21	860
16:45 - 17:00	17	88	53	12	77	28	9	181	30	16	174	12	697
17:00 - 17:15	23	162	59	7	88	45	13	161	35	25	170	29	817
17:15 - 17:30	15	99	55	10	76	27	8	124	17	20	109	17	577
17:30 - 17:45	10	71	51	13	57	39	9	159	15	20	146	11	601
17:45 - 18:00	21	51	37	11	45	28	5	166	20	12	125	8	529
<b>Movement Totals</b>	<b>153</b>	<b>776</b>	<b>450</b>	<b>91</b>	<b>554</b>	<b>261</b>	<b>68</b>	<b>1358</b>	<b>202</b>	<b>170</b>	<b>1354</b>	<b>131</b>	<b>5568</b>
Enter Totals	1379			906			1628			1655			
Exit Totals	975			926			1899			1768			

### Two-Hour Totals

Light Trucks	8	22	29	0	19	7	2	32	12	5	31	13	180
Medium Trucks	0	0	0	0	1	0	0	1	0	0	1	1	4
Heavy Trucks	0	0	1	0	0	0	0	6	3	0	4	0	14
% Trucks	5.2%	2.8%	6.7%	0.0%	3.6%	2.7%	2.9%	2.9%	7.4%	2.9%	2.7%	10.7%	3.6%
Stopped Buses	0	0	0	0	0	0	0	0	0	0	0	0	0
Bicycles	0	0	0	0	1	0	0	0	0	0	1	0	2

	South	West	East	North	
Pedestrians	0	0	0	0	0

### Peak Hour Information

**Peak Hour 16:15 17:15**

	Eastbound			Westbound			Northbound			Southbound			Totals
	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	
Movement Total	83	462	243	48	301	126	32	733	124	92	771	79	3094
Peak Hour Factor	0.90	0.71	0.91	0.71	0.86	0.70	0.62	0.75	0.89	0.85	0.84	0.68	0.90

Enter Totals	788			475			889			942		
Peak Hour Factor	0.81			0.85			0.81			0.85		

Exit Totals	573			517			1024			980		
Peak Hour Factor	0.70			0.87			0.78			0.86		

Light Trucks	6	15	16	0	11	3	2	14	6	3	15	9	100
Medium Trucks	0	0	0	0	1	0	0	1	0	0	1	1	4
Heavy Trucks	0	0	1	0	0	0	0	6	1	0	3	0	11
% Trucks	7.2%	3.2%	7.0%	0.0%	4.0%	2.4%	6.3%	2.9%	5.6%	3.3%	2.5%	12.7%	3.7%
Stopped Buses	0	0	0	0	0	0	0	0	0	0	0	0	0
Bicycles	0	0	0	0	1	0	0	0	0	0	1	0	2

	South	West	East	North	
Pedestrians	0	0	0	0	0

## Intersection Turning Movement Peak Hour Diagram


**Location** NE FRANKLIN AVENUE AT NE 3RD STREET

**Date** 1/4/2007

**Day of Week** Thursday

**Time Begin** 16:00

**Reviewed By:** TM





## Intersection Turning Movement Summary Report

**Location** COLORADO AVENUE AT WALL STREET

**Date** 1/3/2007

**Day of Week** Wednesday

**Time Begin** 16:00

**Reviewed By:** TM

Time Period	Eastbound			Westbound			Northbound			Southbound			Totals
	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	
16:00 - 16:15	0	0	0	0	96	28	0	0	0	40	95	0	259
16:15 - 16:30	0	0	0	0	108	20	0	0	0	29	80	0	237
16:30 - 16:45	0	0	0	0	106	18	0	0	0	26	77	0	227
16:45 - 17:00	0	0	0	0	103	22	0	0	0	30	71	0	226
17:00 - 17:15	0	0	0	0	120	21	0	0	0	29	109	0	279
17:15 - 17:30	0	0	0	0	111	11	0	0	0	35	70	0	227
17:30 - 17:45	0	0	0	0	78	17	0	0	0	25	80	0	200
17:45 - 18:00	0	0	0	0	61	11	0	0	0	19	59	0	150
<b>Movement Totals</b>	0	0	0	0	783	148	0	0	0	233	641	0	1805
Enter Totals	0			931			0			874			
Exit Totals	0			1016			0			789			

### Two-Hour Totals

Light Trucks	0	0	0	0	20	3	0	0	0	4	17	0	44
Medium Trucks	0	0	0	0	2	0	0	0	0	0	0	0	2
Heavy Trucks	0	0	0	0	1	0	0	0	0	0	0	0	1
% Trucks	NA	NA	NA	NA	2.9%	2.0%	NA	NA	NA	1.7%	2.7%	NA	2.6%
Stopped Buses	0	0	0	0	0	0	0	0	0	0	0	0	0
Bicycles	0	0	0	0	0	0	0	0	0	0	0	0	0

	South	West	East	North	
Pedestrians	0	0	0	0	0

### Peak Hour Information

**Peak Hour 16:15 17:15**

	Eastbound			Westbound			Northbound			Southbound			Totals
	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	
Movement Total	0	0	0	0	437	81	0	0	0	114	337	0	969
Peak Hour Factor	NA	NA	NA	NA	0.91	0.92	NA	NA	NA	0.95	0.77	NA	0.87

Enter Totals	0			518			0			451		
Peak Hour Factor	NA			0.92			NA			0.82		

Exit Totals	0			551			0			418		
Peak Hour Factor	NA			0.92			NA			0.80		

Light Trucks	0	0	0	0	11	1	0	0	0	4	9	0	25
Medium Trucks	0	0	0	0	1	0	0	0	0	0	0	0	1
Heavy Trucks	0	0	0	0	1	0	0	0	0	0	0	0	1
% Trucks	NA	NA	NA	NA	3.0%	1.2%	NA	NA	NA	3.5%	2.7%	NA	2.8%
Stopped Buses	0	0	0	0	0	0	0	0	0	0	0	0	0
Bicycles	0	0	0	0	0	0	0	0	0	0	0	0	0

	South	West	East	North	
Pedestrians	0	0	0	0	0

## Intersection Turning Movement Peak Hour Diagram


**Location** COLORADO AVENUE AT WALL STREET

**Date** 1/3/2007

**Day of Week** Wednesday

**Time Begin** 16:00

**Reviewed By:** TM





## Intersection Turning Movement Summary Report

**Location** COLORADO AVENUE AT BOND STREET

**Date** 1/3/2007

**Day of Week** Wednesday

**Time Begin** 16:00

**Reviewed By:** TM

Time Period	Eastbound			Westbound			Northbound			Southbound			Totals
	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	
16:00 - 16:15	0	0	0	29	108	0	0	110	9	0	0	0	256
16:15 - 16:30	0	0	0	23	119	0	0	122	18	0	0	0	282
16:30 - 16:45	0	0	0	25	105	0	0	142	12	0	0	0	284
16:45 - 17:00	0	0	0	25	108	0	0	104	12	0	0	0	249
17:00 - 17:15	0	0	0	30	122	0	0	155	14	0	0	0	321
17:15 - 17:30	0	0	0	33	104	0	0	110	16	0	0	0	263
17:30 - 17:45	0	0	0	16	77	0	0	73	10	0	0	0	176
17:45 - 18:00	0	0	0	25	64	0	0	75	9	0	0	0	173
<b>Movement Totals</b>	<b>0</b>	<b>0</b>	<b>0</b>	<b>206</b>	<b>807</b>	<b>0</b>	<b>0</b>	<b>891</b>	<b>100</b>	<b>0</b>	<b>0</b>	<b>0</b>	<b>2004</b>
Enter Totals	0			1013			991			0			
Exit Totals	0			907			1097			0			

**Two-Hour Totals**

Light Trucks	0	0	0	3	22	0	0	21	2	0	0	0	48
Medium Trucks	0	0	0	0	1	0	0	0	0	0	0	0	1
Heavy Trucks	0	0	0	0	2	0	0	0	0	0	0	0	2
% Trucks	NA	NA	NA	1.5%	3.1%	NA	NA	2.4%	2.0%	NA	NA	NA	2.5%
Stopped Buses	0	0	0	0	0	0	0	0	0	0	0	0	0
Bicycles	0	0	0	0	1	0	0	0	0	0	0	0	1

	South	West	East	North	
Pedestrians	0	0	0	0	0

### Peak Hour Information

**Peak Hour 16:15 17:15**

	Eastbound			Westbound			Northbound			Southbound			Totals
	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	
Movement Total	0	0	0	103	454	0	0	523	56	0	0	0	1136
Peak Hour Factor	NA	NA	NA	0.86	0.93	NA	NA	0.84	0.78	NA	NA	NA	0.88

Enter Totals	0			557			579			0		
Peak Hour Factor	NA			0.92			0.86			NA		

Exit Totals	0			510			626			0		
Peak Hour Factor	NA			0.93			0.85			NA		

Light Trucks	0	0	0	1	15	0	0	13	1	0	0	0	30
Medium Trucks	0	0	0	0	0	0	0	0	0	0	0	0	0
Heavy Trucks	0	0	0	0	2	0	0	0	0	0	0	0	2
% Trucks	NA	NA	NA	1.0%	3.7%	NA	NA	2.5%	1.8%	NA	NA	NA	2.8%
Stopped Buses	0	0	0	0	0	0	0	0	0	0	0	0	0
Bicycles	0	0	0	0	0	0	0	0	0	0	0	0	0

	South	West	East	North	
Pedestrians	0	0	0	0	0

## Intersection Turning Movement Peak Hour Diagram


**Location** COLORADO AVENUE AT BOND STREET

**Date** 1/3/2007

**Day of Week** Wednesday

**Time Begin** 16:00

**Reviewed By:** TM





## Intersection Turning Movement Summary Report

**Location** ARIZONA AVENUE AT WALL STREET  
**Date** 1/3/2007  
**Day of Week** Wednesday  
**Time Begin** 16:00  
**Reviewed By:** TM

Time Period	Eastbound			Westbound			Northbound			Southbound			Totals
	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	
16:00 - 16:15	11	175	0	0	0	0	0	0	0	0	87	29	302
16:15 - 16:30	5	171	0	0	0	0	0	0	0	0	63	45	284
16:30 - 16:45	6	193	0	0	0	0	0	0	0	0	66	32	297
16:45 - 17:00	4	193	0	0	0	0	0	0	0	0	69	27	293
17:00 - 17:15	4	278	0	0	0	0	0	0	0	0	78	52	412
17:15 - 17:30	5	194	0	0	0	0	0	0	0	0	52	33	284
17:30 - 17:45	6	142	0	0	0	0	0	0	0	0	64	34	246
17:45 - 18:00	4	100	0	0	0	0	0	0	0	0	52	14	170
<b>Movement Totals</b>	<b>45</b>	<b>1446</b>	<b>0</b>	<b>0</b>	<b>0</b>	<b>0</b>	<b>0</b>	<b>0</b>	<b>0</b>	<b>0</b>	<b>531</b>	<b>266</b>	<b>2288</b>
Enter Totals	1491			0			0			797			
Exit Totals	1712			0			0			576			

### Two-Hour Totals

Light Trucks	0	22	0	0	0	0	0	0	0	0	14	1	37
Medium Trucks	0	9	0	0	0	0	0	0	0	0	0	0	9
Heavy Trucks	0	4	0	0	0	0	0	0	0	0	0	0	4
% Trucks	0.0%	2.4%	NA	2.6%	0.4%	2.2%							
Stopped Buses	0	0	0	0	0	0	0	0	0	0	0	0	0
Bicycles	0	0	0	0	0	0	0	0	0	0	0	0	0

	South	West	East	North	
Pedestrians	0	0	0	0	0

### Peak Hour Information

**Peak Hour 16:15 17:15**

	Eastbound			Westbound			Northbound			Southbound			Totals
	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	
Movement Total	19	835	0	0	0	0	0	0	0	0	276	156	1286
Peak Hour Factor	0.79	0.75	NA	NA	NA	NA	NA	NA	NA	NA	0.88	0.75	0.78

Enter Totals	854			0			0			432		
Peak Hour Factor	0.76			NA			NA			0.83		

Exit Totals	991			0			0			295		
Peak Hour Factor	0.75			NA			NA			0.90		

Light Trucks	0	16	0	0	0	0	0	0	0	0	7	1	24
Medium Trucks	0	6	0	0	0	0	0	0	0	0	0	0	6
Heavy Trucks	0	4	0	0	0	0	0	0	0	0	0	0	4
% Trucks	0.0%	3.1%	NA	2.5%	0.6%	2.6%							
Stopped Buses	0	0	0	0	0	0	0	0	0	0	0	0	0
Bicycles	0	0	0	0	0	0	0	0	0	0	0	0	0

	South	West	East	North	
Pedestrians	0	0	0	0	0

## Intersection Turning Movement Peak Hour Diagram


**Location** ARIZONA AVENUE AT WALL STREET

**Date** 1/3/2007

**Day of Week** Wednesday

**Time Begin** 16:00

**Reviewed By:** TM





## Intersection Turning Movement Summary Report

**Location** ARIZONA AVENUE AT BOND STREET

**Date** 1/3/2007

**Day of Week** Wednesday

**Time Begin** 16:00

**Reviewed By:** TM

Time Period	Eastbound			Westbound			Northbound			Southbound			Totals
	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	
16:00 - 16:15	0	161	52	0	0	0	32	64	0	0	0	0	309
16:15 - 16:30	0	158	63	0	0	0	29	74	0	0	0	0	324
16:30 - 16:45	0	156	74	0	0	0	27	80	0	0	0	0	337
16:45 - 17:00	0	147	48	0	0	0	32	80	0	0	0	0	307
17:00 - 17:15	0	239	87	0	0	0	26	71	0	0	0	0	423
17:15 - 17:30	0	165	62	0	0	0	20	66	0	0	0	0	313
17:30 - 17:45	0	140	38	0	0	0	16	55	0	0	0	0	249
17:45 - 18:00	0	81	34	0	0	0	12	46	0	0	0	0	173
<b>Movement Totals</b>	0	1247	458	0	0	0	194	536	0	0	0	0	2435
Enter Totals	1705			0			730			0			
Exit Totals	1441			0			994			0			

**Two-Hour Totals**

Light Trucks	0	24	8	0	0	0	6	14	0	0	0	0	52
Medium Trucks	0	8	1	0	0	0	0	0	0	0	0	0	9
Heavy Trucks	0	3	0	0	0	0	0	0	0	0	0	0	3
% Trucks	NA	2.8%	2.0%	NA	NA	NA	3.1%	2.6%	NA	NA	NA	NA	2.6%
Stopped Buses	0	0	0	0	0	0	0	0	0	0	0	0	0
Bicycles	0	0	0	0	0	0	0	0	0	0	0	0	0

	South	West	East	North	
Pedestrians	0	0	0	0	0

### Peak Hour Information

**Peak Hour 16:15 17:15**

	Eastbound			Westbound			Northbound			Southbound			Totals
	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	
Movement Total	0	700	272	0	0	0	114	305	0	0	0	0	1391
Peak Hour Factor	NA	0.73	0.78	NA	NA	NA	0.89	0.95	NA	NA	NA	NA	0.82

Enter Totals	972			0			419			0		
Peak Hour Factor	0.75			NA			0.94			NA		

Exit Totals	814			0			577			0		
Peak Hour Factor	0.77			NA			0.91			NA		

Light Trucks	0	19	5	0	0	0	4	9	0	0	0	0	37
Medium Trucks	0	6	0	0	0	0	0	0	0	0	0	0	6
Heavy Trucks	0	3	0	0	0	0	0	0	0	0	0	0	3
% Trucks	NA	4.0%	1.8%	NA	NA	NA	3.5%	3.0%	NA	NA	NA	NA	3.3%
Stopped Buses	0	0	0	0	0	0	0	0	0	0	0	0	0
Bicycles	0	0	0	0	0	0	0	0	0	0	0	0	0

	South	West	East	North	
Pedestrians	0	0	0	0	0

## Intersection Turning Movement Peak Hour Diagram


**Location** ARIZONA AVENUE AT BOND STREET

**Date** 1/3/2007

**Day of Week** Wednesday

**Time Begin** 16:00

**Reviewed By:** TM





## Intersection Turning Movement Summary Report

**Location** COLORADO AVENUE AT BEND PARKWAY-SB RAMP

**Date** 1/3/2007

**Day of Week** Wednesday

**Time Begin** 16:00

**Reviewed By:** TM

Time Period	Eastbound			Westbound			Northbound			Southbound			Totals
	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	
16:00 - 16:15	0	0	0	6	63	1	155	26	4	76	0	18	349
16:15 - 16:30	0	1	0	9	63	0	153	21	0	62	0	21	330
16:30 - 16:45	0	0	0	9	80	2	155	33	0	57	0	14	350
16:45 - 17:00	0	1	0	13	66	0	140	26	1	55	0	15	317
17:00 - 17:15	0	0	0	15	74	1	214	64	5	72	1	21	467
17:15 - 17:30	0	0	1	3	63	0	169	39	3	78	1	22	379
17:30 - 17:45	0	0	0	3	26	0	53	11	0	23	0	9	125
17:45 - 18:00	0	0	0	0	0	0	0	0	0	0	0	0	0
<b>Movement Totals</b>	<b>0</b>	<b>2</b>	<b>1</b>	<b>58</b>	<b>435</b>	<b>4</b>	<b>1039</b>	<b>220</b>	<b>13</b>	<b>423</b>	<b>2</b>	<b>120</b>	<b>2317</b>
Enter Totals	3			497			1272			545			
Exit Totals	1161			871			279			6			

### Two-Hour Totals

Light Trucks	0	0	0	0	8	0	23	3	0	15	0	4	53
Medium Trucks	0	0	0	0	0	0	1	0	0	1	0	0	2
Heavy Trucks	0	0	0	0	0	0	4	0	0	0	0	2	6
% Trucks	NA	0.0%	0.0%	0.0%	1.8%	0.0%	2.7%	1.4%	0.0%	3.8%	0.0%	5.0%	2.6%
Stopped Buses	0	0	0	0	0	0	0	0	0	0	0	0	0
Bicycles	0	0	0	0	0	0	0	0	0	0	0	0	0

	South	West	East	North	
Pedestrians	0	0	0	0	0

### Peak Hour Information

**Peak Hour 16:30 17:30**

	Eastbound			Westbound			Northbound			Southbound			Totals
	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	
Movement Total	0	1	1	40	283	3	678	162	9	262	2	72	1513
Peak Hour Factor	NA	0.25	0.25	0.67	0.88	0.38	0.79	0.63	0.45	0.84	0.50	0.82	0.81

Enter Totals	2			326			849			336		
Peak Hour Factor	0.50			0.90			0.75			0.83		

Exit Totals	751			554			203			5		
Peak Hour Factor	0.80			0.92			0.64			0.63		

Light Trucks	0	0	0	0	3	0	16	3	0	6	0	2	30
Medium Trucks	0	0	0	0	0	0	1	0	0	1	0	0	2
Heavy Trucks	0	0	0	0	0	0	4	0	0	0	0	2	6
% Trucks	NA	0.0%	0.0%	0.0%	1.1%	0.0%	3.1%	1.9%	0.0%	2.7%	0.0%	5.6%	2.5%
Stopped Buses	0	0	0	0	0	0	0	0	0	0	0	0	0
Bicycles	0	0	0	0	0	0	0	0	0	0	0	0	0

	South	West	East	North	
Pedestrians	0	0	0	0	0

## Intersection Turning Movement Peak Hour Diagram


**Location** COLORADO AVENUE AT BEND PARKWAY-SB RAMP

**Date** 1/3/2007

**Day of Week** Wednesday

**Time Begin** 16:00

**Reviewed By:** TM





## Intersection Turning Movement Summary Report

**Location** BUTLER MARKET ROAD AT BEND PARKWAY-SB RAMP

**Date** 1/2/2007

**Day of Week** Tuesday

**Time Begin** 16:00

**Reviewed By:** TM

Time Period	Eastbound			Westbound			Northbound			Southbound			Totals
	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	
16:00 - 16:15	0	108	0	0	103	0	0	0	0	22	0	45	278
16:15 - 16:30	0	92	0	0	118	0	0	0	0	18	0	38	266
16:30 - 16:45	0	109	0	0	134	0	0	0	0	24	0	49	316
16:45 - 17:00	0	106	0	0	131	0	0	0	0	31	0	39	307
17:00 - 17:15	0	132	0	0	128	0	0	0	0	15	0	50	325
17:15 - 17:30	0	110	0	0	106	0	0	0	0	19	0	38	273
17:30 - 17:45	0	90	0	0	97	0	0	0	0	12	0	39	238
17:45 - 18:00	0	71	0	0	75	0	0	0	0	13	0	28	187
<b>Movement Totals</b>	0	818	0	0	892	0	0	0	0	154	0	326	2190
Enter Totals	818			892			0			480			
Exit Totals	1144			1046			0			0			

### Two-Hour Totals

Light Trucks	0	32	0	0	13	0	0	0	0	4	0	15	64
Medium Trucks	0	2	0	0	2	0	0	0	0	0	0	0	4
Heavy Trucks	0	3	0	0	2	0	0	0	0	2	0	2	9
% Trucks	NA	4.5%	NA	NA	1.9%	NA	NA	NA	NA	3.9%	NA	5.2%	3.5%
Stopped Buses	0	0	0	0	0	0	0	0	0	0	0	0	0
Bicycles	0	1	0	0	0	0	0	0	0	1	0	0	2

	South	West	East	North	
Pedestrians	0	0	0	0	0

### Peak Hour Information

**Peak Hour 16:30 17:30**

	Eastbound			Westbound			Northbound			Southbound			Totals
	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	
Movement Total	0	457	0	0	499	0	0	0	0	89	0	176	1221
Peak Hour Factor	NA	0.87	NA	NA	0.93	NA	NA	NA	NA	0.72	NA	0.88	0.94

Enter Totals	457			499			0			265		
Peak Hour Factor	0.87			0.93			NA			0.91		

Exit Totals	633			588			0			0		
Peak Hour Factor	0.87			0.91			NA			NA		

Light Trucks	0	16	0	0	8	0	0	0	0	2	0	7	33
Medium Trucks	0	1	0	0	1	0	0	0	0	0	0	0	2
Heavy Trucks	0	1	0	0	0	0	0	0	0	2	0	2	5
% Trucks	NA	3.9%	NA	NA	1.8%	NA	NA	NA	NA	4.5%	NA	5.1%	3.3%
Stopped Buses	0	0	0	0	0	0	0	0	0	0	0	0	0
Bicycles	0	1	0	0	0	0	0	0	0	0	0	0	1

	South	West	East	North	
Pedestrians	0	0	0	0	0

## Intersection Turning Movement Peak Hour Diagram


**Location** BUTLER MARKET ROAD AT BEND PARKWAY-SB RAMP

**Date** 1/2/2007

**Day of Week** Tuesday

**Time Begin** 16:00

**Reviewed By:** TM





## Intersection Turning Movement Summary Report

**Location** BUTLER MARKET ROAD AT BEND PARKWAY-NB RAMP

**Date** 1/2/2007

**Day of Week** Tuesday

**Time Begin** 16:00

**Reviewed By:** TM

Time Period	Eastbound			Westbound			Northbound			Southbound			Totals
	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	
16:00 - 16:15	2	128	23	51	95	2	5	0	1	0	0	0	307
16:15 - 16:30	5	116	11	38	117	0	1	0	1	0	0	0	289
16:30 - 16:45	1	144	12	47	128	3	5	1	2	0	0	0	343
16:45 - 17:00	0	133	12	44	170	2	3	1	6	0	0	0	371
17:00 - 17:15	2	169	20	57	137	3	5	3	4	0	0	0	400
17:15 - 17:30	2	131	11	56	101	1	1	1	2	0	0	0	306
17:30 - 17:45	0	113	12	45	101	2	1	2	0	0	0	0	276
17:45 - 18:00	1	92	4	30	79	2	3	0	0	0	0	0	211
<b>Movement Totals</b>	<b>13</b>	<b>1026</b>	<b>105</b>	<b>368</b>	<b>928</b>	<b>15</b>	<b>24</b>	<b>8</b>	<b>16</b>	<b>0</b>	<b>0</b>	<b>0</b>	<b>2503</b>
Enter Totals	1144			1311			48			0			
Exit Totals	1050			944			481			28			

### Two-Hour Totals

Light Trucks	1	34	5	10	14	1	0	0	2	0	0	0	67
Medium Trucks	1	1	0	0	3	0	0	0	0	0	0	0	5
Heavy Trucks	0	6	0	4	1	0	0	0	0	0	0	0	11
% Trucks	15.4%	4.0%	4.8%	3.8%	1.9%	6.7%	0.0%	0.0%	12.5%	NA	NA	NA	3.3%
Stopped Buses	0	0	0	0	0	0	0	0	0	0	0	0	0
Bicycles	0	1	0	0	0	0	0	0	0	0	0	0	1

	South	West	East	North	
Pedestrians	0	0	0	0	0

### Peak Hour Information

**Peak Hour 16:30 17:30**

	Eastbound			Westbound			Northbound			Southbound			Totals
	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	
Movement Total	5	577	55	204	536	9	14	6	14	0	0	0	1420
Peak Hour Factor	0.63	0.85	0.69	0.89	0.79	0.75	0.70	0.50	0.58	NA	NA	NA	0.89

Enter Totals	637			749			34			0			
Peak Hour Factor	0.83			0.87			0.71			NA			

Exit Totals	591			550			265			14			
Peak Hour Factor	0.85			0.78			0.83			0.70			

Light Trucks	0	13	3	8	9	1	0	0	2	0	0	0	36
Medium Trucks	1	0	0	0	1	0	0	0	0	0	0	0	2
Heavy Trucks	0	4	0	1	0	0	0	0	0	0	0	0	5
% Trucks	20.0%	2.9%	5.5%	4.4%	1.9%	11.1%	0.0%	0.0%	14.3%	NA	NA	NA	3.0%
Stopped Buses	0	0	0	0	0	0	0	0	0	0	0	0	0
Bicycles	0	1	0	0	0	0	0	0	0	0	0	0	1

	South	West	East	North	
Pedestrians	0	0	0	0	0

## Intersection Turning Movement Peak Hour Diagram


**Location** BUTLER MARKET ROAD AT BEND PARKWAY-NB RAMP

**Date** 1/2/2007

**Day of Week** Tuesday

**Time Begin** 16:00

**Reviewed By:** TM





## Intersection Turning Movement Summary Report

**Location** BUTLER MARKET ROAD AT NE 4TH STREET

**Date** 1/2/2007

**Day of Week** Tuesday

**Time Begin** 16:00

**Reviewed By:** BV

Time Period	Eastbound			Westbound			Northbound			Southbound			Totals
	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	
16:00 - 16:15	26	109	3	1	97	18	15	0	43	11	5	1	329
16:15 - 16:30	28	84	0	1	93	11	16	0	43	13	1	0	290
16:30 - 16:45	28	116	0	0	123	13	10	0	41	5	3	0	339
16:45 - 17:00	23	108	0	0	112	22	16	0	62	5	1	0	349
17:00 - 17:15	28	130	1	0	112	23	19	0	53	8	0	0	374
17:15 - 17:30	16	109	1	0	99	9	15	0	46	5	1	0	301
17:30 - 17:45	18	98	0	0	101	11	9	1	37	4	1	0	280
17:45 - 18:00	16	81	0	0	73	10	7	1	31	1	0	0	220
<b>Movement Totals</b>	<b>183</b>	<b>835</b>	<b>5</b>	<b>2</b>	<b>810</b>	<b>117</b>	<b>107</b>	<b>2</b>	<b>356</b>	<b>52</b>	<b>12</b>	<b>1</b>	<b>2482</b>
Enter Totals	1023			929			465			65			
Exit Totals	943			1218			9			312			

**Two-Hour Totals**

Light Trucks	6	14	0	0	12	2	2	0	3	0	0	0	39
Medium Trucks	0	1	0	0	1	0	0	0	1	0	0	0	3
Heavy Trucks	4	1	1	0	2	0	0	0	3	1	0	0	12
% Trucks	5.5%	1.9%	20.0%	0.0%	1.9%	1.7%	1.9%	0.0%	2.0%	1.9%	0.0%	0.0%	2.2%
Stopped Buses	0	0	0	0	0	0	0	0	0	0	0	0	0
Bicycles	0	0	0	0	0	0	0	0	0	0	0	0	0

	South	West	East	North	
Pedestrians	0	0	0	3	3

### Peak Hour Information

**Peak Hour 16:30 17:30**

	Eastbound			Westbound			Northbound			Southbound			Totals
	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	
Movement Total	95	463	2	0	446	67	60	0	202	23	5	0	1363
Peak Hour Factor	0.85	0.89	0.50	NA	0.91	0.73	0.79	NA	0.81	0.72	0.42	NA	0.91

Enter Totals	560			513			262			28		
Peak Hour Factor	0.88			0.94			0.84			0.88		

Exit Totals	523			671			2			167		
Peak Hour Factor	0.88			0.94			0.50			0.82		

Light Trucks	5	3	0	0	5	1	1	0	1	0	0	0	16
Medium Trucks	0	0	0	0	1	0	0	0	0	0	0	0	1
Heavy Trucks	3	0	1	0	0	0	0	0	0	1	0	0	5
% Trucks	8.4%	0.6%	50.0%	NA	1.3%	1.5%	1.7%	NA	0.5%	4.3%	0.0%	NA	1.6%
Stopped Buses	0	0	0	0	0	0	0	0	0	0	0	0	0
Bicycles	0	0	0	0	0	0	0	0	0	0	0	0	0

	South	West	East	North	
Pedestrians	0	0	0	3	3

## Intersection Turning Movement Peak Hour Diagram


**Location** BUTLER MARKET ROAD AT NE 4TH STREET

**Date** 1/2/2007

**Day of Week** Tuesday

**Time Begin** 16:00

**Reviewed By:** BV





## Intersection Turning Movement Summary Report

**Location** NE STUDIO ROAD AT NE 4TH STREET

**Date** 1/2/2007

**Day of Week** Tuesday

**Time Begin** 16:00

**Reviewed By:** BM

Time Period	Eastbound			Westbound			Northbound			Southbound			Totals
	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	
16:00 - 16:15	0	0	0	7	0	28	53	75	0	0	103	14	280
16:15 - 16:30	2	4	1	6	4	26	35	72	0	0	93	16	259
16:30 - 16:45	2	2	1	5	2	27	45	56	0	0	93	11	244
16:45 - 17:00	1	2	0	8	0	25	62	71	0	0	82	17	268
17:00 - 17:15	0	0	0	3	1	31	57	90	0	0	76	13	271
17:15 - 17:30	0	0	0	3	0	22	65	71	0	0	80	12	253
17:30 - 17:45	0	0	0	7	0	31	46	59	0	0	64	14	221
17:45 - 18:00	0	0	0	8	0	24	42	51	0	0	44	22	191
<b>Movement Totals</b>	<b>5</b>	<b>8</b>	<b>2</b>	<b>47</b>	<b>7</b>	<b>214</b>	<b>405</b>	<b>545</b>	<b>0</b>	<b>0</b>	<b>635</b>	<b>119</b>	<b>1987</b>
Enter Totals	15			268			950			754			
Exit Totals	532			7			594			854			

### Two-Hour Totals

Light Trucks	0	0	0	0	0	6	10	5	0	0	7	0	28
Medium Trucks	0	0	0	0	0	0	2	0	0	0	0	0	2
Heavy Trucks	0	0	0	0	0	0	0	0	0	0	1	0	1
% Trucks	0.0%	0.0%	0.0%	0.0%	0.0%	2.8%	3.0%	0.9%	NA	NA	1.3%	0.0%	1.6%
Stopped Buses	0	0	0	0	0	0	0	0	0	0	0	0	0
Bicycles	0	8	0	0	7	1	1	1	0	0	4	0	22

	South 27	West 0	East 0	North 0	27
--	-------------	-----------	-----------	------------	----

### Peak Hour Information

**Peak Hour 16:00 17:00**

	Eastbound			Westbound			Northbound			Southbound			Totals
	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	
Movement Total	5	8	2	26	6	106	195	274	0	0	371	58	1051
Peak Hour Factor	0.63	0.50	0.50	0.81	0.38	0.95	0.79	0.91	NA	NA	0.90	0.85	0.94

Enter Totals	15			138			469			429		
Peak Hour Factor	0.54			0.96			0.88			0.92		

Exit Totals	261			6			302			482		
Peak Hour Factor	0.81			0.38			0.92			0.92		

Light Trucks	0	0	0	0	0	3	6	4	0	0	6	0	19
Medium Trucks	0	0	0	0	0	0	2	0	0	0	0	0	2
Heavy Trucks	0	0	0	0	0	0	0	0	0	0	1	0	1
% Trucks	0.0%	0.0%	0.0%	0.0%	0.0%	2.8%	4.1%	1.5%	NA	NA	1.9%	0.0%	2.1%
Stopped Buses	0	0	0	0	0	0	0	0	0	0	0	0	0
Bicycles	0	8	0	0	6	1	0	1	0	0	2	0	18

	South 14	West 0	East 0	North 0	14
--	-------------	-----------	-----------	------------	----

## Intersection Turning Movement Peak Hour Diagram


**Location** NE STUDIO ROAD AT NE 4TH STREET

**Date** 1/2/2007

**Day of Week** Tuesday

**Time Begin** 16:00

**Reviewed By:** BM





## Intersection Turning Movement Summary Report

**Location** NE REVERE AVENUE AT NE 4TH STREET

**Date** 1/2/2007

**Day of Week** Tuesday

**Time Begin** 16:00

**Reviewed By:** BV

Time Period	Eastbound			Westbound			Northbound			Southbound			Totals
	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	
16:00 - 16:15	23	67	49	29	50	3	7	42	13	52	46	28	409
16:15 - 16:30	30	68	45	25	49	4	8	38	11	46	39	29	392
16:30 - 16:45	15	61	44	20	62	4	6	33	12	51	35	36	379
16:45 - 17:00	17	52	51	22	67	3	4	51	17	47	27	29	387
17:00 - 17:15	37	71	57	18	66	8	13	53	15	54	29	26	447
17:15 - 17:30	23	79	70	24	56	5	15	43	10	36	35	33	429
17:30 - 17:45	5	43	40	16	43	2	6	37	12	43	19	33	299
17:45 - 18:00	7	43	35	17	41	5	7	30	8	27	28	26	274
<b>Movement Totals</b>	<b>157</b>	<b>484</b>	<b>391</b>	<b>171</b>	<b>434</b>	<b>34</b>	<b>66</b>	<b>327</b>	<b>98</b>	<b>356</b>	<b>258</b>	<b>240</b>	<b>3016</b>
Enter Totals	1032			639			491			854			
Exit Totals	790			888			889			449			

**Two-Hour Totals**

Light Trucks	2	1	5	1	3	0	0	9	1	4	12	3	41
Medium Trucks	0	0	3	0	0	0	0	0	0	0	0	0	3
Heavy Trucks	0	0	1	0	0	0	0	0	0	1	0	0	2
% Trucks	1.3%	0.2%	2.3%	0.6%	0.7%	0.0%	0.0%	2.8%	1.0%	1.4%	4.7%	1.3%	1.5%
Stopped Buses	0	0	0	0	0	0	0	0	0	0	0	0	0
Bicycles	0	0	0	0	0	0	0	0	0	0	0	0	0

	South	West	East	North	
Pedestrians	0	4	1	3	8

### Peak Hour Information

**Peak Hour 16:30 17:30**

	Eastbound			Westbound			Northbound			Southbound			Totals
	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	
Movement Total	92	263	222	84	251	20	38	180	54	188	126	124	1642
Peak Hour Factor	0.62	0.83	0.79	0.88	0.94	0.63	0.63	0.85	0.79	0.87	0.90	0.86	0.92

Enter Totals	577			355			272			438		
Peak Hour Factor	0.84			0.96			0.84			0.90		

Exit Totals	425			493			486			238		
Peak Hour Factor	0.84			0.91			0.89			0.80		

Light Trucks	2	1	4	1	2	0	0	3	1	4	6	2	26
Medium Trucks	0	0	2	0	0	0	0	0	0	0	0	0	2
Heavy Trucks	0	0	0	0	0	0	0	0	0	1	0	0	1
% Trucks	2.2%	0.4%	2.7%	1.2%	0.8%	0.0%	0.0%	1.7%	1.9%	2.7%	4.8%	1.6%	1.8%
Stopped Buses	0	0	0	0	0	0	0	0	0	0	0	0	0
Bicycles	0	0	0	0	0	0	0	0	0	0	0	0	0

	South	West	East	North	
Pedestrians	0	1	1	1	3

## Intersection Turning Movement Peak Hour Diagram


**Location** NE REVERE AVENUE AT NE 4TH STREET

**Date** 1/2/2007

**Day of Week** Tuesday

**Time Begin** 16:00

**Reviewed By:** BV





## Intersection Turning Movement Summary Report

**Location** OLNEY AVENUE AT 4TH STREET

**Date** 1/2/2007

**Day of Week** Tuesday

**Time Begin** 16:00

**Reviewed By:** BV

Time Period	Eastbound			Westbound			Northbound			Southbound			Totals
	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	
16:00 - 16:15	6	78	14	5	72	10	8	35	6	25	36	24	319
16:15 - 16:30	4	66	18	11	61	8	18	40	12	22	32	29	321
16:30 - 16:45	8	49	13	7	61	14	20	29	4	17	22	14	258
16:45 - 17:00	6	67	17	5	55	5	8	42	10	13	22	25	275
17:00 - 17:15	9	76	26	10	78	8	8	54	7	12	24	32	344
17:15 - 17:30	3	71	16	3	65	5	10	35	4	14	26	29	281
17:30 - 17:45	3	58	8	8	67	9	4	27	6	12	18	18	238
17:45 - 18:00	3	48	11	4	72	7	4	20	3	11	19	10	212
<b>Movement Totals</b>	<b>42</b>	<b>513</b>	<b>123</b>	<b>53</b>	<b>531</b>	<b>66</b>	<b>80</b>	<b>282</b>	<b>52</b>	<b>126</b>	<b>199</b>	<b>181</b>	<b>2248</b>
Enter Totals	678			650			414			506			
Exit Totals	774			709			458			307			

**Two-Hour Totals**

Light Trucks	0	2	5	0	2	0	0	3	0	6	4	3	25
Medium Trucks	0	0	0	0	0	0	0	0	0	0	0	0	0
Heavy Trucks	0	0	0	0	0	0	0	0	0	0	0	0	0
% Trucks	0.0%	0.4%	4.1%	0.0%	0.4%	0.0%	0.0%	1.1%	0.0%	4.8%	2.0%	1.7%	1.1%
Stopped Buses	0	0	0	0	0	0	0	0	0	0	0	0	0
Bicycles	0	0	0	0	0	0	0	0	0	0	0	0	0

Pedestrians	South 6	West 6	East 4	North 10	26
-------------	------------	-----------	-----------	-------------	----

### Peak Hour Information

**Peak Hour 16:15 17:15**

	Eastbound			Westbound			Northbound			Southbound			Totals
	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	
Movement Total	27	258	74	33	255	35	54	165	33	64	100	100	1198
Peak Hour Factor	0.75	0.85	0.71	0.75	0.82	0.63	0.68	0.76	0.69	0.73	0.78	0.78	0.87

Enter Totals	359			323			252			264		
Peak Hour Factor	0.81			0.84			0.90			0.80		

Exit Totals	412			352			272			162		
Peak Hour Factor	0.89			0.91			0.76			0.92		

Light Trucks	0	1	2	0	0	0	0	2	0	3	2	0	10
Medium Trucks	0	0	0	0	0	0	0	0	0	0	0	0	0
Heavy Trucks	0	0	0	0	0	0	0	0	0	0	0	0	0
% Trucks	0.0%	0.4%	2.7%	0.0%	0.0%	0.0%	0.0%	1.2%	0.0%	4.7%	2.0%	0.0%	0.8%
Stopped Buses	0	0	0	0	0	0	0	0	0	0	0	0	0
Bicycles	0	0	0	0	0	0	0	0	0	0	0	0	0

Pedestrians	South 4	West 4	East 2	North 6	16
-------------	------------	-----------	-----------	------------	----

## Intersection Turning Movement Peak Hour Diagram


**Location** OLNEY AVENUE AT 4TH STREET

**Date** 1/2/2007

**Day of Week** Tuesday

**Time Begin** 16:00

**Reviewed By:** BV





## Intersection Turning Movement Summary Report

**Location** NW LAFAYETTE AVENUE AT BEND PARKWAY

**Date** 1/3/2007

**Day of Week** Wednesday

**Time Begin** 16:00

**Reviewed By:** TM

Time Period	Eastbound			Westbound			Northbound			Southbound			Totals
	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	
16:00 - 16:15	19	0	0	0	0	0	0	468	0	12	486	0	985
16:15 - 16:30	12	0	0	0	0	0	0	409	0	14	421	0	856
16:30 - 16:45	22	0	0	0	0	0	0	451	0	17	474	0	964
16:45 - 17:00	14	0	0	0	0	0	0	417	0	12	487	0	930
17:00 - 17:15	41	0	0	0	0	0	0	561	0	9	550	0	1161
17:15 - 17:30	21	0	0	0	0	0	0	463	0	14	498	0	996
17:30 - 17:45	26	0	0	0	0	0	0	337	0	6	437	0	806
17:45 - 18:00	11	0	0	0	0	0	0	313	0	11	366	0	701
Movement Totals	166	0	0	0	0	0	0	3419	0	95	3719	0	7399
Enter Totals	166			0			3419			3814			
Exit Totals	0			95			3419			3885			

### Two-Hour Totals

Light Trucks	3	0	0	0	0	0	0	104	0	3	118	0	228
Medium Trucks	0	0	0	0	0	0	0	10	0	0	15	0	25
Heavy Trucks	0	0	0	0	0	0	0	38	0	0	72	0	110
% Trucks	1.8%	NA	NA	NA	NA	NA	NA	4.4%	NA	3.2%	5.5%	NA	4.9%
Stopped Buses	0	0	0	0	0	0	0	0	0	0	0	0	0
Bicycles	0	0	0	0	0	0	0	0	0	0	0	0	0

	South	West	East	North	
Pedestrians	0	0	0	0	0

### Peak Hour Information

**Peak Hour 16:30 17:30**

	Eastbound			Westbound			Northbound			Southbound			Totals
	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	
Movement Total	98	0	0	0	0	0	0	1892	0	52	2009	0	4051
Peak Hour Factor	0.60	NA	NA	NA	NA	NA	NA	0.84	NA	0.76	0.91	NA	0.87

Enter Totals	98			0			1892			2061		
Peak Hour Factor	0.60			NA			0.84			0.92		

Exit Totals	0			52			1892			2107		
Peak Hour Factor	NA			0.76			0.84			0.89		

Light Trucks	1	0	0	0	0	0	0	40	0	2	49	0	92
Medium Trucks	0	0	0	0	0	0	0	5	0	0	4	0	9
Heavy Trucks	0	0	0	0	0	0	0	22	0	0	34	0	56
% Trucks	1.0%	NA	NA	NA	NA	NA	NA	3.5%	NA	3.8%	4.3%	NA	3.9%
Stopped Buses	0	0	0	0	0	0	0	0	0	0	0	0	0
Bicycles	0	0	0	0	0	0	0	0	0	0	0	0	0

	South	West	East	North	
Pedestrians	0	0	0	0	0

## Intersection Turning Movement Peak Hour Diagram


**Location** NW LAFAYETTE AVENUE AT BEND PARKWAY

**Date** 1/3/2007

**Day of Week** Wednesday

**Time Begin** 16:00

**Reviewed By:** TM





## Intersection Turning Movement Summary Report

**Location** WALL STREET AT BOND STREET

**Date** 1/2/2007

**Day of Week** Tuesday

**Time Begin** 16:00

**Reviewed By:** BV

Time Period	Eastbound			Westbound			Northbound			Southbound			Totals
	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	
16:00 - 16:15	0	25	0	4	95	0	84	0	13	6	0	0	227
16:15 - 16:30	1	43	3	4	106	0	87	1	12	2	0	3	262
16:30 - 16:45	0	29	3	2	114	0	66	2	8	10	0	3	237
16:45 - 17:00	0	33	1	2	93	0	64	1	10	7	0	3	214
17:00 - 17:15	0	28	1	0	91	0	92	2	12	8	0	5	239
17:15 - 17:30	0	23	1	0	102	0	76	1	17	6	0	2	228
17:30 - 17:45	0	28	1	0	76	0	68	0	5	3	0	1	182
17:45 - 18:00	0	27	2	1	89	0	52	0	6	3	0	2	182
<b>Movement Totals</b>	<b>1</b>	<b>236</b>	<b>12</b>	<b>13</b>	<b>766</b>	<b>0</b>	<b>589</b>	<b>7</b>	<b>83</b>	<b>45</b>	<b>0</b>	<b>19</b>	<b>1771</b>
Enter Totals	249			779			679			64			
Exit Totals	844			894			32			1			

### Two-Hour Totals

Light Trucks	0	2	0	0	5	0	5	0	0	0	0	0	12
Medium Trucks	0	0	0	0	0	0	0	0	0	0	0	0	0
Heavy Trucks	0	0	0	0	0	0	0	0	0	0	0	0	0
% Trucks	0.0%	0.8%	0.0%	0.0%	0.7%	NA	0.8%	0.0%	0.0%	0.0%	NA	0.0%	0.7%
Stopped Buses	0	0	0	0	0	0	0	0	0	0	0	0	0
Bicycles	0	0	0	0	0	0	0	0	0	0	0	0	0

	South 8	West 2	East 0	North 13	23
--	------------	-----------	-----------	-------------	----

### Peak Hour Information

**Peak Hour 16:15 17:15**

	Eastbound			Westbound			Northbound			Southbound			Totals
	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	
Movement Total	1	133	8	8	404	0	309	6	42	27	0	14	952
Peak Hour Factor	0.25	0.77	0.67	0.50	0.89	NA	0.84	0.75	0.88	0.68	NA	0.70	0.91

Enter Totals	142			412			357			41		
Peak Hour Factor	0.76			0.89			0.84			0.79		

Exit Totals	456			473			22			1		
Peak Hour Factor	0.86			0.90			0.69			0.25		

Light Trucks	0	2	0	0	4	0	3	0	0	0	0	0	9
Medium Trucks	0	0	0	0	0	0	0	0	0	0	0	0	0
Heavy Trucks	0	0	0	0	0	0	0	0	0	0	0	0	0
% Trucks	0.0%	1.5%	0.0%	0.0%	1.0%	NA	1.0%	0.0%	0.0%	0.0%	NA	0.0%	0.9%
Stopped Buses	0	0	0	0	0	0	0	0	0	0	0	0	0
Bicycles	0	0	0	0	0	0	0	0	0	0	0	0	0

	South 2	West 2	East 0	North 7	11
--	------------	-----------	-----------	------------	----

## Intersection Turning Movement Peak Hour Diagram


**Location** WALL STREET AT BOND STREET

**Date** 1/2/2007

**Day of Week** Tuesday

**Time Begin** 16:00

**Reviewed By:** BV





## Intersection Turning Movement Summary Report

**Location** NE GREENWOOD AVENUE AT NE 4TH STREET

**Date** 1/4/2007

**Day of Week** Thursday

**Time Begin** 16:00

**Reviewed By:** BV

Time Period	Eastbound			Westbound			Northbound			Southbound			Totals
	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	
16:00 - 16:15	0	205	1	22	207	13	17	0	0	20	0	0	485
16:15 - 16:30	4	242	4	31	198	10	23	0	0	31	0	0	543
16:30 - 16:45	4	205	4	22	192	12	16	1	0	16	0	0	472
16:45 - 17:00	4	253	2	18	180	13	28	0	0	27	1	1	527
17:00 - 17:15	4	243	12	27	177	13	25	1	0	37	0	0	539
17:15 - 17:30	6	244	7	22	206	10	47	0	0	13	0	0	555
17:30 - 17:45	0	203	5	17	191	10	18	0	0	15	2	0	461
17:45 - 18:00	4	185	1	7	186	10	14	0	0	6	0	0	413
<b>Movement Totals</b>	<b>26</b>	<b>1780</b>	<b>36</b>	<b>166</b>	<b>1537</b>	<b>91</b>	<b>188</b>	<b>2</b>	<b>0</b>	<b>165</b>	<b>3</b>	<b>1</b>	<b>3995</b>
Enter Totals	1842			1794			190			169			
Exit Totals	1969			1702			204			120			

### Two-Hour Totals

Light Trucks	6	25	1	4	11	1	1	0	0	5	0	0	54
Medium Trucks	0	0	0	0	4	0	0	0	0	0	0	0	4
Heavy Trucks	0	12	0	0	12	0	0	0	0	0	0	0	24
% Trucks	23.1%	2.1%	2.8%	2.4%	1.8%	1.1%	0.5%	0.0%	NA	3.0%	0.0%	0.0%	2.1%
Stopped Buses	0	0	0	0	0	0	0	0	0	0	0	0	0
Bicycles	0	0	0	0	0	0	0	0	0	0	0	0	0

	South 3	West 4	East 0	North 6	13
--	------------	-----------	-----------	------------	----

### Peak Hour Information

**Peak Hour 16:30 17:30**

	Eastbound			Westbound			Northbound			Southbound			Totals
	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	
Movement Total	18	945	25	89	755	48	116	2	0	93	1	1	2093
Peak Hour Factor	0.75	0.93	0.52	0.82	0.92	0.92	0.62	0.50	NA	0.63	0.25	0.25	0.94

Enter Totals	988			892			118			95		
Peak Hour Factor	0.95			0.94			0.63			0.64		

Exit Totals	1062			848			116			67		
Peak Hour Factor	0.91			0.97			0.73			0.93		

Light Trucks	2	12	1	2	7	0	1	0	0	2	0	0	27
Medium Trucks	0	0	0	0	3	0	0	0	0	0	0	0	3
Heavy Trucks	0	9	0	0	9	0	0	0	0	0	0	0	18
% Trucks	11.1%	2.2%	4.0%	2.2%	2.5%	0.0%	0.9%	0.0%	NA	2.2%	0.0%	0.0%	2.3%
Stopped Buses	0	0	0	0	0	0	0	0	0	0	0	0	0
Bicycles	0	0	0	0	0	0	0	0	0	0	0	0	0

	South 2	West 4	East 0	North 2	8
--	------------	-----------	-----------	------------	---

## Intersection Turning Movement Peak Hour Diagram


**Location** NE GREENWOOD AVENUE AT NE 4TH STREET

**Date** 1/4/2007

**Day of Week** Thursday

**Time Begin** 16:00

**Reviewed By:** BV





## Intersection Turning Movement Summary Report

**Location** NE HAWTHORNE AVENUE AT NE 3RD STREET

**Date** 1/4/2007

**Day of Week** Thursday

**Time Begin** 16:00

**Reviewed By:** TM

Time Period	Eastbound			Westbound			Northbound			Southbound			Totals
	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	
16:00 - 16:15	8	0	0	11	0	0	2	239	3	6	223	6	498
16:15 - 16:30	6	0	3	6	3	0	7	246	2	6	219	6	504
16:30 - 16:45	9	1	1	13	0	0	6	249	1	4	206	8	498
16:45 - 17:00	7	0	0	6	0	0	7	253	1	4	182	5	465
17:00 - 17:15	7	1	6	13	0	0	4	235	3	4	191	7	471
17:15 - 17:30	7	0	1	15	0	1	2	242	2	3	198	10	481
17:30 - 17:45	5	0	1	9	0	0	5	253	2	0	243	6	524
17:45 - 18:00	0	0	1	8	0	1	4	193	1	0	161	2	371
<b>Movement Totals</b>	<b>49</b>	<b>2</b>	<b>13</b>	<b>81</b>	<b>3</b>	<b>2</b>	<b>37</b>	<b>1910</b>	<b>15</b>	<b>27</b>	<b>1623</b>	<b>50</b>	<b>3812</b>
Enter Totals	64			86			1962			1700			
Exit Totals	89			45			2004			1674			

### Two-Hour Totals

Light Trucks	3	0	0	14	0	0	13	48	3	0	38	4	123
Medium Trucks	0	0	0	0	0	0	1	0	0	0	2	0	3
Heavy Trucks	0	0	0	0	0	0	0	7	0	0	5	0	12
% Trucks	6.1%	0.0%	0.0%	17.3%	0.0%	0.0%	37.8%	2.9%	20.0%	0.0%	2.8%	8.0%	3.6%
Stopped Buses	0	0	0	0	0	0	0	0	0	0	0	0	0
Bicycles	0	0	0	0	0	0	0	0	0	0	1	0	1

	South	West	East	North	
Pedestrians	0	0	0	0	0

### Peak Hour Information

**Peak Hour 16:00 17:00**

	Eastbound			Westbound			Northbound			Southbound			Totals
	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	
Movement Total	30	1	4	36	3	0	22	987	7	20	830	25	1965
Peak Hour Factor	0.83	0.25	0.33	0.69	0.25	NA	0.79	0.98	0.58	0.83	0.93	0.78	0.97

Enter Totals	35			39			1016			875		
Peak Hour Factor	0.80			0.75			0.97			0.93		

Exit Totals	48			30			1027			860		
Peak Hour Factor	0.80			0.68			0.98			0.93		

Light Trucks	3	0	0	6	0	0	6	34	2	0	32	1	84
Medium Trucks	0	0	0	0	0	0	1	0	0	0	1	0	2
Heavy Trucks	0	0	0	0	0	0	0	6	0	0	3	0	9
% Trucks	10.0%	0.0%	0.0%	16.7%	0.0%	NA	31.8%	4.1%	28.6%	0.0%	4.3%	4.0%	4.8%
Stopped Buses	0	0	0	0	0	0	0	0	0	0	0	0	0
Bicycles	0	0	0	0	0	0	0	0	0	0	1	0	1

	South	West	East	North	
Pedestrians	0	0	0	0	0

## Intersection Turning Movement Peak Hour Diagram


**Location** NE HAWTHORNE AVENUE AT NE 3RD STREET

**Date** 1/4/2007

**Day of Week** Thursday

**Time Begin** 16:00

**Reviewed By:** TM





## Intersection Turning Movement Summary Report

**Location** NE HAWTHORNE AVENUE AT NE 4TH STREET

**Date** 1/4/2007

**Day of Week** Thursday

**Time Begin** 16:00

**Reviewed By:** BV

Time Period	Eastbound			Westbound			Northbound			Southbound			Totals
	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	
16:00 - 16:15	1	5	5	0	1	0	0	13	3	4	26	0	58
16:15 - 16:30	6	6	8	1	3	1	1	14	2	7	18	2	69
16:30 - 16:45	6	3	5	1	1	0	1	18	2	7	26	1	71
16:45 - 17:00	3	7	8	0	1	2	0	12	3	4	25	2	67
17:00 - 17:15	6	7	15	1	3	1	1	20	3	6	24	2	89
17:15 - 17:30	5	2	9	0	5	1	0	15	5	7	15	1	65
17:30 - 17:45	4	6	9	0	5	0	0	8	4	3	11	1	51
17:45 - 18:00	3	2	4	0	3	0	1	7	1	3	16	0	40
<b>Movement Totals</b>	<b>34</b>	<b>38</b>	<b>63</b>	<b>3</b>	<b>22</b>	<b>5</b>	<b>4</b>	<b>107</b>	<b>23</b>	<b>41</b>	<b>161</b>	<b>9</b>	<b>510</b>
Enter Totals	135			30			134			211			
Exit Totals	51			86			173			200			

### Two-Hour Totals

Light Trucks	12	4	1	0	0	0	0	1	4	7	0	0	29
Medium Trucks	1	0	0	0	0	0	0	0	0	0	0	0	1
Heavy Trucks	0	0	0	0	0	0	0	0	0	0	0	0	0
% Trucks	38.2%	10.5%	1.6%	0.0%	0.0%	0.0%	0.0%	0.9%	17.4%	17.1%	0.0%	0.0%	5.9%
Stopped Buses	0	0	0	0	0	0	0	0	0	0	0	0	0
Bicycles	0	0	0	0	0	0	0	0	0	0	0	0	0

Pedestrians	South 0	West 4	East 0	North 4	8
-------------	------------	-----------	-----------	------------	---

### Peak Hour Information

**Peak Hour 16:15 17:15**

	Eastbound			Westbound			Northbound			Southbound			Totals
	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	
Movement Total	21	23	36	3	8	4	3	64	10	24	93	7	296
Peak Hour Factor	0.88	0.82	0.60	0.75	0.67	0.50	0.75	0.80	0.83	0.86	0.89	0.88	0.83

Enter Totals	80			15			77			124		
Peak Hour Factor	0.71			0.75			0.80			0.91		

Exit Totals	33			42			103			118		
Peak Hour Factor	0.83			0.88			0.72			0.92		

Light Trucks	6	2	0	0	0	0	0	0	2	4	0	0	14
Medium Trucks	1	0	0	0	0	0	0	0	0	0	0	0	1
Heavy Trucks	0	0	0	0	0	0	0	0	0	0	0	0	0
% Trucks	33.3%	8.7%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	20.0%	16.7%	0.0%	0.0%	5.1%
Stopped Buses	0	0	0	0	0	0	0	0	0	0	0	0	0
Bicycles	0	0	0	0	0	0	0	0	0	0	0	0	0

Pedestrians	South 0	West 3	East 0	North 4	7
-------------	------------	-----------	-----------	------------	---

## Intersection Turning Movement Peak Hour Diagram


**Location** NE HAWTHORNE AVENUE AT NE 4TH STREET

**Date** 1/4/2007

**Day of Week** Thursday

**Time Begin** 16:00

**Reviewed By:** BV





## Intersection Turning Movement Summary Report

**Location** NW HAWTHORNE AVENUE AT BEND PARKWAY  
**Date** 1/3/2007  
**Day of Week** Wednesday  
**Time Begin** 16:00  
**Reviewed By:** BV

Time Period	Eastbound			Westbound			Northbound			Southbound			Totals
	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	
16:00 - 16:15	44	0	0	0	0	0	0	469	0	49	481	0	1043
16:15 - 16:30	38	0	0	0	0	0	0	452	0	36	443	0	969
16:30 - 16:45	38	0	0	0	0	0	0	438	0	41	461	0	978
16:45 - 17:00	35	0	0	0	0	0	0	416	0	43	454	0	948
17:00 - 17:15	61	0	0	0	0	0	0	545	0	37	552	0	1195
17:15 - 17:30	40	0	0	0	0	0	0	462	0	41	474	0	1017
17:30 - 17:45	50	0	0	0	0	0	0	331	0	42	425	0	848
17:45 - 18:00	34	0	0	0	0	0	0	306	0	43	333	0	716
<b>Movement Totals</b>	<b>340</b>	<b>0</b>	<b>0</b>	<b>0</b>	<b>0</b>	<b>0</b>	<b>0</b>	<b>3419</b>	<b>0</b>	<b>332</b>	<b>3623</b>	<b>0</b>	<b>7714</b>
Enter Totals	340			0			3419			3955			
Exit Totals	0			332			3419			3963			

### Two-Hour Totals

Light Trucks	1	0	0	0	0	0	0	56	0	15	57	0	129
Medium Trucks	0	0	0	0	0	0	0	16	0	2	19	0	37
Heavy Trucks	0	0	0	0	0	0	0	36	0	1	70	0	107
% Trucks	0.3%	NA	NA	NA	NA	NA	NA	3.2%	NA	5.4%	4.0%	NA	3.5%
Stopped Buses	0	0	0	0	0	0	0	0	0	0	0	0	0
Bicycles	0	0	0	0	0	0	0	0	0	0	0	0	0

	South	West	East	North	
Pedestrians	0	0	0	0	0

### Peak Hour Information

**Peak Hour 16:30 17:30**

	Eastbound			Westbound			Northbound			Southbound			Totals
	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	
Movement Total	174	0	0	0	0	0	0	1861	0	162	1941	0	4138
Peak Hour Factor	0.71	NA	NA	NA	NA	NA	NA	0.85	NA	0.94	0.88	NA	0.87

Enter Totals	174			0			1861			2103		
Peak Hour Factor	0.71			NA			0.85			0.89		

Exit Totals	0			162			1861			2115		
Peak Hour Factor	NA			0.94			0.85			0.86		

Light Trucks	1	0	0	0	0	0	0	24	0	4	26	0	55
Medium Trucks	0	0	0	0	0	0	0	10	0	0	8	0	18
Heavy Trucks	0	0	0	0	0	0	0	21	0	1	33	0	55
% Trucks	0.6%	NA	NA	NA	NA	NA	NA	3.0%	NA	3.1%	3.5%	NA	3.1%
Stopped Buses	0	0	0	0	0	0	0	0	0	0	0	0	0
Bicycles	0	0	0	0	0	0	0	0	0	0	0	0	0

	South	West	East	North	
Pedestrians	0	0	0	0	0

## Intersection Turning Movement Peak Hour Diagram


**Location** NW HAWTHORNE AVENUE AT BEND PARKWAY

**Date** 1/3/2007

**Day of Week** Wednesday

**Time Begin** 16:00

**Reviewed By:** BV





## Intersection Turning Movement Summary Report

**Location** NE FRANKLIN AVENUE AT NE 4TH STREET

**Date** 1/4/2007

**Day of Week** Thursday

**Time Begin** 16:00

**Reviewed By:** BV

Time Period	Eastbound			Westbound			Northbound			Southbound			Totals
	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	
16:00 - 16:15	9	121	8	1	89	1	7	2	4	25	5	1	273
16:15 - 16:30	8	109	9	5	75	6	5	4	5	16	1	3	246
16:30 - 16:45	9	124	13	2	84	6	11	4	5	28	4	4	294
16:45 - 17:00	5	90	12	3	81	3	5	4	4	21	3	2	233
17:00 - 17:15	10	139	14	2	87	4	12	6	5	38	2	2	321
17:15 - 17:30	5	133	14	1	88	1	3	3	6	18	1	3	276
17:30 - 17:45	4	90	13	2	72	3	12	3	4	23	2	1	229
17:45 - 18:00	3	75	6	2	52	2	5	2	5	22	2	3	179
<b>Movement Totals</b>	<b>53</b>	<b>881</b>	<b>89</b>	<b>18</b>	<b>628</b>	<b>26</b>	<b>60</b>	<b>28</b>	<b>38</b>	<b>191</b>	<b>20</b>	<b>19</b>	<b>2051</b>
Enter Totals	1023			672			126			230			
Exit Totals	960			857			135			99			

**Two-Hour Totals**

Light Trucks	0	8	0	4	4	0	2	0	1	13	0	0	32
Medium Trucks	1	1	0	0	1	0	0	0	0	0	1	0	4
Heavy Trucks	0	0	0	0	0	0	0	0	0	0	0	0	0
% Trucks	1.9%	1.0%	0.0%	22.2%	0.8%	0.0%	3.3%	0.0%	2.6%	6.8%	5.0%	0.0%	1.8%
Stopped Buses	0	0	0	0	0	0	0	0	0	0	0	0	0
Bicycles	0	0	0	0	0	0	0	0	0	0	0	0	0

	South	West	East	North	
Pedestrians	0	6	0	3	9

### Peak Hour Information

**Peak Hour 16:30 17:30**

	Eastbound			Westbound			Northbound			Southbound			Totals
	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	
Movement Total	29	486	53	8	340	14	31	17	20	105	10	11	1124
Peak Hour Factor	0.73	0.87	0.95	0.67	0.97	0.58	0.65	0.71	0.83	0.69	0.63	0.69	0.88

Enter Totals	568			362			68			126		
Peak Hour Factor	0.87			0.97			0.74			0.75		

Exit Totals	528			465			78			53		
Peak Hour Factor	0.86			0.89			0.89			0.70		

Light Trucks	0	5	0	1	2	0	1	0	0	6	0	0	15
Medium Trucks	1	0	0	0	1	0	0	0	0	0	1	0	3
Heavy Trucks	0	0	0	0	0	0	0	0	0	0	0	0	0
% Trucks	3.4%	1.0%	0.0%	12.5%	0.9%	0.0%	3.2%	0.0%	0.0%	5.7%	10.0%	0.0%	1.6%
Stopped Buses	0	0	0	0	0	0	0	0	0	0	0	0	0
Bicycles	0	0	0	0	0	0	0	0	0	0	0	0	0

	South	West	East	North	
Pedestrians	0	2	0	1	3

## Intersection Turning Movement Peak Hour Diagram


**Location** NE FRANKLIN AVENUE AT NE 4TH STREET

**Date** 1/4/2007

**Day of Week** Thursday

**Time Begin** 16:00

**Reviewed By:** BV





## Intersection Turning Movement Summary Report

**Location** TUMALO AVENUE AT NW RIVERSIDE BOULEVARD

**Date** 1/3/2007

**Day of Week** Wednesday

**Time Begin** 16:00

**Reviewed By:** TM

Time Period	Eastbound			Westbound			Northbound			Southbound			Totals
	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	
16:00 - 16:15	1	32	68	0	23	1	0	2	2	78	2	3	212
16:15 - 16:30	4	31	58	0	36	0	0	2	9	99	5	0	244
16:30 - 16:45	6	40	66	0	32	0	1	1	7	100	6	6	265
16:45 - 17:00	4	38	50	2	28	0	1	1	9	111	8	2	254
17:00 - 17:15	7	37	50	1	52	1	0	1	11	93	4	1	258
17:15 - 17:30	7	35	70	0	47	0	0	1	14	88	6	1	269
17:30 - 17:45	6	35	45	0	40	0	1	4	12	80	6	4	233
17:45 - 18:00	5	27	52	1	26	1	1	1	5	63	7	1	190
<b>Movement Totals</b>	<b>40</b>	<b>275</b>	<b>459</b>	<b>4</b>	<b>284</b>	<b>3</b>	<b>4</b>	<b>13</b>	<b>69</b>	<b>712</b>	<b>44</b>	<b>18</b>	<b>1925</b>
Enter Totals	774			291			86			774			
Exit Totals	297			1065			476			87			

### Two-Hour Totals

Light Trucks	0	3	23	0	2	0	0	0	1	14	1	1	45
Medium Trucks	0	0	1	0	0	0	0	0	0	0	0	0	1
Heavy Trucks	0	0	0	0	0	0	0	0	0	1	0	0	1
% Trucks	0.0%	1.1%	5.2%	0.0%	0.7%	0.0%	0.0%	0.0%	1.4%	2.1%	2.3%	5.6%	2.4%
Stopped Buses	0	0	0	0	0	0	0	0	0	0	0	0	0
Bicycles	0	0	0	0	0	0	0	0	0	0	0	0	0

	South	West	East	North	
Pedestrians	0	0	0	0	0

### Peak Hour Information

**Peak Hour 16:30 17:30**

	Eastbound			Westbound			Northbound			Southbound			Totals
	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	
Movement Total	24	150	236	3	159	1	2	4	41	392	24	10	1046
Peak Hour Factor	0.86	0.94	0.84	0.38	0.76	0.25	0.50	1.00	0.73	0.88	0.75	0.42	0.97

Enter Totals	410			163			47			426		
Peak Hour Factor	0.92			0.75			0.78			0.88		

Exit Totals	162			592			243			49		
Peak Hour Factor	0.86			0.95			0.86			0.94		

Light Trucks	0	2	14	0	0	0	0	0	1	8	1	0	26
Medium Trucks	0	0	1	0	0	0	0	0	0	0	0	0	1
Heavy Trucks	0	0	0	0	0	0	0	0	0	1	0	0	1
% Trucks	0.0%	1.3%	6.4%	0.0%	0.0%	0.0%	0.0%	0.0%	2.4%	2.3%	4.2%	0.0%	2.7%
Stopped Buses	0	0	0	0	0	0	0	0	0	0	0	0	0
Bicycles	0	0	0	0	0	0	0	0	0	0	0	0	0

	South	West	East	North	
Pedestrians	0	0	0	0	0

## Intersection Turning Movement Peak Hour Diagram


**Location** TUMALO AVENUE AT NW RIVERSIDE BOULEVARD

**Date** 1/3/2007

**Day of Week** Wednesday

**Time Begin** 16:00

**Reviewed By:** TM





## Intersection Turning Movement Summary Report

**Location** COLORADO AVENUE AT BEND PARKWAY-NB RAMP

**Date** 1/3/2007

**Day of Week** Wednesday

**Time Begin** 16:00

**Reviewed By:** TM

Time Period	Eastbound			Westbound			Northbound			Southbound			Totals
	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	
16:00 - 16:15	0	36	141	69	31	0	0	0	0	34	0	3	314
16:15 - 16:30	0	47	135	67	31	0	0	0	0	42	0	5	327
16:30 - 16:45	0	34	121	78	43	0	0	0	0	48	0	1	325
16:45 - 17:00	0	33	119	63	37	0	0	0	0	39	0	4	295
17:00 - 17:15	0	44	179	129	50	0	0	0	0	39	0	1	442
17:15 - 17:30	0	49	167	69	21	0	0	0	0	39	0	4	349
17:30 - 17:45	0	36	103	53	31	0	0	0	0	28	0	0	251
17:45 - 18:00	0	26	64	44	20	0	0	0	0	28	0	5	187
Movement Totals	0	305	1029	572	264	0	0	0	0	297	0	23	2490
Enter Totals	1334			836			0			320			
Exit Totals	328			561			1601			0			

### Two-Hour Totals

Light Trucks	0	13	23	23	9	0	0	0	0	6	0	2	76
Medium Trucks	0	2	8	0	0	0	0	0	0	0	0	1	11
Heavy Trucks	0	2	3	3	1	0	0	0	0	0	0	0	9
% Trucks	NA	5.6%	3.3%	4.5%	3.8%	NA	NA	NA	NA	2.0%	NA	13.0%	3.9%
Stopped Buses	0	0	1	0	0	0	0	0	0	0	0	0	1
Bicycles	0	0	0	0	0	0	0	0	0	0	0	0	0

	South	West	East	North	
Pedestrians	0	0	0	0	0

### Peak Hour Information

**Peak Hour 16:30 17:30**

	Eastbound			Westbound			Northbound			Southbound			Totals
	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	Right	Thru	Left	
Movement Total	0	160	586	339	151	0	0	0	0	165	0	10	1411
Peak Hour Factor	NA	0.82	0.82	0.66	0.76	NA	NA	NA	NA	0.86	NA	0.63	0.80

Enter Totals	746			490			0			175		
Peak Hour Factor	0.84			0.68			NA			0.89		

Exit Totals	170			316			925			0		
Peak Hour Factor	0.80			0.87			0.75			NA		

Light Trucks	0	8	13	9	3	0	0	0	0	1	0	1	35
Medium Trucks	0	1	3	0	0	0	0	0	0	0	0	0	4
Heavy Trucks	0	2	1	1	0	0	0	0	0	0	0	0	4
% Trucks	NA	6.9%	2.9%	2.9%	2.0%	NA	NA	NA	NA	0.6%	NA	10.0%	3.0%
Stopped Buses	0	0	1	0	0	0	0	0	0	0	0	0	1
Bicycles	0	0	0	0	0	0	0	0	0	0	0	0	0

	South	West	East	North	
Pedestrians	0	0	0	0	0

## Intersection Turning Movement Peak Hour Diagram


**Location** COLORADO AVENUE AT BEND PARKWAY-NB RAMP

**Date** 1/3/2007

**Day of Week** Wednesday

**Time Begin** 16:00

**Reviewed By:** TM



**APPENDIX E**

---

**Seasonal Adjustments to Traffic Counts**

Turning Movement Count  
60 Minute Counts

2007 HV Unbalanced

DATE	TIME	INTID	INTNAME	EB-R	EB-T	EB-L	WB-R	WB-T	WB-L	NB-R	NB-T	NB-L	SB-R
1/2/2007	1615	101	Butler Market Rd & US 20	150	140	85	190	150	410	160	995	120	85
1/2/2007	1615	102	Butler Mkt Rd & Bend Pkwy SB Ramp	0	620	0	0	720	0	0	0	0	125
1/2/2007	1615	103	Butler Mkt Rd & Bend Pkwy NB Ramp	10	795	80	260	780	10	20	5	20	0
1/3/2007	1615	104	Butler Mkt Rd & 4th St	150	620	0	0	620	95	85	0	280	45
1/2/2007	1615	105	Studio Rd & 4th St	5	10	5	30	10	155	280	410	0	0
1/2/2007	1615	106	Revere Ave & Bend Pkwy SB Ramp	10	15	15	355	25	610	700	115	15	5
1/2/2007	1615	107	Revere Ave & Bend Pkwy NB Ramp	445	375	170	125	490	50	565	285	115	305
1/2/2007	1615	108	Revere Ave & 3rd St	250	555	270	65	370	240	100	1280	125	65
1/2/2007	1615	109	Revere Ave & 4th St	140	355	280	120	345	25	45	245	80	280
1/2/2007	1615	110	Portland Ave & Hill St	115	220	320	105	300	80	110	520	160	405
1/2/2007	1615	111	Olney Ave & 3rd St	85	280	130	110	325	135	115	1460	95	25
1/2/2007	1615	112	Olney Ave & 4th St	40	365	105	45	360	50	75	235	45	90
1/3/2007	1615	113	Lafayette Ave & Bend Pkwy SB Ramp	125	0	0	0	0	0	0	2590	0	75
1/2/2007	1615	114	<b>Bond St &amp; Wall St.</b>	0	190	10	10	570	0	435	10	60	40
1/4/2007	1615	115	<b>Newport Ave &amp; Wall St.</b>	160	410	150	35	505	290	0	0	0	175
1/3/2007	1615	116	<b>Newport Ave &amp; Bond St</b>	0	490	15	60	690	0	355	435	240	0
1/4/2007	1615	117	Greenwood Ave & 3rd St	135	800	310	295	585	300	285	930	150	105
1/4/2007	1615	118	Greenwood Ave & 4th St	25	1330	30	140	1055	70	130	5	0	155
1/4/2007	1615	119	Hawthorne Ave & 3rd St	40	5	15	55	5	0	35	1385	10	25
1/4/2007	1615	120	Hawthorne Ave & 4th St	30	30	50	5	10	5	5	90	15	35
1/3/2007	1615	121	<b>Oregon St &amp; Wall St.</b>	25	25	0	0	70	215	0	0	0	50
1/3/2007	1615	122	<b>Oregon St &amp; Bond St</b>	0	115	110	170	95	0	110	810	180	0
1/3/2007	1615	123	Hawthorne Ave & Bend Pkwy SB Ramp	245	0	0	0	0	0	0	2610	0	220
1/3/2007	1615	124	<b>Franklin Ave &amp; Wall St.</b>	30	465	0	0	390	175	0	0	0	270
1/3/2007	1615	125	<b>Franklin Ave &amp; Bond St</b>	0	435	255	115	505	0	285	675	60	0
1/4/2007	1615	126	Franklin Ave & 3rd St	115	650	345	70	425	180	45	1035	175	130
1/4/2007	1615	127	Franklin Ave & 4th St	45	650	70	15	460	25	45	25	25	145
1/3/2007	1615	128	Tumalo Ave & Riverside Dr	30	205	315	5	210	0	5	5	50	570
1/3/2007	1615	129	<b>Colorado Ave &amp; Wall St</b>	0	0	0	0	615	115	0	0	0	160
1/3/2007	1615	130	Colorado Ave & Bond St	0	0	0	145	640	0	0	740	80	0
1/3/2007	1615	131	Arizona Ave & Wall St	25	1180	0	0	0	0	0	0	0	0
1/3/2007	1615	132	Arizona Ave & Bond St	0	985	385	0	0	0	160	430	0	0
1/3/2007	1615	133	Colorado Ave & Bend Pkwy SB Ramp	0	0	0	65	400	5	935	205	10	345
1/3/2007	1615	134	Colorado Ave & Bend Pkwy NB Ramp	0	225	780	475	225	0	0	0	0	235

**Seasonal Adjustment for 30HV**

US 97 Dalles-California Hwy	Hwy 04
ATR 09-C Summer	Weekday
Seasonal Factor Peak Period	
0.8378	
Count Date Factor	
1-Jan	1.1815
Adjustment Factor =Count Date Factor/ Seasonal Peak Period Factor	
	1.4102

Turning Movement Count      2007 HV Balanced  
60 Minute Counts

DATE	TIME	INTID	INTNAME	EBR	EBT	EBL	WBR	WBT	WBL	NBR	NBT	NBL	SBR	SBT	SBL
1/2/2007	1615	101	Butler Market Rd & US 20	150	140	85	190	150	410	160	995	120	85	1360	215
1/2/2007	1615	102	Butler Mkt Rd & Bend Pkwy SB Ramp	0	620	0	0	760	0	0	0	0	125	0	255
1/2/2007	1615	103	Butler Mkt Rd & Bend Pkwy NB Ramp	10	785	80	255	760	10	20	5	20	0	0	0
1/3/2007	1615	104	Butler Mkt Rd & 4th St	155	635	0	0	655	95	85	0	295	45	5	0
1/2/2007	1615	105	Studio Rd & 4th St	5	10	5	30	10	155	280	410	0	0	485	80
1/2/2007	1615	106	Revere Ave & Bend Pkwy SB Ramp	10	15	15	350	25	595	730	115	15	5	230	205
1/2/2007	1615	107	Revere Ave & Bend Pkwy NB Ramp	440	365	160	125	510	50	585	285	120	315	5	140
1/2/2007	1615	108	Revere Ave & 3rd St	250	565	270	65	395	240	105	1365	135	70	815	80
1/2/2007	1615	109	Revere Ave & 4th St	140	350	275	120	345	25	45	245	80	280	185	170
1/2/2007	1615	110	Portland Ave & Hill St	115	220	320	105	300	80	110	520	160	405	350	40
1/2/2007	1615	111	Olney Ave & 3rd St	85	280	130	105	315	130	115	1460	95	25	1105	140
1/2/2007	1615	112	Olney Ave & 4th St	40	385	105	45	385	50	75	235	45	100	140	140
1/3/2007	1615	113	Lafayette Ave & Bend Pkwy SB Ramp	125	0	0	0	0	0	0	2610	0	75	2725	0
1/2/2007	1615	114	<b>Bond St &amp; Wall St.</b>	0	190	10	10	605	0	435	10	65	45	0	20
1/4/2007	1615	115	<b>Newport Ave &amp; Wall St.</b>	160	410	150	40	565	325	0	0	0	170	455	115
1/3/2007	1615	116	<b>Newport Ave &amp; Bond St</b>	0	510	15	60	690	0	370	450	240	0	0	0
1/4/2007	1615	117	Greenwood Ave & 3rd St	135	775	310	295	585	300	295	960	150	110	745	325
1/4/2007	1615	118	Greenwood Ave & 4th St	25	1330	30	140	1055	70	130	5	0	155	0	0
1/4/2007	1615	119	Hawthorne Ave & 3rd St	45	5	15	55	5	0	35	1385	10	25	1220	35
1/4/2007	1615	120	Hawthorne Ave & 4th St	30	30	50	5	10	5	5	90	15	35	130	10
1/3/2007	1615	121	<b>Oregon St &amp; Wall St.</b>	25	25	0	0	70	205	0	0	0	20	835	140
1/3/2007	1615	122	<b>Oregon St &amp; Bond St</b>	0	100	100	165	95	0	110	795	175	0	0	0
1/3/2007	1615	123	Hawthorne Ave & Bend Pkwy SB Ramp	245	0	0	0	0	0	0	2610	0	220	2695	0
1/3/2007	1615	124	<b>Franklin Ave &amp; Wall St.</b>	30	465	0	0	390	175	0	0	0	280	510	235
1/3/2007	1615	125	<b>Franklin Ave &amp; Bond St</b>	0	435	260	115	505	0	285	690	60	0	0	0
1/4/2007	1615	126	Franklin Ave & 3rd St	115	640	345	70	415	180	45	1035	175	125	1045	105
1/4/2007	1615	127	Franklin Ave & 4th St	45	660	70	15	470	25	45	25	25	145	15	15
1/3/2007	1615	128	Tumalo Ave & Riverside Dr	30	205	315	5	210	0	5	5	50	570	30	15
1/3/2007	1615	129	<b>Colorado Ave &amp; Wall St</b>	0	0	0	0	615	115	0	0	0	160	485	0
1/3/2007	1615	130	Colorado Ave & Bond St	0	0	0	145	640	0	0	740	80	0	0	0
1/3/2007	1615	131	Arizona Ave & Wall St	25	1170	0	0	0	0	0	0	0	0	390	220
1/3/2007	1615	132	Arizona Ave & Bond St	0	990	390	0	0	0	160	430	0	0	0	0
1/3/2007	1615	133	Colorado Ave & Bend Pkwy SB Ramp	0	0	0	65	400	5	930	205	10	345	0	95
1/3/2007	1615	134	Colorado Ave & Bend Pkwy NB Ramp	0	230	795	475	230	0	0	0	0	240	0	15

Turning Movement Count  
60Minute Counts

2007 Raw Counts

DATE	TIME	INTID	INTNAME	EB-R	EB-T	EB-L	WB-R	WB-T	WB-L	NB-R	NB-T	NB-L	SB-R	SB-T	SB-L
1/2/2007	1615	101	Butler Market Rd & US 20	106	101	61	133	108	291	112	706	84	62	965	153
1/2/2007	1615	102	Butler Mkt Rd & Bend Pkwy SB Ramp	0	439	0	0	511	0	0	0	0	88	0	176
1/2/2007	1615	103	Butler Mkt Rd & Bend Pkwy NB Ramp	8	562	55	186	552	8	14	5	13	0	0	0
1/3/2007	1615	104	Butler Mkt Rd & 4th St	107	438	1	1	440	69	61	0	199	31	5	0
1/2/2007	1615	105	Studio Rd & 4th St	5	8	2	22	7	109	199	289	0	0	344	57
1/2/2007	1615	106	Revere Ave & Bend Pkwy SB Ramp	6	10	9	252	16	433	495	82	11	4	164	140
1/2/2007	1615	107	Revere Ave & Bend Pkwy NB Ramp	316	265	121	88	348	35	400	201	82	215	5	88
1/2/2007	1615	108	Revere Ave & 3rd St	177	394	190	46	262	170	71	909	88	46	579	54
1/2/2007	1615	109	Revere Ave & 4th St	99	252	197	85	244	19	31	175	55	198	130	120
1/2/2007	1615	110	Portland Ave & Hill St	81	156	226	74	211	56	79	367	113	288	248	27
1/2/2007	1615	111	Olney Ave & 3rd St	61	199	92	78	229	96	82	1034	69	16	782	99
1/2/2007	1615	112	Olney Ave & 4th St	27	258	74	33	255	35	54	165	33	64	100	100
1/3/2007	1615	113	Lafayette Ave & Bend Pkwy SB Ramp	89	0	0	0	0	0	0	1838	0	52	1932	0
1/2/2007	1615	114	<b>Bond St &amp; Wall St.</b>	1	133	8	8	404	0	309	6	42	27	0	14
1/4/2007	1615	115	<b>Newport Ave &amp; Wall St.</b>	112	290	107	24	359	206	0	0	0	124	334	82
1/3/2007	1615	116	<b>Newport Ave &amp; Bond St</b>	0	346	9	44	491	0	251	308	170	0	0	0
1/4/2007	1615	117	Greenwood Ave & 3rd St	96	568	219	209	414	211	203	658	107	76	504	219
1/4/2007	1615	118	Greenwood Ave & 4th St	16	943	22	98	747	48	92	2	0	111	1	1
1/4/2007	1615	119	Hawthorne Ave & 3rd St	29	2	10	38	3	0	24	983	7	18	798	26
1/4/2007	1615	120	Hawthorne Ave & 4th St	21	23	36	3	8	4	3	64	10	24	93	7
1/3/2007	1615	121	<b>Oregon St &amp; Wall St.</b>	18	18	0	0	48	151	0	0	0	36	593	92
1/3/2007	1615	122	<b>Oregon St &amp; Bond St</b>	0	82	77	120	69	0	77	575	128	0	0	0
1/3/2007	1615	123	Hawthorne Ave & Bend Pkwy SB Ramp	172	0	0	0	0	0	0	1851	0	157	1910	0
1/3/2007	1615	124	<b>Franklin Ave &amp; Wall St.</b>	21	329	0	0	278	124	0	0	0	193	349	160
1/3/2007	1615	125	<b>Franklin Ave &amp; Bond St</b>	0	307	182	82	358	0	203	477	44	0	0	0
1/4/2007	1615	126	Franklin Ave & 3rd St	83	462	243	48	301	126	32	733	124	92	771	79
1/4/2007	1615	127	Franklin Ave & 4th St	32	462	48	12	327	19	33	18	19	103	10	11
1/3/2007	1615	128	Tumalo Ave & Riverside Dr	21	146	224	3	148	1	2	5	36	403	23	9
1/3/2007	1615	129	<b>Colorado Ave &amp; Wall St</b>	0	0	0	0	437	81	0	0	0	114	337	0
1/3/2007	1615	130	Colorado Ave & Bond St	0	0	0	103	454	0	0	523	56	0	0	0
1/3/2007	1615	131	Arizona Ave & Wall St	19	835	0	0	0	0	0	0	0	0	276	156
1/3/2007	1615	132	Arizona Ave & Bond St	0	700	272	0	0	0	114	305	0	0	0	0
1/3/2007	1615	133	Colorado Ave & Bend Pkwy SB Ramp	0	0	0	46	283	3	662	144	6	246	1	71
1/3/2007	1615	134	Colorado Ave & Bend Pkwy NB Ramp	0	158	554	337	161	0	0	0	0	168	0	11

**APPENDIX F**

---

**2006 Intersection Traffic Operations Analysis Worksheets**

101: Butler Market Rd & US 20

2007 PM Peak Hour


Baseline

Lane Group	EBL	EBT	EBR	WBL	WBT	NBL	NBT	SBL	SBT	SBR
Lane Configurations	85	140	150	410	150	120	995	215	1360	85
Volume (vph)	92	152	163	446	370	130	1256	234	1478	92
Lane Group Flow (vph)	Prot	Perm								
Turn Type	3	8	8	7	4	1	6	5	2	2
Protected Phases	3	8	8	7	4	1	6	5	2	2
Detector Phases	3	8	8	7	4	1	6	5	2	2
Minimum Initial (s)	6.0	8.0	8.0	6.0	5.0	5.0	10.0	5.0	10.0	10.0
Minimum Split (s)	10.0	12.0	12.0	10.0	25.0	8.5	31.0	8.5	31.0	31.0
Total Split (s)	11.0	20.0	20.0	15.0	24.0	13.0	43.0	17.0	47.0	47.0
Total Split (%)	11.6%	21.1%	21.1%	15.8%	25.3%	13.7%	45.3%	17.9%	49.5%	49.5%
Yellow Time (s)	4.0	4.0	4.0	4.0	3.5	5.0	3.5	5.0	5.0	5.0
All-Red Time (s)	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Lead/Lag	Lead	Lag	Lag	Lead	Lead	Lead	Lead	Lag	Lag	Lag
Lead-Lag Optimizer?	Yes									
Recall Mode	Max									
v/c Ratio	0.71	0.48	0.41	1.12	0.91	0.77	0.87	0.97	0.92	0.12
Control Delay	72.4	41.7	9.1	122.1	58.8	72.3	33.6	92.8	35.5	4.0
Queue Delay	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Delay	72.4	41.7	9.1	122.1	58.8	72.3	33.6	92.8	35.5	4.0
Queue Length 50th (ft)	55	84	0	~161	186	78	352	142	426	1
Queue Length 95th (ft)	#133	146	54	#257	#357	#173	#461	#290	#585	27
Internal Link Dist (ft)		466		381		888		693		
Turn Bay Length (ft)										
Base Capacity (vph)	130	314	402	398	407	168	1436	242	1602	766
Starvation Cap Reductn	0	0	0	0	0	0	0	0	0	0
Spillback Cap Reductn	0	0	0	0	0	0	0	0	0	0
Storage Cap Reductn	0	0	0	0	0	0	0	0	0	0
Reduced v/c Ratio	0.71	0.48	0.41	1.12	0.91	0.77	0.87	0.97	0.92	0.12

Intersection Summary

Cycle Length: 95	Actuated Cycle Length: 95
Offset: 13 (14%), Referenced to phase 2:SBT and 6:NBT, Start of Green	Natural Cycle: 90
Control Type: Pretimed	Volume exceeds capacity, queue is theoretically infinite.
Queue shown is maximum after two cycles.	# 95th percentile volume exceeds capacity, queue may be longer.
Queue shown is maximum after two cycles.	

Splits and Phases: 101: Butler Market Rd & US 20



HCM Signalized Intersection Capacity Analysis

2007 PM Peak Hour

Baseline

Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Ideal Flow (vphpl)	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0
Total Lost time (s)	1.00	1.00	1.00	0.97	1.00	1.00	0.95	1.00	0.95	1.00	0.95	1.00
Lane Util. Factor	1.00	1.00	0.85	1.00	0.92	1.00	0.98	1.00	0.98	1.00	1.00	0.85
Fit Protected	0.95	1.00	1.00	0.95	1.00	1.00	0.95	1.00	0.95	1.00	1.00	1.00
Satd. Flow (prot)	1770	1863	1583	3433	1706	1770	3466	1770	3466	1770	3539	1583
Fit Permitted	0.95	1.00	1.00	0.95	1.00	1.00	0.95	1.00	0.95	1.00	1.00	1.00
Satd. Flow (perm)	1770	1863	1583	3433	1706	1770	3466	1770	3466	1770	3539	1583
Volume (vph)	85	140	150	410	150	190	120	995	160	215	1360	85
Peak-hour factor, PHF	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Adtl. Flow (vph)	92	152	163	446	163	207	130	1082	174	234	1478	92
RTOR Reduction (vph)	0	0	136	0	48	0	14	0	0	0	0	49
Lane Group Flow (vph)	92	152	27	446	322	0	130	1242	0	234	1478	43
Turn Type	Prot	Perm	Prot	Prot	Prot	Prot	Prot	Prot	Prot	Prot	Perm	Perm
Protected Phases	3	8	8	7	4	1	6	5	2	2	2	2
Actuated Green, G (s)	7.0	16.0	16.0	11.0	20.0	9.5	38.0	13.5	42.0	42.0	42.0	42.0
Effective Green, g (s)	7.0	16.0	16.0	11.0	20.0	9.0	39.0	13.0	43.0	43.0	43.0	43.0
Actuated g/c Ratio	0.07	0.17	0.17	0.12	0.21	0.09	0.41	0.14	0.45	0.45	0.45	0.45
Clearance Time (s)	4.0	4.0	4.0	4.0	4.0	3.5	5.0	3.5	5.0	5.0	5.0	5.0
Lane Grp Cap (vph)	130	314	267	398	359	168	1423	242	1602	717		
v/s Ratio Prot	0.05	0.08	0.02	c0.13	c0.19	0.07	c0.36	0.13	c0.42	0.03		
v/s Ratio Perm	0.71	0.48	0.10	1.12	0.90	0.77	0.87	0.97	0.92	0.06		
Uniform Delay, d1	43.0	35.8	33.4	42.0	36.5	42.0	25.7	40.8	24.4	14.6		
Progression Factor	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00		
Incremental Delay, d2	27.7	5.3	0.8	82.1	27.4	28.6	7.7	49.9	10.3	0.2		
Delay (s)	70.7	41.0	34.2	124.1	63.9	70.6	33.4	90.7	34.8	14.8		
Level of Service	E	D	C	D	F	E	C	E	C	B		
Approach Delay (s)	45.0											
Approach LOS	D											

Intersection Summary

HCM Average Control Delay	50.4	HCM Level of Service	D
HCM Volume to Capacity ratio	0.97		
Actuated Cycle Length (s)	95.0	Sum of lost time (s)	16.0
Intersection Capacity Utilization	82.4%	ICU Level of Service	E
Analysis Period (min)	15		
c Critical Lane Group			

HCM Unsignalized Intersection Capacity Analysis  
 102: Butler Mkt Rd & Bend Pkwy SB Ramp  
 2007 PM Peak Hour  
 Baseline

Movement	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations	Free	Free	Stop	Stop		
Sign Control	0%	0%	0%	0%		
Grade	0	620	760	0	255	125
Volume (veh/h)	0	0.92	0.92	0.92	0.92	0.92
Peak Hour Factor	0	674	826	0	277	136
Hourly flow rate (vph)						
Pedestrians						
Lane Width (ft)						
Walking Speed (ft/s)						
Percent Blockage						
Right turn flare (veh)						
Median type					TWLT	
Median storage (veh)					1	
Upstream signal (ft)					461	
PX, platoon unblocked					0.93	
VC, conflicting volume					1500	826
VC1, stage 1 conf vol					826	
VC2, stage 2 conf vol					674	
VCU, unblocked vol					1535	826
TC, single (s)					6.4	6.2
TC, 2 stage (s)					5.4	
IF (s)					2.2	3.3
p0 queue free %					100	63
cm capacity (veh/h)					805	262 372
Direction, Lane #	EB 1	WB 1	SB 1			
Volume Total	674	826	413			
Volume Left	0	0	277			
Volume Right	0	0	136			
CSH	1700	1700	290			
Volume to Capacity	0.40	0.49	1.42			
Queue Length 95th (ft)	0	0	537			
Control Delay (s)	0.0	0.0	242.5			
Lane LOS	F	F	F			
Approach Delay (s)	0.0	0.0	242.5			
Approach LOS	F	F	F			
<b>Intersection Summary</b>						
Average Delay	52.4					
Intersection Capacity Utilization	68.4%		ICU Level of Service	C		
Analysis Period (min)	15					

HCM Unsignalized Intersection Capacity Analysis  
 103: Butler Mkt Rd & Bend Pkwy NB Ramp  
 2007 PM Peak Hour  
 Baseline

Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations	Free	Free	Free	Free	Free	Free	Stop	Stop	Stop			
Sign Control	0%	0%	0%	0%	0%	0%	0%	0%	0%			
Grade	80	785	10	10	760	255	20	20	0	0	0	0
Volume (veh/h)	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Peak Hour Factor	87	853	11	11	826	277	22	5	22	0	0	0
Hourly flow rate (vph)												
Pedestrians												
Lane Width (ft)												
Walking Speed (ft/s)												
Percent Blockage												
Right turn flare (veh)												
Median type										TWLT		None
Median storage (veh)										1		
Upstream signal (ft)										910		
PX, platoon unblocked							0.98	0.98	0.98	0.98	0.98	0.98
VC, conflicting volume							1103	864	1880	2158	859	2038 2024 965
VC1, stage 1 conf vol							1033	1033				
VC2, stage 2 conf vol							848	1125				
VCU, unblocked vol							1103	861	1901	2185	855	2062 2048 965
TC, single (s)							4.1	4.1	6.4	6.5	6.2	7.1 6.5 6.2
TC, 2 stage (s)							2.2	2.2	5.4	5.5		
IF (s)							2.2	2.2	3.5	4.0	3.3	4.0 3.3
p0 queue free %							86	99	87	95	94	100 100 100
cm capacity (veh/h)							633	763	171	117	350	32 46 309
Direction, Lane #	EB 1	EB 2	WB 1	WB 2	NB 1	NB 2						
Volume Total	87	864	11	11	1103	49						
Volume Left	87	0	11	0	22	22						
Volume Right	0	11	0	277	22	22						
CSH	633	1700	763	1700	207	207						
Volume to Capacity	0.14	0.51	0.01	0.65	0.24	0.24						
Queue Length 95th (ft)	12	0	1	0	22	22						
Control Delay (s)	11.6	0.0	9.8	0.0	27.6	27.6						
Lane LOS	B	A	A	D	D	D						
Approach Delay (s)	1.1	0.1	0.1	27.6								
Approach LOS	D	D	D	D								
<b>Intersection Summary</b>												
Average Delay	1.2											
Intersection Capacity Utilization	73.3%			ICU Level of Service	D							
Analysis Period (min)	15											
* User Entered Value												

HCM Unsignalized Intersection Capacity Analysis  
 104: Butler Mkt Rd & 4th St  
 2007 PM Peak Hour  
 Baseline

Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations	Free	Free	Free	Free	Free	Free	Stop	Stop	Stop	Stop	Stop	Stop
Sign Control	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%
Volume (veh/h)	0	635	155	95	655	0	295	0	85	0	5	45
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Hourly Flow rate (vph)	0	690	168	103	712	0	321	0	92	0	5	49
Pedestrians												
Lane Width (ft)												
Walking Speed (ft/s)												
Percent Blockage												
Right turn flare (veh)												
Median type							TWLT					
Median storage (veh)							1					
Upstream signal (ft)												
pX, platoon unblocked												
VC1, conflicting volume	712			859			1745	1693	774	1701	1777	712
VC1, stage 1 conf vol							774	774				
VC2, stage 2 conf vol							970	918				
VCU, unblocked vol	712			859			1745	1693	774	1701	1777	712
TC, single (s)	4.1			4.1			7.1	6.5	6.2	7.1	6.5	6.2
TC, 2 stage (s)							6.1	5.5				
IF (s)	2.2			2.2			3.5	4.0	3.3	3.5	4.0	3.3
p0 queue free %	100			87			0	100	77	100	92	89
cm capacity (veh/h)	888			782			148	195	398	50	72	432
Direction, Lane #	EB 1	EB 2	WB 1	WB 2	NB 1	NB 2	SB 1					
Volume Total	0	859	103	712	321	92	54					
Volume Left	0	0	103	0	321	0	0					
Volume Right	0	168	0	0	92	49						
CSH	1700	1700	782	1700	148	398	287					
Volume to Capacity	0.00	0.51	0.13	0.42	2.16	0.23	0.19					
Queue Length 95th (ft)	0	0	11	0	654	22	17					
Control Delay (s)	0.0	0.0	10.3	0.0	595.2	16.8	20.4					
Lane LOS			B		F	C	C					
Approach Delay (s)	0.0		1.3		465.8		20.4					
Approach LOS			F		F		C					
<b>Intersection Summary</b>												
Average Delay	90.9											
Intersection Capacity Utilization	81.1%											
ICU Level of Service	D											
Analysis Period (min)	15											

HCM Unsignalized Intersection Capacity Analysis  
 105: Studio Rd & 4th St  
 2007 PM Peak Hour  
 Baseline


Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations	Stop	Stop	Stop	Stop	Stop	Stop	Free	Free	Free	Free	Free	Free
Sign Control	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%
Volume (veh/h)	5	10	5	155	10	30	0	410	280	80	485	0
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Hourly Flow rate (vph)	5	11	5	168	11	33	0	446	304	87	527	0
Pedestrians												
Lane Width (ft)												
Walking Speed (ft/s)												
Percent Blockage												
Right turn flare (veh)												
Median type												
Median storage (veh)												
Upstream signal (ft)												
pX, platoon unblocked												
VC1, conflicting volume	1337	1451	527	1310	1299	598	527					
VC1, stage 1 conf vol												
VC2, stage 2 conf vol												
VCU, unblocked vol	1337	1451	527	1310	1299	598	527					
TC, single (s)	7.1	6.5	6.2	7.1	6.5	6.2	4.1					
TC, 2 stage (s)												
IF (s)	3.5	4.0	3.3	3.5	4.0	3.3	2.2					
p0 queue free %	95	91	99	0	93	94	100					
cm capacity (veh/h)	106	117	551	116	145	502	1040					
Direction, Lane #	EB 1	WB 1	NB 1	SB 1								
Volume Total	22	212	750	614								
Volume Left	5	168	0	87								
Volume Right	5	33	304	0								
CSH	141	133	1040	859								
Volume to Capacity	0.15	1.60	0.00	0.10								
Queue Length 95th (ft)	13	37.9	0	8								
Control Delay (s)	35.0	360.3	0.0	2.6								
Lane LOS	E	F	A	A								
Approach Delay (s)	35.0	360.3	0.0	2.6								
Approach LOS	E	F	F	F								
<b>Intersection Summary</b>												
Average Delay	49.3											
Intersection Capacity Utilization	96.2%											
ICU Level of Service	F											
Analysis Period (min)	15											

106: Reverse Ave & Bend Pkwy SB Ramp

2007 PM Peak Hour

Baseline

Lane Group	EBT	WBL	WBT	NBL	NBT	NBR	SBL	SBT
Lane Configurations	4	1	1	1	1	1	1	1
Volume (vph)	15	595	25	15	115	730	205	230
Lane Group Flow (vph)	43	647	407	16	125	793	223	235
Turn Type	Split	Perm	Perm	pm+ov	Perm	Perm	Perm	2
Protected Phases	7	3	3	6	6	6	2	2
Detector Phases	7	3	3	6	6	6	3	2
Minimum Initial (s)	10.0	6.0	6.0	10.0	10.0	6.0	10.0	10.0
Minimum Split (s)	14.0	27.0	27.0	24.0	27.0	24.0	24.0	24.0
Total Split (s)	14.0	32.0	32.0	24.0	24.0	32.0	24.0	24.0
Yellow Time (s)	20.0%	45.7%	45.7%	34.3%	45.7%	34.3%	34.3%	4.0
All-Red Time (s)	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0
Lead/Lag	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Lead-Lag Optimizer?	None	None	None	Max	None	Min	Min	Min
v/c Ratio	0.16	0.89	0.46	0.05	0.20	0.54	0.53	0.41
Control Delay	22.8	36.0	4.3	19.1	19.3	1.8	25.5	21.2
Queue Delay	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Delay	22.8	36.0	4.3	19.1	19.3	1.8	25.5	21.2
Queue Length 50th (ft)	12	255	7	5	41	0	83	90
Queue Length 95th (ft)	39	#457	57	19	81	21	154	155
Internal Link Dist (ft)	273		685		1215		572	
Turn Bay Length (ft)								
Base Capacity (vph)	274	779	918	296	626	1461	424	624
Starvation Cap Reducin	0	0	0	0	0	0	0	0
Spillback Cap Reducin	0	0	0	0	0	0	0	0
Storage Cap Reducin	0	0	0	0	0	0	0	0
Reduced v/c Ratio	0.16	0.83	0.44	0.05	0.20	0.54	0.53	0.41
<b>Intersection Summary</b>								
Cycle Length: 70								
Actuated Cycle Length: 61.5								
Natural Cycle: 70								
Control Type: Actuated-Uncoordinated								
# 95th Percentile Volume Exceeds Capacity: Queue may be longer.								
Queue shown is maximum after two cycles.								



106: Reverse Ave & Bend Pkwy SB Ramp

2007 PM Peak Hour

Baseline


Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations	4	1	1	1	1	1	1	1	1	1	1	1
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Total Lost time (s)	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0
Lane Util. Factor	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Fit	0.97	1.00	0.86	1.00	0.85	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Fit Protected	0.98	0.95	1.00	0.95	1.00	0.95	1.00	0.95	1.00	0.95	1.00	1.00
Satd. Flow (prot)	1766	1770	1602	1770	1602	1770	1863	1583	1770	1857	1770	1857
Fit Permitted	0.98	1.00	0.95	1.00	0.51	1.00	1.00	0.68	1.00	0.68	1.00	1.00
Satd. Flow (perm)	1766	1770	1602	1770	1602	1770	1863	1583	1770	1857	1770	1857
Volume (vph)	15	15	10	595	25	350	15	115	730	205	230	230
Peak-hour factor, PHF	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Adj. Flow (vph)	16	16	11	647	27	380	16	125	793	223	250	250
RTOR Reduction (vph)	0	10	0	0	228	0	0	0	217	0	1	0
Lane Group Flow (vph)	0	33	0	647	179	0	16	125	576	223	254	0
Turn Type	Split	Split	Split	Perm	pm+ov	Perm	Perm	pm+ov	Perm	Perm	Perm	2
Protected Phases	7	7	3	3	6	6	3	6	6	2	2	2
Actuated Green, G (s)	5.3	25.2	25.2	20.7	20.7	45.9	20.7	20.7	20.7	20.7	20.7	20.7
Effective Green, g (s)	5.3	25.2	25.2	20.7	20.7	45.9	20.7	20.7	20.7	20.7	20.7	20.7
Actuated g/c Ratio	0.08	0.40	0.40	0.33	0.33	0.73	0.33	0.33	0.33	0.33	0.33	0.33
Clearance Time (s)	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0
Vehicle Extension (s)	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5
Lane Grp Cap (vph)	148	706	639	313	610	1250	413	608	608	608	608	608
v/s Ratio Prot	0.002	0.37	0.11	0.02	0.18	0.18	0.07	0.18	0.18	0.18	0.18	0.18
v/s Ratio Perm	0.22	0.92	0.28	0.05	0.20	0.46	0.54	0.42	0.42	0.42	0.42	0.42
Uniform Delay, d1	27.0	18.0	12.9	14.5	15.3	3.6	17.4	16.6	16.6	16.6	16.6	16.6
Progression Factor	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Incremental Delay, d2	0.6	16.6	0.2	0.3	0.8	0.2	2.0	0.7	0.7	0.7	0.7	0.7
Delay (s)	27.6	34.6	13.0	14.8	16.1	3.8	19.3	17.3	17.3	17.3	17.3	17.3
Level of Service	C	C	B	B	B	A	B	B	B	B	B	B
Approach Delay (s)	27.6			26.3			5.6		18.2			
Approach LOS	C			C			A		B			
<b>Intersection Summary</b>												
HCM Average Control Delay	17.1		HCM Level of Service		B							
HCM Volume to Capacity ratio	0.69		Sum of lost time (s)		12.0							
Actuated Cycle Length (s)	63.2		ICU Level of Service		D							
Intersection Capacity Utilization	74.9%		Analysis Period (min)		15							
Analysis Period (min)	15		Critical Lane Group		c							

107: Reverse Ave & Bend Pkwy NB Ramp 2007 PM Peak Hour

Lane Group	EBL	EBT	EBR	WBL	WBT	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations	4	4	4	4	4	4	4	4	4	4	4
Volume (vph)	160	365	440	50	510	120	285	585	140	5	315
Lane Group Flow (vph)	0	571	478	0	744	0	440	636	152	5	342
Turn Type	Perm	Perm	Perm	Perm	Perm	Perm	Perm	Prot	Perm	Perm	Perm
Protected Phases	2	2	2	6	6	8	8	8	7	4	4
Detector Phases	2	2	2	6	6	8	8	8	7	4	4
Minimum Initial (s)	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
Minimum Split (s)	32.0	32.0	32.0	26.0	26.0	28.0	28.0	28.0	8.0	28.0	28.0
Total Split (s)	33.0	33.0	33.0	33.0	33.0	30.0	30.0	30.0	12.0	42.0	42.0
Total Split (%)	44.0%	44.0%	44.0%	44.0%	44.0%	40.0%	40.0%	40.0%	16.0%	56.0%	56.0%
Yellow Time (s)	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0
All-Red Time (s)	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Lead/Lag	Lag	Lag	Lag	Lag	Lag	Lag	Lag	Lag	Lead	Lead	Lead
Lead/Lag Optimizer?	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Recall Mode	1,02dI	0.55	0.55	0.68	0.68	0.75	0.88	0.68	0.01	0.40	0.40
Control Delay	29.2	4.4	4.4	20.2	20.2	29.5	28.9	50.3	9.0	6.9	6.9
Queue Delay	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Delay	29.2	4.4	4.4	20.2	20.2	29.5	28.9	50.3	9.0	6.9	6.9
Queue Length 50th (ft)	117	0	0	135	135	164	155	67	1	38	38
Queue Length 95th (ft)	179	55	55	192	192	#315	#379	#167	6	95	95
Internal Link Dist (ft)	685			811	202			274			
Turn Bay Length (ft)											
Base Capacity (vph)	883	968	968	1360	1360	698	810	241	1056	969	969
Starvation Cap Reducin	0	0	0	0	0	0	0	0	0	0	0
Spillback Cap Reducin	0	0	0	0	0	0	0	0	0	0	0
Storage Cap Reducin	0	0	0	0	0	0	0	0	0	0	0
Reduced v/c Ratio	0.65	0.49	0.49	0.55	0.55	0.63	0.79	0.63	0.00	0.35	0.35

**Intersection Summary**

Cycle Length: 75  
 Actuated Cycle Length: 60.9  
 Natural Cycle: 75  
 Control Type: Actuated-Uncoordinated  
 # 95th Percentile volume exceeds capacity, queue may be longer.  
 Queue shown is maximum after two cycles.  
 dI Detracto Left Lane. Recode with 1 through lane as a left lane.



107: Reverse Ave & Bend Pkwy NB Ramp 2007 PM Peak Hour

Movement	EBL	EBT	EBR	WBL	WBT	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations	4	4	4	4	4	4	4	4	4	4	4
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Total Lost time (s)	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0
Lane Util. Factor	0.95	1.00	1.00	0.95	0.97	1.00	1.00	1.00	1.00	1.00	1.00
Fit	1.00	0.85	0.85	0.97	0.97	1.00	1.00	1.00	1.00	0.85	0.85
Fit Protected	0.98	1.00	1.00	1.00	1.00	0.99	1.00	0.95	1.00	1.00	1.00
Stand. Flow (prot)	3485	1583	1583	3430	3430	1836	1583	1770	1863	1583	1583
Fit Permitted	0.57	1.00	1.00	0.88	0.88	0.90	1.00	0.95	1.00	1.00	1.00
Stand. Flow (perm)	2004	1583	1583	3021	1684	1583	1770	1863	1583	1583	1583
Volume (vph)	160	365	440	50	510	120	285	585	140	5	315
Peak-hour factor, PHF	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Adtl. Flow (vph)	174	397	478	54	554	136	130	636	152	5	342
RTOR Reduction (vph)	0	0	307	0	27	0	0	170	0	0	81
Lane Group Flow (vph)	0	571	478	0	717	0	440	466	152	5	261
Turn Type	Perm	Perm	Perm	Perm	Perm	Perm	Perm	Prot	Perm	Perm	Perm
Protected Phases	2	2	2	6	6	8	8	8	7	4	4
Actuated Green, G (s)	21.7	21.7	21.7	21.7	21.7	21.2	21.2	5.6	30.8	30.8	30.8
Effective Green, g (s)	21.7	21.7	21.7	21.7	21.7	21.2	21.2	5.6	30.8	30.8	30.8
Actuated g/C Ratio	0.36	0.36	0.36	0.36	0.36	0.35	0.35	0.09	0.51	0.51	0.51
Clearance Time (s)	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0
Vehicle Extension (s)	2.5	2.5	2.5	2.5	2.5	2.0	2.0	2.0	2.0	2.0	2.0
Lane Grp Cap (vph)	719	568	568	1084	1084	590	555	164	948	806	806
v/s Ratio Prot											
v/s Ratio Perm	0.28	0.11	0.11	0.24	0.24	0.26	0.29	0.09	0.00	0.16	0.16
v/c Ratio	1.02dI	0.30	0.30	0.66	0.66	0.75	0.84	0.93	0.01	0.32	0.32
Uniform Delay, d1	17.4	14.0	14.0	16.3	16.3	17.3	18.1	27.2	7.3	8.7	8.7
Progression Factor	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Incremental Delay, d2	5.9	0.2	0.2	1.4	1.4	4.5	10.6	48.3	0.0	0.1	0.1
Delay (s)	23.2	14.2	14.2	17.7	17.7	21.8	28.7	75.5	7.3	8.8	8.8
Level of Service	C	B	B	B	B	C	C	E	A	A	A
Approach Delay (s)	19.1			17.7	17.7	25.9		29.1			
Approach LOS	B			B	B	C		C			

**Intersection Summary**

HCM Average Control Delay: 22.4 HCM Level of Service: C  
 HCM Volume to Capacity ratio: 0.83 Sum of lost time (s): 12.0  
 Actuated Cycle Length (s): 60.5 ICU Level of Service: D  
 Intersection Capacity Utilization: 77.0% Analysis Period (min): 15  
 dI Detracto Left Lane. Recode with 1 through lane as a left lane.  
 c Critical Lane Group

Lane Group	EBL	EBT	WBL	WBT	NBL	NBT	SBL	SBT
Lane Configurations	270	565	240	395	135	1365	80	815
Volume (vph)	270	565	240	395	135	1365	80	815
Lane Group Flow (vph)	293	886	246	515	147	1598	87	962
Turn Type	Split	Split	Split	Prot	Prot	Prot	Prot	Prot
Protected Phases	4	4	8	8	5	2	1	6
Permitted Phases	4	4	8	8	5	2	1	6
Detector Phases	4	4	8	8	5	2	1	6
Minimum Initial (s)	10.0	10.0	6.0	6.0	6.0	10.0	6.0	10.0
Minimum (s)	27.0	27.0	27.0	10.0	24.0	10.0	24.0	24.0
Total Split (s)	37.0	37.0	27.0	27.0	19.0	60.0	16.0	57.0
Yellow Time (s)	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0
All-Red Time (s)	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Lead/Lag Optimizer?	None	None	None	None	None	C-Max	None	C-Max
Recall Mode	0.70	1.06	0.94	0.94	0.82	1.10	0.66	0.71
v/c Ratio	0.70	1.06	0.94	0.94	0.82	1.10	0.66	0.71
Control Delay	59.3	97.7	99.8	83.2	94.6	95.5	85.6	39.8
Queue Delay	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Delay	59.3	97.7	99.8	83.2	94.6	95.5	85.6	39.8
Queue Length 50th (ft)	246	~450	246	252	133	~887	78	390
Queue Length 95th (ft)	353	#586	#429	#368	#242	#1033	138	471
Internal Link Dist (ft)	811		432		924		603	
Turn Bay Length (ft)	417	832	265	553	190	1450	152	1357
Base Capacity (vph)	0	0	0	0	0	0	0	0
Starvation Cap Reducin	0	0	0	0	0	0	0	0
Spillback Cap Reducin	0	0	0	0	0	0	0	0
Storage Cap Reducin	0	0	0	0	0	0	0	0
Reduced v/c Ratio	0.70	1.06	0.93	0.93	0.77	1.10	0.57	0.71
<b>Intersection Summary</b>								
Cycle Length: 140								
Activated Cycle Length: 140								
Offset: 0.00%, Referenced to phase 2:NBT and 6:SBT, Start of Green								
Control Cycle: 140								
Control Type: Actuated-Coordinated								
~ Volume exceeds capacity, queue is theoretically infinite.								
~ Queue shown is maximum after two cycles.								
# 95th percentile volume exceeds capacity, queue may be longer.								
Queue shown is maximum after two cycles.								



HCM Signalized Intersection Capacity Analysis  
 108: Revere Ave & 3rd St  
 2007 PM Peak Hour  
 Baseline

Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Total Lost time (s)	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0
Lane Util. Factor	1.00	0.95	1.00	0.91	0.91	1.00	0.95	1.00	0.95	1.00	0.95	1.00
Fit Protected	1.00	0.95	1.00	0.98	0.98	1.00	0.99	1.00	0.99	1.00	0.99	1.00
Fit Permitted	0.95	1.00	0.95	1.00	0.95	1.00	0.95	1.00	0.95	1.00	0.95	1.00
Satd. Flow (prot)	1770	3376	1610	3315	1770	3501	1770	3497	1770	3497	1770	3497
Fit Permitted	0.95	1.00	0.95	1.00	0.95	1.00	0.95	1.00	0.95	1.00	0.95	1.00
Satd. Flow (perm)	1770	3376	1610	3315	1770	3501	1770	3497	1770	3497	1770	3497
Volume (vph)	270	565	250	240	395	65	135	1365	105	80	815	70
Peak-hour factor, PHF	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Adj. Flow (vph)	293	614	272	261	429	71	147	1484	114	87	886	76
RTOR Reduction (vph)	0	36	0	0	8	0	0	4	0	0	4	0
Lane Group Flow (vph)	293	850	0	246	507	0	147	1594	0	87	958	0
Turn Type	Split	Split	Split	Prot								
Protected Phases	4	4	8	8	5	2						
Permitted Phases	4	4	8	8	5	2						
Activated Green, G (s)	33.0	33.0	22.7	22.7	14.1	57.8						
Effective Green, g (s)	33.0	33.0	22.7	22.7	14.1	57.8						
Effective Green, g (s)	33.0	33.0	22.7	22.7	14.1	57.8						
Actuated g/c Ratio	0.24	0.24	0.16	0.16	0.10	0.41						
Clearance Time (s)	4.0	4.0	4.0	4.0	4.0	4.0						
Vehicle Extension (s)	2.5	2.5	2.5	2.5	2.5	4.3						
Lane Grp Cap (vph)	417	796	261	538	178	1445						
v/s Ratio Prot	0.17	0.025	0.15	0.15	0.08	0.46						
v/s Ratio Perm	0.70	1.07	0.94	0.94	0.83	1.10						
v/c Ratio	0.70	1.07	0.94	0.94	0.83	1.10						
Uniform Delay, d1	49.0	53.5	58.0	58.0	61.7	41.1						
Progression Factor	1.00	1.00	1.00	1.00	1.00	1.00						
Incremental Delay, d2	4.9	51.6	40.1	25.0	25.2	57.2						
Delay (s)	53.9	105.1	98.1	83.0	87.0	98.3						
Level of Service	D	F	F	F	F	F						
Approach Delay (s)	92.4		87.9		97.3							
Approach LOS	F		F		F							
<b>Intersection Summary</b>												
HCM Average Control Delay	82.3		HCM Level of Service		F							
HCM Volume to Capacity ratio	1.05		Sum of lost time (s)		16.0							
Actuated Cycle Length (s)	140.0		ICU Level of Service		F							
Intersection Capacity Utilization	96.3%		Analysis Period (min)		15							
c Critical Lane Group												

HCM Unsignalized Intersection Capacity Analysis  
 109: Revere Ave & 4th St


2007 PM Peak Hour  
 Baseline

Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations	Stop	Stop	Stop	Stop	Stop	Stop	Stop	Stop	Stop	Stop	Stop	Stop
Volume (vph)	275	350	140	25	345	120	80	245	45	170	185	280
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Hourly Flow rate (vph)	299	380	152	27	375	130	87	266	49	185	201	304
Direction, Lane #	EB 1	EB 2	WB 1	WB 2	NB 1	NB 2	SB 1	SB 2				
Volume Total (vph)	299	533	27	505	402	386	304					
Volume Left (vph)	299	0	27	0	87	185	0					
Volume Right (vph)	0	152	0	130	49	0	304					
Had'l (s)	0.53	-0.17	0.53	-0.15	0.00	0.27	-0.67					
Departure Headway (s)	10.1	9.4	10.3	9.6	9.9	9.8	8.9					
Degree Utilization, x	0.84	1.39	0.08	1.35	1.11	1.06	0.75					
Capacity (veh/h)	353	392	345	383	373	371	397					
Control Delay (s)	47.2	216.4	12.9	199.0	111.0	93.5	33.4					
Approach Delay (s)	155.6		189.5		111.0	67.0						
Approach LOS	F		F		F	F						
<b>Intersection Summary</b>												
Delay	130.7											
HCM Level of Service	F											
Intersection Capacity Utilization	93.2%											
ICU Level of Service	F											
Analysis Period (min)	15											

Timings  
 110: Portland Ave & Hill St

2007 PM Peak Hour  
 Baseline

Lane Group	EBL	EBT	WBL	WBT	WBR	NBL	NBT	SBL	SBT	SBR
Lane Configurations	Prot	Prot	Prot	Perm pm+pt	Perm pm+pt	pm+pt	pm+pt	Perm		
Volume (vph)	320	220	80	300	105	160	520	40	350	405
Lane Group Flow (vph)	348	364	87	326	114	174	685	43	380	440
Turn Type	Prot	Prot	Prot	Perm pm+pt	Perm pm+pt	pm+pt	pm+pt	Perm		
Protected Phases	7	4	3	8	8	5	2	1	6	
Permitted Phases										
Detector Phases	7	4	3	8	8	5	2	1	6	
Minimum Initial (s)	5.0	6.0	5.0	10.0	10.0	4.0	10.0	6.0	8.0	8.0
Minimum Split (s)	9.2	23.0	9.2	24.0	24.0	8.0	21.0	10.0	23.0	23.0
Total Split (s)	24.0	36.4	11.6	24.0	24.0	14.0	42.0	10.0	38.0	38.0
Total Split (%)	24.0%	36.4%	11.6%	24.0%	24.0%	14.0%	42.0%	10.0%	38.0%	38.0%
Yellow Time (s)	4.0	4.0	4.0	4.0	4.0	3.5	4.0	4.0	4.0	4.0
All-Red Time (s)	0.2	0.0	0.2	0.0	0.0	0.5	0.0	0.0	0.0	0.0
Lead/Lag	Lead	Lag	Lead	Lag	Lag	Lead	Lag	Lead	Lag	Lag
Lead-Lag Optimize?	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Recall Mode	None	None	None	None	None	Min	None	Min	Min	Min
v/c Ratio	0.92	0.56	0.65	0.88	0.28	0.47	0.94	0.24	0.65	0.55
Control Delay	68.2	28.2	67.2	63.7	8.7	19.8	50.5	18.4	33.5	5.3
Queue Delay	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Delay	68.2	28.2	67.2	63.7	8.7	19.8	50.5	18.4	33.5	5.3
Queue Length 50th (ft)	223	180	55	203	0	62	420	14	199	0
Queue Length 95th (ft)	#403	278	#125	#357	45	104	#667	33	297	65
Internal Link Dist (ft)			940				946		1215	
Turn Bay Length (ft)										
Base Capacity (vph)	380	656	141	393	424	375	740	176	647	837
Starvation Cap Reductn	0	0	0	0	0	0	0	0	0	0
Spillback Cap Reductn	0	0	0	0	0	0	0	0	0	0
Storage Cap Reductn	0	0	0	0	0	0	0	0	0	0
Reduced v/c Ratio	0.92	0.55	0.62	0.83	0.27	0.46	0.93	0.24	0.59	0.53
<b>Intersection Summary</b>										
Cycle Length: 100										
Actuated Cycle Length: 93.8										
Natural Cycle: 100										
Control Type: Actuated-Uncoordinated										
# 95th percentile volume exceeds capacity, queue may be longer.										
Queue shown is maximum after two cycles.										



HCM Signalized Intersection Capacity Analysis  
1101: Portland Ave & Hill St  
2007 PM Peak Hour  
Baseline

Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Total Lost time (s)	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0
Lane Util. Factor	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Fit	1.00	0.95	1.00	1.00	0.85	1.00	0.97	1.00	1.00	0.85	1.00	0.85
Fit Protected	0.95	1.00	0.95	1.00	1.00	0.95	1.00	1.00	0.95	1.00	1.00	1.00
Satd. Flow (prot)	1770	1767	1770	1863	1583	1770	1814	1770	1863	1583	1770	1863
Fit Permitted	0.95	1.00	0.95	1.00	1.00	0.27	1.00	0.13	1.00	1.00	1.00	1.00
Satd. Flow (perm)	1770	1767	1770	1863	1583	509	1814	237	1863	1583	1770	1863
Volume (vph)	320	220	115	80	300	105	160	520	110	40	350	405
Peak-hour factor, PHF	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Adj. Flow (vph)	348	239	125	87	326	114	174	565	120	43	380	440
RTOR Reduction (vph)	0	18	0	0	0	91	0	7	0	0	0	296
Lane Group Flow (vph)	348	346	0	87	326	23	174	678	0	43	380	144
Turn Type	Prot	Prot	Prot	Perm	pm+pt	pm+pt	pm+pt	Perm	pm+pt	Perm	Perm	Perm
Protected Phases	7	4	3	8	8	2	5	2	6	6	6	6
Actuated Green, G (s)	20.0	33.8	5.7	19.5	19.5	44.8	37.4	34.9	31.5	31.5	31.5	31.5
Effective Green, g (s)	20.2	33.8	5.9	19.5	19.5	44.8	37.4	34.9	31.5	31.5	31.5	31.5
Actuated g/C Ratio	0.21	0.35	0.06	0.20	0.20	0.46	0.39	0.36	0.33	0.33	0.33	0.33
Clearance Time (s)	4.2	4.0	4.2	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0
Vehicle Extension (s)	2.5	2.5	2.5	2.5	2.5	3.0	4.2	2.5	4.2	4.2	4.2	4.2
Lane Grp Cap (vph)	371	619	108	376	320	358	703	140	608	517	608	517
v/s Ratio Prot	0.20	0.20	0.05	0.18	0.01	0.18	0.01	0.18	0.01	0.20	0.09	0.09
v/s Ratio Perm	0.94	0.56	0.81	0.87	0.07	0.49	0.96	0.31	0.62	0.28	0.28	0.28
v/c Ratio	37.5	25.3	44.7	37.2	31.2	17.3	28.9	23.9	27.5	24.1	24.1	24.1
Uniform Delay, d1	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Progression Factor	30.9	0.9	33.1	18.3	0.1	1.0	25.3	0.9	2.4	0.4	0.4	0.4
Incremental Delay, d2	68.5	26.2	77.8	55.6	31.2	18.3	54.2	24.8	29.9	24.5	24.5	24.5
Delay (s)	E	C	E	E	C	B	D	C	C	C	C	C
Level of Service	E	C	E	E	C	B	D	C	C	C	C	C
Approach Delay (s)	46.9	46.9	54.0	54.0	46.9	46.9	46.9	26.9	26.9	26.9	26.9	
Approach LOS	D	D	D	D	D	D	D	C	C	C	C	
<b>Intersection Summary</b>												
HCM Average Control Delay	42.3			HCM Level of Service			D					
HCM Volume to Capacity ratio	0.92			Sum of lost time (s)			16.0					
Actuated Cycle Length (s)	85.9%			ICU Level of Service			E					
Intersection Capacity Utilization	15											
Analysis Period (min)	15											
c Critical Lane Group												

Timings  
111: Olney Ave & 3rd St  
2007 PM Peak Hour  
Baseline

Lane Group	EBL	EBT	WBL	WBT	NBL	NBT	SBL	SBT
Lane Configurations	130	280	130	315	95	1460	140	1105
Volume (vph)	141	396	141	456	103	1712	152	1228
Lane Group Flow (vph)	Prot	Prot	Prot	Prot	Prot	Prot	Prot	Prot
Turn Type	Prot	Prot	Prot	Prot	Prot	Prot	Prot	Prot
Protected Phases	7	4	3	8	5	2	1	6
Permitted Phases	7	4	3	8	5	2	1	6
Detector Phases	4	4	3	8	5	2	1	6
Minimum Initial (s)	8.0	24.0	8.0	24.0	8.0	25.0	8.0	25.0
Minimum Split (s)	12.0	27.0	13.0	28.0	13.0	53.0	13.0	53.0
Total Split (s)	11.3%	25.5%	12.3%	26.4%	12.3%	50.0%	12.3%	50.0%
Total Split (%)	3.5	4.0	3.5	4.0	3.5	4.0	3.5	4.0
All-Red Time (s)	0.0	0.0	0.0	0.0	0.0	1.0	0.0	1.0
Lead/Lag	Lag	Lag	Lead	Lead	Lag	Lag	Lag	Lag
Lead/Lag Optimizer?	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Lead-Mode	None	None	None	None	C-Min	None	C-Min	None
v/c Ratio	1.05	0.99	0.94	1.09	0.73	1.05	1.01	0.74
Control Delay	140.8	83.8	108.8	110.1	76.2	67.1	126.5	26.6
Queue Delay	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Delay	140.8	83.8	108.8	110.1	76.2	67.1	126.5	26.6
Queue Length 50th (ft)	~105	262	97	~343	69	~671	~106	350
Queue Length 95th (ft)	#231	#461	#220	#544	#149	#812	#238	435
Internal Link Dist (ft)	300	422	1798	924				
Turn Bay Length (ft)	134	400	150	417	150	1623	150	1650
Base Capacity (vph)	0	0	0	0	0	0	0	0
Starvation Cap Reductn	0	0	0	0	0	0	0	0
Storage Cap Reductn	0	0	0	0	0	0	0	0
Reduced v/c Ratio	1.05	0.99	0.94	1.09	0.69	1.05	1.01	0.74
<b>Intersection Summary</b>								
Cycle Length: 106								
Actuated Cycle Length: 106								
Offset: 0.00%	Referenced to phase 2:NBT and 6:SBT, Start of Green							
Natural Cycle: 120								
Control Type: Actuated-Coordinated								
~ Volume exceeds capacity, queue is theoretically infinite.								
Queue shown is maximum after two cycles.								
# 95th percentile volume exceeds capacity, queue may be longer.								
Queue shown is maximum after two cycles.								
Splits and Phases: 111: Olney Ave & 3rd St								

HCM Signalized Intersection Capacity Analysis  
 111: Olney Ave & 3rd St  
 2007 PM Peak Hour  
 Baseline

Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Total Lost time (s)	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0
Lane Util. Factor	1.00	1.00	1.00	1.00	1.00	1.00	0.95	1.00	0.95	1.00	0.95	1.00
Frt.	1.00	0.97	1.00	1.00	0.96	1.00	0.99	1.00	0.99	1.00	1.00	1.00
Fit Protected	0.95	1.00	0.95	1.00	0.95	1.00	0.95	1.00	0.95	1.00	0.95	1.00
Satd. Flow (prot)	1770	1798	1770	1793	1770	3500	1770	3528	1770	3528	1770	3528
Fit Permitted	0.95	1.00	0.95	1.00	0.95	1.00	0.95	1.00	0.95	1.00	0.95	1.00
Satd. Flow (perm)	1770	1798	1770	1793	1770	3500	1770	3500	1770	3528	1770	3528
Volume (vph)	130	280	85	130	315	105	95	1460	115	140	1105	25
Peak-hour factor, PHF	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Adj. Flow (vph)	141	304	92	141	342	114	103	1587	125	152	1201	27
RTOR Reduction (vph)	0	10	0	0	12	0	0	5	0	0	2	0
Lane Group Flow (vph)	141	386	0	141	444	0	103	1707	0	152	1226	0
Turn Type	Prot	Prot	Prot	Prot	Prot	Prot	Prot	Prot	Prot	Prot	Prot	Prot
Protected Phases	7	4	3	8	5	2	1	6				
Permitted Phases												
Actuated Green, G (s)	8.5	23.0	9.5	24.0	9.0	48.0	9.5	48.5				
Effective Green, g (s)	8.0	23.0	9.0	24.0	8.5	49.0	9.0	49.5				
Actuated g/C Ratio	0.08	0.22	0.08	0.23	0.08	0.46	0.08	0.47				
Clearance Time (s)	3.5	4.0	3.5	4.0	3.5	5.0	3.5	5.0				
Vehicle Extension (s)	2.5	2.5	2.5	2.5	2.5	4.8	2.5	4.8				
Lane Grp Cap (vph)	134	390	150	406	142	1618	150	1648				
v/s Ratio Prot	0.08	c0.21	0.08	c0.25	0.06	c0.49	0.06	c0.09	0.35			
v/s Ratio Perm	1.05	0.99	0.94	1.09	0.73	1.05	1.01	0.74				
Uniform Delay, d1	49.0	41.4	48.2	41.0	47.6	28.5	48.5	23.1				
Progression Factor	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00				
Incremental Delay, d2	92.4	42.3	55.6	72.6	15.8	38.4	77.0	3.1				
Delay (s)	141.4	83.6	103.8	113.6	63.4	66.9	125.5	26.2				
Level of Service	F	F	F	F	E	E	F	C				
Approach Delay (s)	98.8		111.3		66.7		37.1					
Approach LOS	F		F		E		D					
<b>Intersection Summary</b>												
HCM Average Control Delay	67.4	HCM Level of Service					E					
HCM Volume to Capacity ratio	1.04						12.0					
Actuated Cycle Length (s)	106.0	Sum of lost time (s)					12.0					
Intersection Capacity Utilization	95.3%	ICU Level of Service					F					
Analysis Period (min)	15											
c Critical Lane Group												

HCM Unsignalized Intersection Capacity Analysis  
 112: Olney Ave & 4th St  
 2007 PM Peak Hour  
 Baseline

Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations	105	Stop	40	50	385	45	45	235	75	140	140	100
Volume (vph)	105	385	40	50	385	45	45	235	75	140	140	100
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Hourly flow rate (vph)	114	418	43	54	418	49	49	255	82	152	152	109
Direction, Lane #	EB 1	EB 2	WB 1	WB 2	NB 1	SB 1						
Volume Total (vph)	114	462	54	467	386	413						
Volume Left (vph)	114	0	54	0	49	152						
Volume Right (vph)	0	43	0	49	82	109						
Hadl (s)	0.53	-0.03	0.53	-0.04	-0.07	-0.05						
Departure Headway (s)	10.2	9.6	10.2	9.6	9.4	9.4						
Degree Utilization, x	0.32	1.23	0.15	1.24	1.01	1.08						
Capacity (veh/h)	351	381	350	381	386	390						
Control Delay (s)	16.7	153.1	13.8	158.2	79.1	100.2						
Approach Delay (s)	126.1		143.2		79.1	100.2						
Approach LOS	F		F		F	F						
<b>Intersection Summary</b>												
Delay	115.6											
HCM Level of Service	F											
Intersection Capacity Utilization	82.8%	ICU Level of Service										
Analysis Period (min)	15	E										

HCM Unsignalized Intersection Capacity Analysis  
113: Lafayette Ave & Bend Pkwy SB Ramp

Baseline  
2007 PM Peak Hour

Movement	EBL	EBR	NBL	NBT	SBT	SBR
Lane Configurations	EBL	EBR	NBL	NBT	SBT	SBR
Sign Control	Stop	Free	Free	Free	Free	Free
Grade	0%	0%	0%	0%	0%	0%
Volume (veh/h)	0	125	0	2610	2725	75
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92
Hourly flow rate (vph)	0	136	0	2837	2962	82
Pedestrians						
Lane Width (ft)						
Walking Speed (ft/s)						
Percent Blockage						
Right turn flare (veh)						
Median type	None					
Median storage (veh)				740		
Upstream signal (ft)						
PX, platoon unblocked						
VC1, conflicting volume	4380	1481	3043			
VC1, stage 1 conf vol						
VC2, stage 2 conf vol						
VCU, unblocked vol	4380	1481	3043			
TC, single (s)	6.8	6.9	4.1			
TC, 2 stage (s)						
IF (s)	3.5	3.3	2.2			
p0 queue free %	100	0	100			
cm capacity (veh/h)	1	114	109			
Direction, Lane #	EB 1	NB 1	NB 2	SB 1	SB 2	SB 3
Volume Total	136	1418	1418	1481	1481	82
Volume Left	0	0	0	0	0	0
Volume Right	136	0	0	0	0	82
CSH	114	1700	1700	1700	1700	1700
Volume to Capacity	1.19	0.83	0.83	0.87	0.87	0.05
Queue Length 95th (ft)	215	0	0	0	0	0
Control Delay (s)	214.9	0.0	0.0	0.0	0.0	0.0
Lane LOS	F					
Approach Delay (s)	214.9	0.0		0.0		
Approach LOS	F			C		
<b>Intersection Summary</b>						
Average Delay	4.9					
Intersection Capacity Utilization	89.7%					
ICU Level of Service	E					
Analysis Period (min)	15					

HCM Unsignalized Intersection Capacity Analysis  
114: Wall St. & Bond St

Baseline  
2007 PM Peak Hour

Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Sign Control	Free	Free	Free	Free	Free	Free	Stop	Stop	Stop	Stop	Stop	Stop
Grade	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%
Volume (veh/h)	10	190	0	0	605	10	65	10	435	20	0	45
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Hourly flow rate (vph)	11	207	0	0	658	11	71	11	473	22	0	49
Pedestrians												
Lane Width (ft)												
Walking Speed (ft/s)												
Percent Blockage												
Right turn flare (veh)												
Median type							None		None			None
Median storage (veh)												
Upstream signal (ft)							155					
PX, platoon unblocked												
VC1, conflicting volume				668	207		940	897	207	1370	891	663
VC1, stage 1 conf vol												
VC2, stage 2 conf vol												
VCU, unblocked vol				668	207		940	897	207	1370	891	663
TC, single (s)				4.1	4.1		7.1	6.5	6.2	7.1	6.5	6.2
TC, 2 stage (s)												
IF (s)				2.2	2.2		3.5	4.0	3.3	3.5	4.0	3.3
p0 queue free %				99	100		67	96	43	58	100	89
cm capacity (veh/h)				921	1365		216	276	834	51	278	461
Direction, Lane #	EB 1	WB 1	NB 1	NB 2	SB 1							
Volume Total	217	668	82	473	71							
Volume Left	11	0	71	0	22							
Volume Right	0	11	0	473	49							
CSH	921	1700	222	834	134							
Volume to Capacity	0.01	0.39	0.37	0.57	0.53							
Queue Length 95th (ft)	1	0	40	91	64							
Control Delay (s)	0.6	0.0	30.3	14.8	58.7							
Lane LOS	A		D	B	F							
Approach Delay (s)	0.6	0.0	17.1		58.7							
Approach LOS	C		C		F							
<b>Intersection Summary</b>												
Average Delay	9.1											
Intersection Capacity Utilization	51.4%											
ICU Level of Service	A											
Analysis Period (min)	15											

Lane Group	EBL	EBT	WBL	WBT	SBT	SBR
Lane Configurations	150	410	325	565	455	170
Volume (vph)	163	620	353	657	620	185
Lane Group Flow (vph)	Prot	Prot	Prot	Perm	Perm	Perm
Turn Type	5	2	1	6	4	4
Protected Phases	5	2	1	6	4	4
Permitted Phases	5	2	1	6	4	4
Detector Phases	6.0	6.0	6.0	6.0	6.0	6.0
Minimum Initial (s)	10.0	20.0	10.0	24.0	29.0	29.0
Minimum (s)	20.0	28.0	23.0	31.0	29.0	29.0
Total Split (s)	25.0%	35.0%	28.8%	38.8%	36.3%	36.3%
Yellow Time (s)	4.0	4.0	4.0	4.0	4.0	4.0
All-Red Time (s)	0.0	0.0	0.0	0.0	0.0	0.0
Lead/Lag Optimizer?	Yes	Yes	Yes	Yes	Yes	Yes
Lead-Lag Mode	Max	Max	Max	Max	Max	Max
v/c Ratio	0.46	0.58	0.84	1.05	0.57	0.30
Control Delay	33.1	23.3	49.2	77.4	25.4	4.8
Queue Delay	0.0	0.0	0.0	43.6	0.6	0.0
Total Delay	33.1	23.3	49.2	121.0	26.0	4.8
Queue Length 50th (ft)	72	120	180	~369	134	0
Queue Length 95th (ft)	131	179	#316	#576	187	43
Internal Link Dist (ft)	429	314	483			
Turn Bay Length (ft)						
Base Capacity (vph)	354	1069	420	626	1095	622
Starvation Cap Reductn	0	0	0	59	0	0
Spillback Cap Reductn	0	1	0	0	184	0
Storage Cap Reductn	0	0	0	0	0	0
Reduced v/c Ratio	0.46	0.58	0.84	1.16	0.68	0.30
<b>Intersection Summary</b>						
Cycle Length: 80						
Actuated Cycle Length: 80						
Offset: 0.00%, Referenced to phase 2:EBT and 6:WBT, Start of Green						
Natural Cycle: 75						
Control Type: Pretimed						
~ Volume exceeds capacity, queue is theoretically infinite.						
~ Queue shown is maximum after two cycles.						
# 95th percentile volume exceeds capacity, queue may be longer.						
m Volume for 95th percentile queue is metered by upstream signal.						




Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Ideal Flow (vphpl)	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0
Total Lost time (s)	1.00	0.95	1.00	1.00	1.00	1.00	1.00	0.99	1.00	0.95	1.00	1.00
Lane Util. Factor	1.00	0.96	1.00	0.99	1.00	0.99	1.00	0.85	1.00	0.99	1.00	0.85
Fit Protected	0.95	1.00	0.95	1.00	0.95	1.00	0.95	1.00	0.99	1.00	0.99	1.00
Std. Flow (prot)	1770	3390	1770	1844	1770	1844	1770	1844	3504	1583	3504	1583
Fit Permitted	0.95	1.00	0.95	1.00	0.95	1.00	0.99	1.00	0.99	1.00	0.99	1.00
Std. Flow (perm)	1770	3390	1770	1844	1770	1844	1770	1844	3504	1583	3504	1583
Volume (vph)	150	410	160	325	565	40	0	0	115	455	170	170
Peak-hour factor, PHF	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Adl. Flow (vph)	163	446	174	353	614	43	0	0	125	495	185	185
RTOR Reduction (vph)	0	52	0	0	3	0	0	0	0	0	0	127
Lane Group Flow (vph)	163	568	0	353	654	0	0	0	0	620	38	38
Turn Type	Prot	Prot	Prot	Prot	Perm	Perm	Perm	Perm	Perm	Perm	Perm	Perm
Protected Phases	5	2		1	6					4		4
Permitted Phases	5	2		1	6					4		4
Actuated Green, G (s)	16.0	24.0		19.0	27.0					25.0		25.0
Effective Green, g (s)	16.0	24.0		19.0	27.0					25.0		25.0
Actuated g/C Ratio	0.20	0.30		0.24	0.34					0.31		0.31
Clearance Time (s)	4.0	4.0		4.0	4.0					4.0		4.0
Lane Grp Cap (vph)	354	1017		420	622					1095		495
v/s Ratio Prot	0.09	c0.17		0.20	c0.35							
v/s Ratio Perm												
v/c Ratio	0.46	0.56		0.84	1.05					0.18		0.04
Uniform Delay, d1	28.2	23.5		29.1	26.5					0.57		0.12
Progression Factor	1.00	1.00		1.11	1.13					23.0		19.6
Incremental Delay, d2	4.3	2.2		15.3	46.9					1.00		1.00
Delay (s)	32.5	25.8		47.5	76.8					2.1		0.5
Level of Service	C	C		D	E					C		C
Approach Delay (s)				27.2						66.6		23.9
Approach LOS				C	E					A		C
<b>Intersection Summary</b>												
HCM Average Control Delay	41.5			HCM Level of Service			D					
HCM Volume to Capacity ratio	0.77											
Actuated Cycle Length (s)	80.0			Sum of lost time (s)			12.0					
Intersection Capacity Utilization	66.4%			ICU Level of Service			C					
Analysis Period (min)	15											
c Critical Lane Group												

Timings Baseline  
 116: Newport Ave & Bond St 2007 PM Peak Hour

Lane Group	EBL	EBT	WBT	NBT
Lane Configurations	15	510	690	450
Volume (vph)	0	570	815	1152
Lane Group Flow (vph)	Perm	2	6	8
Turn Type	2	2	6	8
Protected Phases	2	2	6	8
Detector Phases	6.0	6.0	6.0	4.0
Minimum Initial (s)	28.0	28.0	29.0	20.0
Minimum (s)	39.0	39.0	39.0	41.0
Total Split (%)	48.8%	48.8%	48.8%	51.3%
Yellow Time (s)	4.0	4.0	4.0	3.5
All-Red Time (s)	0.0	0.0	0.0	0.5

Lead-Lag Optimizer?  
 Recall Mode Max Max Max Max  
 v/c Ratio 0.40 0.53 0.71  
 Control Delay 22.9 17.7 20.9  
 Queue Delay 0.0 0.1 2.9  
 Total Delay 22.9 17.9 23.8  
 Queue Length 50th (ft) 88 148 193  
 Queue Length 95th (ft) 141 201 232  
 Internal Link Dist (ft) 314 1020 356  
 Turn Bay Length (ft) 1435 1538 1623  
 Starvation Cap Reducin 0 0 62  
 Spillback Cap Reducin 0 131 350  
 Storage Cap Reducin 0 0 0  
 Reduced v/c Ratio 0.40 0.58 0.90



HCM Signalized Intersection Capacity Analysis Baseline  
 116: Newport Ave & Bond St 2007 PM Peak Hour

Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Ideal Flow (vphpl)	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0
Total Lost time (s)	0.95	0.95	0.95	0.99	0.99	0.99	0.99	0.99	0.99	0.99	0.99	0.99
Lane Util. Factor	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Fit Protected	3534	3534	3497	3497	3497	3497	3497	3497	3497	3497	3497	3497
Satd. Flow (prot)	3279	3279	3279	3279	3279	3279	3279	3279	3279	3279	3279	3279
Satd. Flow (perm)	15	510	0	0	690	60	240	450	370	0	0	0
Volume (vph)	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Peak-hour factor, PHF	16	554	0	0	750	65	261	489	402	0	0	0
Adtl. Flow (vph)	0	0	0	0	0	0	0	0	0	0	0	0
RTOR Reduction (vph)	0	0	0	0	0	0	0	0	0	0	0	0
Lane Group Flow (vph)	Perm	2	Perm	6	Perm	8	Perm	8	Perm	8	Perm	8
Turn Type	2	2	2	2	2	2	2	2	2	2	2	2
Protected Phases	35.0	35.0	35.0	35.0	35.0	35.0	35.0	35.0	35.0	35.0	35.0	35.0
Actuated Green, G (s)	35.0	35.0	35.0	35.0	35.0	35.0	35.0	35.0	35.0	35.0	35.0	35.0
Effective Green, g (s)	0.44	0.44	0.44	0.44	0.44	0.44	0.44	0.44	0.44	0.44	0.44	0.44
Actuated g/C Ratio	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0
Clearance Time (s)	1435	1435	1435	1435	1435	1435	1435	1435	1435	1435	1435	1435
Lane Grp Cap (vph)	0.17	0.17	0.17	0.17	0.17	0.17	0.17	0.17	0.17	0.17	0.17	0.17
v/s Ratio Prot	0.40	0.40	0.40	0.40	0.40	0.40	0.40	0.40	0.40	0.40	0.40	0.40
v/s Ratio Perm	15.3	15.3	15.3	15.3	15.3	15.3	15.3	15.3	15.3	15.3	15.3	15.3
v/c Ratio	1.43	1.43	1.43	1.43	1.43	1.43	1.43	1.43	1.43	1.43	1.43	1.43
Uniform Delay, d1	0.7	0.7	0.7	0.7	0.7	0.7	0.7	0.7	0.7	0.7	0.7	0.7
Progression Factor	22.6	22.6	22.6	22.6	22.6	22.6	22.6	22.6	22.6	22.6	22.6	22.6
Incremental Delay, d2	17.8	17.8	17.8	17.8	17.8	17.8	17.8	17.8	17.8	17.8	17.8	17.8
Delay (s)	C	C	C	C	C	C	C	C	C	C	C	C
Level of Service	22.6	22.6	22.6	22.6	22.6	22.6	22.6	22.6	22.6	22.6	22.6	22.6
Approach Delay (s)	C	C	C	C	C	C	C	C	C	C	C	C
Approach LOS	17.8	17.8	17.8	17.8	17.8	17.8	17.8	17.8	17.8	17.8	17.8	17.8

Intersection Summary  
 HCM Average Control Delay 21.5 HCM Level of Service C  
 HCM Volume to Capacity ratio 0.61  
 Actuated Cycle Length (s) 80.0 Sum of lost time (s) 8.0  
 Intersection Capacity Utilization 62.9% ICU Level of Service B  
 Analysis Period (min) 15  
 Critical Lane Group c


117: Greenwood Ave & 3rd St  
2007 PM Peak Hour

Lane Group	EBL	EBT	WBL	WBT	NBL	NBT	SBL	SBT
Lane Configurations	310	775	300	585	150	960	325	745
Volume (vph)	310	775	300	585	150	960	325	745
Lane Group Flow (vph)	337	989	326	957	163	1364	353	930
Turn Type	Prot							
Protected Phases	7	4	3	8	1	6	5	2
Permitted Phases	7	4	3	8	1	6	5	2
Detector Phases	5.0	8.0	5.0	8.0	5.0	10.0	5.0	10.0
Minimum Initial (s)	9.0	27.0	9.0	27.0	9.0	24.0	9.0	24.0
Minimum Split (s)	24.0	24.0	24.0	24.0	22.0	47.0	25.0	50.0
Total Split (s)	20.0%	20.0%	20.0%	20.0%	18.3%	39.2%	20.8%	41.7%
Yellow Time (s)	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0
All-Red Time (s)	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Lead/Lag Optimizer?	Lead	Lag	Lead	Lag	Lag	Lead	Lead	Lead
Recall Mode	None	Ped	None	None	None	Min	None	C-Min
v/c Ratio	1.14	1.68	1.11	1.56	0.42	1.09	1.14	0.85
Control Delay	141.6	344.7	129.9	292.7	34.0	74.7	138.8	45.5
Queue Delay	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Delay	141.6	344.7	129.9	292.7	34.0	74.7	138.8	45.5
Queue Length 50th (ft)	~305	~590	~288	~533	73	~599	~319	350
Queue Length 95th (ft)	#491	#724	#471	#667	m133	m#533	#508	387
Internal Link Dist (ft)	1176				654			1798
Turn Bay Length (ft)	295	589	295	613	390	1248	310	1341
Base Capacity (vph)	0	0	0	0	0	0	0	0
Starvation Cap Reductn	0	0	0	0	0	0	0	0
Spillover Cap Reductn	0	0	0	0	0	0	0	0
Storage Cap Reductn	0	0	0	0	0	0	0	0
Reduced v/c Ratio	1.14	1.68	1.11	1.56	0.42	1.09	1.14	0.69

**Intersection Summary**

Cycle Length: 120  
 Actuated Cycle Length: 120  
 Offset: 43 (36%), Referenced to phase 2: SBT, Start of Green

Natural Cycle: 130  
 Control Type: Actuated-Coordinated  
 ~ Volume exceeds capacity, queue is theoretically infinite.  
 ~ Queue shown is maximum after two cycles.  
 # 95th percentile volume exceeds capacity, queue may be longer.  
 m Volume for 95th percentile queue is metered by upstream signal.



HCM Signalized Intersection Capacity Analysis  
 117: Greenwood Ave & 3rd St  
 2007 PM Peak Hour

Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Total Lost time (s)	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0
Lane Util. Factor	1.00	0.95	1.00	0.95	1.00	0.95	1.00	0.95	1.00	0.95	1.00	0.95
Fit Protected	1.00	0.98	1.00	0.95	1.00	0.98	1.00	0.96	1.00	0.98	1.00	0.98
Fit Permitted	0.95	1.00	0.95	1.00	0.95	1.00	0.95	1.00	0.95	1.00	0.95	1.00
Satd. Flow (prot)	1770	3460	1770	3361	1770	3414	1770	3471	1770	3471	1770	3471
Fit Permitted	0.95	1.00	0.95	1.00	0.95	1.00	0.95	1.00	0.95	1.00	0.95	1.00
Satd. Flow (perm)	1770	3460	1770	3361	1770	3414	1770	3471	1770	3471	1770	3471
Volume (vph)	310	775	135	300	585	295	150	960	295	325	745	110
Peak-hour factor, PHF	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Adtl. Flow (vph)	337	842	147	326	636	321	163	1043	321	353	810	120
RTOR Reduction (vph)	0	12	0	53	0	24	0	0	0	0	11	0
Lane Group Flow (vph)	337	977	0	326	905	0	163	1340	0	353	919	0
Turn Type	Prot	Prot	Prot	Prot	Prot	Prot	Prot	Prot	Prot	Prot	Prot	Prot
Protected Phases	7	4		3	8		1	6		5		2
Permitted Phases	7	4		3	8		1	6		5		2
Actuated Green, G (s)	20.0	20.0		20.0	20.0		26.4	43.0		21.0		37.6
Effective Green, g (s)	20.0	20.0		20.0	20.0		26.4	43.0		21.0		37.6
Effective g/C Ratio	0.17	0.17		0.17	0.17		0.22	0.36		0.18		0.31
Actuated g/C Ratio	0.17	0.17		0.17	0.17		0.22	0.36		0.18		0.31
Clearance Time (s)	4.0	4.0		4.0	4.0		4.0	4.0		4.0		4.0
Vehicle Extension (s)	2.5	2.5		2.5	2.5		2.5	4.3		2.5		4.3
Lane Grp Cap (vph)	295	577		295	560		389	1223		310		1088
v/s Ratio Prot	0.19	0.028		0.18	0.27		0.09	0.039		0.20		0.26
v/s Ratio Perm	1.14	1.69		1.11	1.62		0.42	1.10		1.14		0.84
v/c Ratio	1.14	1.69		1.11	1.62		0.42	1.10		1.14		0.84
Uniform Delay, d1	50.0	50.0		50.0	50.0		40.2	38.5		49.5		38.5
Progression Factor	1.00	1.00		1.00	1.00		0.75	0.66		1.00		1.00
Incremental Delay, d2	96.6	319.7		83.6	285.0		0.3	50.0		94.1		8.1
Delay (s)	146.6	369.7		133.6	335.0		30.6	75.6		143.6		46.5
Level of Service	F	F		F	F		C	E		F		D
Approach Delay (s)	313.0			283.8			70.8			73.2		
Approach LOS	F			F			E			E		E

**Intersection Summary**

HCM Average Control Delay: 181.1 HCM Level of Service: F  
 HCM Volume to Capacity ratio: 1.23  
 Actuated Cycle Length (s): 120.0 Sum of lost time (s): 16.0  
 Intersection Capacity Utilization: 110.1% ICU Level of Service: H  
 Analysis Period (min): 15  
 Critical Lane Group: c

HCM Unsignalized Intersection Capacity Analysis  
 118: Greenwood Ave & 4th St

Baseline  
 2007 PM Peak Hour

Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations	Free	Free	Free	Free	Free	Free	Stop	Stop	Stop	Stop	Stop	Stop
Sign Control	Free	Free	Free	Free	Free	Free	Stop	Stop	Stop	Stop	Stop	Stop
Grade	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%
Volume (veh/h)	30	1330	25	70	1055	140	0	0	130	0	0	155
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Hourly Flow rate (vph)	33	1446	27	76	1147	152	0	0	141	0	0	168
Pedestrians												
Lane Width (ft)												
Walking Speed (ft/s)												
Percent Blockage												
Right turn flare (veh)												
Median type							None	None	None	None	None	None
Median storage (veh)												
Upstream signal (ft)		495										
PX, platoon unblocked				0.84					0.84	0.84	0.84	0.84
VC, conflicting volume			1299		1473				2418	2976	736	2304
VC1, stage 1 conf vol												2913
VC2, stage 2 conf vol												649
VCU, unblocked vol		1299		1375					2496	3157	501	2361
IC, single (s)		4.1		4.1					7.5	6.5	6.9	6.5
IC, 2 stage (s)												6.9
IF (s)		2.2		2.2					3.5	4.0	3.3	4.0
p0 queue free %		94		82					100	100	67	100
p0 queue free %		94		82					100	100	67	100
cm capacity (veh/h)		529		417					6	7	434	9
cm capacity (veh/h)		529		417					6	7	434	9
cm capacity (veh/h)		529		417					6	7	434	9
cm capacity (veh/h)		529		417					6	7	434	9
Direction, Lane #	EB 1	EB 2	EB 3	WB 1	WB 2	WB 3	NB 1	NB 2	NB 3	SB 1	SB 2	SB 3
Volume Total	33	964	509	76	764	534	141	168				
Volume Left	33	0	0	76	0	0	0	0				
Volume Right	0	0	27	0	0	152	141	168				
CSH	529	1700	1700	417	1700	1700	434	412				
Volume to Capacity	0.06	0.57	0.30	0.18	0.45	0.31	0.33	0.41				
Queue Length 95th (ft)	5	0	0	16	0	0	35	49				
Control Delay (s)	12.2	0.0	0.0	15.5	0.0	0.0	17.2	19.6				
Lane LOS	B	C	C	C	C	C	C	C				
Approach Delay (s)	0.3			0.9			17.2	19.6				
Approach LOS	C			C			C	C				
<b>Intersection Summary</b>												
Average Delay	2.3			2.3			2.3			2.3		
Intersection Capacity Utilization	52.3%			52.3%			52.3%			52.3%		
Analysis Period (min)	15			15			15			15		
ICU Level of Service	A			A			A			A		

HCM Unsignalized Intersection Capacity Analysis  
 119: Hawthorne Ave & 3rd St

Baseline  
 2007 PM Peak Hour

Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations	Stop	Stop	Stop	Stop	Stop	Stop	Free	Free	Free	Free	Free	Free
Sign Control	Stop	Stop	Stop	Stop	Stop	Stop	Free	Free	Free	Free	Free	Free
Grade	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%
Volume (veh/h)	15	5	45	0	5	55	10	1385	35	35	1220	25
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Hourly Flow rate (vph)	16	5	49	0	5	60	11	1505	38	38	1326	27
Pedestrians												
Lane Width (ft)												
Walking Speed (ft/s)												
Percent Blockage												
Right turn flare (veh)												
Median type				TWLTTL								
Median storage (veh)				1	1	1	1	1	1	1	1	1
Upstream signal (ft)				0.84	0.84	0.77	0.84	0.84	0.73	0.77		745
PX, platoon unblocked				0.84	0.84	0.77	0.84	0.84	0.73	0.77		745
VC, conflicting volume				2253	2981	677	2337	2976	772	1353		1543
VC1, stage 1 conf vol				1416	1416		1546	1546				
VC2, stage 2 conf vol				837	1565		791	1429				
VCU, unblocked vol				1475	2340	278	1575	2334	308	1158		1371
IC, single (s)				7.5	6.5	6.9	7.5	6.5	6.9	4.1		4.1
IC, 2 stage (s)				6.5	5.5		6.5	5.5				
IF (s)				3.5	4.0	3.3	3.5	4.0	3.3	2.2		2.2
p0 queue free %				84	92	91	100	93	88	98		89
p0 queue free %				84	92	91	100	93	88	98		89
cm capacity (veh/h)				103	71	553	90	82	499	460		360
cm capacity (veh/h)				103	71	553	90	82	499	460		360
cm capacity (veh/h)				103	71	553	90	82	499	460		360
cm capacity (veh/h)				103	71	553	90	82	499	460		360
Direction, Lane #	EB 1	WB 1	NB 1	NB 2	NB 3	SB 1	SB 2	SB 3				
Volume Total	71	65	11	1004	540	38	884	469				
Volume Left	16	0	11	0	0	38	0	0				
Volume Right	49	60	0	0	38	0	0	27				
CSH	218	350	460	1700	1700	360	1700	1700				
Volume to Capacity	0.32	0.19	0.02	0.59	0.32	0.11	0.52	0.28				
Queue Length 95th (ft)	33	17	2	0	0	9	0	0				
Control Delay (s)	29.2	17.6	13.0	0.0	0.0	16.2	0.0	0.0				
Lane LOS	D	C	B	C	C	C	C	C				
Approach Delay (s)	29.2	17.6	0.1			0.4						
Approach LOS	D	C	C			C						
<b>Intersection Summary</b>												
Average Delay	1.3			1.3			1.3			1.3		
Intersection Capacity Utilization	56.6%			56.6%			56.6%			56.6%		
Analysis Period (min)	15			15			15			15		
ICU Level of Service	B			B			B			B		

HCM Unsignalized Intersection Capacity Analysis  
 120: Hawthorne Ave & 4th St


2007 PM Peak Hour  
 Baseline

Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		Stop		Stop		Stop		Free		Free		Free
Sign Control		Stop		Stop		Stop		Free		Free		Free
Grade	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%
Volume (veh/h)	50	30	30	5	10	5	15	90	5	10	130	35
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Hourly flow rate (vph)	54	33	33	5	11	5	16	98	5	11	141	38
Pedestrians												
Lane Width (ft)												
Walking Speed (ft/s)												
Percent Blockage												
Right turn flare (veh)												
Median type		None			None							
Median storage (veh)												
Upstream signal (ft)												
PX, platoon unblocked												
VC, conflicting volume	326	318	160	364	334	101	179					103
VC1, stage 1 conf vol												
VC2, stage 2 conf vol												
VCU, unblocked vol	326	318	160	364	334	101	179					103
TC, single (s)	7.1	6.5	6.2	7.1	6.5	6.2	4.1					4.1
TC, 2 stage (s)												
IF (s)	3.5	4.0	3.3	3.5	4.0	3.3	2.2					2.2
p0 queue free %	91	94	96	99	98	99	99					99
CM capacity (veh/h)	606	587	885	538	575	955	1396					1489
Direction, Lane #	EB 1	WB 1	NB 1	SB 1								
Volume Total	120	22	120	190								
Volume Left	54	5	16	11								
Volume Right	33	5	5	38								
CSH	656	627	1396	1489								
Volume to Capacity	0.18	0.03	0.01	0.01								
Queue Length 95th (ft)	17	3	1	1								
Control Delay (s)	11.7	11.0	1.1	0.5								
Lane LOS	B	B	A	A								
Approach Delay (s)	11.7	11.0	1.1	0.5								
Approach LOS	B	B	A	A								
<b>Intersection Summary</b>												
Average Delay	4.1											
Intersection Capacity Utilization	28.3%											
Analysis Period (min)	15											
ICU Level of Service	A											

Timings  
 121: Oregon St & Wall St.

2007 PM Peak Hour  
 Baseline

Lane Group	EBT	WBL	WBT	SBT
Lane Configurations	1	4	4	4
Volume (vph)	25	205	70	835
Lane Group Flow (vph)	54	0	299	1082
Turn Type	Perm			
Protected Phases	2	6	6	4
Permitted Phases				
Detector Phases	2	6	6	4
Minimum Initial (s)	4.0	4.0	4.0	4.0
Minimum Split (s)	20.5	20.5	20.5	20.5
Total Split (s)	47.0	47.0	47.0	33.0
Total Split (%)	58.8%	58.8%	58.8%	41.3%
Yellow Time (s)	4.0	4.0	4.0	4.0
All-Red Time (s)	0.0	0.0	0.0	0.0
Lead-Lag				
Lead-Lag Optimize?				
Recall Mode	Max	Max	Max	Max
v/c Ratio	0.07	0.46	0.46	0.93
Control Delay	5.6	15.4	27.7	
Queue Delay	0.0	0.0	1.3	
Total Delay	5.6	15.4	28.9	
Queue Length 50th (ft)	6	107	178	
Queue Length 95th (ft)	22	181	m#382	
Internal Link Dist (ft)	126	313	295	
Turn Bay Length (ft)				
Base Capacity (vph)	820	646	1164	
Starvation Cap Reductn	0	0	20	
Spillback Cap Reductn	0	0	0	
Storage Cap Reductn	0	0	0	
Reduced v/c Ratio	0.07	0.46	0.95	
<b>Intersection Summary</b>				
Cycle Length: 80				
Actuated Cycle Length: 80				
Offset: 61 (76%), Referenced to phase 2:EBT, Start of Green				
Natural Cycle: 50				
Control Type: Pretimed				
# 95th percentile volume exceeds capacity, queue may be longer.				
Queue shown is maximum after two cycles.				
m Volume for 95th percentile queue is metered by upstream signal.				



HCM Signalized Intersection Capacity Analysis  
 121: Oregon St & Wall St

Baseline  
 2007 PM Peak Hour

Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		↓			↓						↓	↓
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Total Lost time (s)	4.0				4.0						4.0	4.0
Lane Util. Factor	1.00				1.00						0.95	0.95
Fit Protected	0.93				1.00						1.00	0.99
Satd. Flow (prot)	1503				1553						3206	3206
Fit Permitted	1.00				0.75						0.99	0.99
Satd. Flow (perm)	1503				1203						3206	3206
Volume (vph)	0	25	25	205	70	0	0	0	0	140	835	20
Peak-hour factor, PHF	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Adj. Flow (vph)	0	27	27	223	76	0	0	0	0	152	908	22
RTOR Reduction (vph)	0	12	0	0	0	0	0	0	0	0	2	0
Lane Group Flow (vph)	0	42	0	0	299	0	0	0	0	1080	0	0
Parking (#/hr)	7	7	7	7	7	7	7	7	7	14	14	14
Turn Type				Perm						Perm		
Protected Phases		2			6						4	
Permitted Phases												
Actuated Green, G (s)		43.0			43.0						29.0	
Effective Green, g (s)		43.0			43.0						29.0	
Actuated g/C Ratio		0.54			0.54						0.36	
Clearance Time (s)		4.0			4.0						4.0	
Lane Grp Cap (vph)		808			647						1162	
v/s Ratio Prot		0.03									0.34	
v/s Ratio Perm											0.33	
v/c Ratio		0.05			0.46						0.33	
Uniform Delay, d1		8.8			11.4						24.5	
Progression Factor		1.00			1.12						0.58	
Incremental Delay, d2		0.1			2.0						11.6	
Delay (s)		8.9			14.7						25.9	
Level of Service		A			B						C	
Approach Delay (s)		8.9			14.7						25.9	
Approach LOS		A			B						C	
<b>Intersection Summary</b>												
HCM Average Control Delay		22.9			HCM Level of Service						C	
HCM Volume to Capacity ratio		0.65			Sum of lost time (s)						8.0	
Actuated Cycle Length (s)		80.0			ICU Level of Service						B	
Intersection Capacity Utilization		56.2%			Analysis Period (min)						15	
c Critical Lane Group												

Timings  
 122: Oregon St & Bond St

Baseline  
 2007 PM Peak Hour

Lane Group	EBL	EBT	WBT	NBT
Lane Configurations		↓	↓	↓
Volume (vph)	100	100	95	795
Lane Group Flow (vph)	0	218	282	1174
Turn Type		Perm		
Protected Phases		2	6	8
Permitted Phases		2	2	6
Detector Phases		2	2	8
Minimum Initial (s)		4.0	4.0	4.0
Minimum Split (s)		20.5	20.5	20.5
Total Split (s)		33.0	33.0	47.0
Total Split (%)		41.3%	41.3%	58.8%
Yellow Time (s)		4.0	4.0	4.0
All-Red Time (s)		0.0	0.0	0.0
Lead-Lag				
Lead-Lag Optimize?				
Recall Mode		Max	Max	Max
v/c Ratio		0.49	0.41	0.63
Control Delay		13.6	12.4	10.7
Queue Delay		0.0	0.0	0.0
Total Delay		13.6	12.4	10.8
Queue Length 50th (ft)		67	55	127
Queue Length 95th (ft)		m86	117	m161
Internal Link Dist (ft)		313	523	693
Turn Bay Length (ft)				
Base Capacity (vph)		442	696	1869
Starvation Cap Reductn		0	0	0
Spillback Cap Reductn		0	0	8
Storage Cap Reductn		0	0	0
Reduced v/c Ratio		0.49	0.41	0.63
<b>Intersection Summary</b>				
Cycle Length: 80				
Actuated Cycle Length: 80				
Offset: 51 (64%), Referenced to phase 2:EBT1 and 6:WBT1, Start of Green				
Natural Cycle: 45				
Control Type: Prelimed				
m Volume for 95th percentile queue is metered by upstream signal.				
Splits and Phases: 122: Oregon St & Bond St				

HCM Signalized Intersection Capacity Analysis  
 122: Oregon St & Bond St  
 Baseline  
 2007 PM Peak Hour

Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		4			4			4	4			
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Total Lost time (s)	4.0				4.0			4.0	4.0			
Lane Util. Factor	1.00	1.00	1.00	1.00	1.00	1.00	1.00	0.95	0.95	1.00	1.00	1.00
Fit Protected	1.00	0.98	1.00	0.91	0.98	1.00	0.99	0.98	0.99	1.00	1.00	1.00
Satd. Flow (prot)	1817	1817	1817	1703	1703	1703	3457	3457	3457	1703	1703	1703
Fit Permitted	0.65	1.00	0.65	1.00	0.99	1.00	0.99	0.99	0.99	1.00	1.00	1.00
Satd. Flow (perm)	1220	1220	1220	1703	1703	1703	3457	3457	3457	1703	1703	1703
Volume (vph)	100	100	0	0	95	165	175	795	110	0	0	0
Peak-hour factor, PHF	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Adj. Flow (vph)	109	109	0	0	103	179	190	864	120	0	0	0
RTOR Reduction (vph)	0	0	0	0	78	0	11	0	0	0	0	0
Lane Group Flow (vph)	0	218	0	0	204	0	0	1163	0	0	0	0
Turn Type	Perm	Perm			Perm			Perm	Perm			
Protected Phases		2			6			8				
Permitted Phases		2			6			8				
Actuated Green, G (s)		29.0			29.0			43.0				
Effective Green, g (s)		29.0			29.0			43.0				
Actuated g/C Ratio		0.36			0.36			0.54				
Clearance Time (s)		4.0			4.0			4.0				
Lane Grp Cap (vph)		442			617			1858				
v/s Ratio Prot					0.12			0.34				
v/s Ratio Perm		0.18			0.33			0.63				
v/c Ratio		0.49			19.8			12.9				
Uniform Delay, d1		0.52			1.00			0.73				
Progression Factor		2.9			1.4			1.3				
Incremental Delay, d2		13.2			19.9			10.7				
Delay (s)		13.2			19.9			10.7				
Level of Service		B			B			B				
Approach Delay (s)		13.2			19.9			10.7				0.0
Approach LOS		B			B			B				A
<b>Intersection Summary</b>												
HCM Average Control Delay		12.6			HCM Level of Service			B				
HCM Volume to Capacity ratio		0.57			Sum of lost time (s)			8.0				
Actuated Cycle Length (s)		80.0			ICU Level of Service			C				
Intersection Capacity Utilization		66.5%			Analysis Period (min)			15				
c Critical Lane Group												

HCM Unsignalized Intersection Capacity Analysis  
 123: Oregon St & Bend Pkwy SB Ramp  
 Baseline  
 2007 PM Peak Hour


Movement	EBL	EBR	NBL	NBT	SBT	SBR
Lane Configurations						
Sign Control	Stop		Free	Free	Free	Free
Grade	0%		0%	0%	0%	0%
Volume (veh/h)	0	245	0	2610	2695	220
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92
Hourly flow rate (vph)	0	266	0	2837	2929	239
Pedestrians						
Lane Width (ft)						
Walking Speed (ft/s)						
Percent Blockage						
Right turn flare (veh)						
Median type		None				
Median storage (veh)						
Upstream signal (ft)				773	710	
pX, platoon unblocked						
VC, conflicting volume		4348	1465	3168		
VC1, stage 1 conf vol						
VC2, stage 2 conf vol						
VCU, unblocked vol		4348	1465	3168		
TC, single (s)		6.8	6.9	4.1		
TC, 2 stage (s)						
IF (s)		3.5	3.3	2.2		
p0 queue free %		100	0	100		
cM capacity (veh/h)		1	117	97		
Direction, Lane #	EB 1	NB 1	NB 2	SB 1	SB 2	SB 3
Volume Total	266	1418	1418	1465	1465	239
Volume Left	0	0	0	0	0	0
Volume Right	266	0	0	0	0	239
CSH	117	1700	1700	1700	1700	1700
Volume to Capacity	2.27	0.83	0.83	0.86	0.86	0.14
Queue Length 95th (ft)	57.4	0	0	0	0	0
Control Delay (s)	656.8	0.0	0.0	0.0	0.0	0.0
Lane LOS	F					
Approach Delay (s)	656.8	0.0	0.0	0.0	0.0	0.0
Approach LOS	F					
<b>Intersection Summary</b>						
Average Delay		27.9				
Intersection Capacity Utilization		96.3%				
Analysis Period (min)		15				
ICU Level of Service F						

Lane Group	EBT	WBL	WBT	SBT	SBR
Lane Configurations	465	175	390	510	280
Volume (vph)	465	175	390	510	280
Lane Group Flow (vph)	538	190	424	809	304
Turn Type	pm+pt			Perm	
Protected Phases	8	7	4	6	6
Permitted Phases	8	7	4	6	6
Detector Phases	4	4	4	6	6
Minimum Initial (s)	20.5	8.5	20.5	20.5	20.5
Minimum (s)	31.0	16.0	47.0	33.0	33.0
Total Split (%)	38.8%	20.0%	58.8%	41.3%	41.3%
Yellow Time (s)	4.0	4.0	4.0	4.0	4.0
All-Red Time (s)	0.0	0.0	0.0	0.0	0.0
Lead/Lag	Lag	Lead			
Lead-Lag Optimizer?	Yes	Yes			
Recall Mode	Max	Max	Max	Max	Max
v/c Ratio	0.86	0.53	0.42	0.64	0.40
Control Delay	40.4	19.7	2.4	23.3	6.6
Queue Delay	0.0	0.0	0.9	0.0	0.0
Total Delay	40.4	19.7	3.3	23.3	6.6
Queue Length 50th (ft)	246	23	14	126	22
Queue Length 95th (ft)	#425	m141	m19	m153	m37
Internal Link Dist (ft)	420		308	677	
Turn Bay Length (ft)					
Base Capacity (vph)	626	359	1001	1263	768
Starvation Cap Reductn	0	0	317	0	0
Spillback Cap Reductn	0	0	0	0	0
Storage Cap Reductn	0	0	0	0	0
Reduced v/c Ratio	0.86	0.53	0.62	0.64	0.40

**Intersection Summary**

Cycle Length: 80
Actuated Cycle Length: 80
Offset: 0.00%, Referenced to phase 4:WBL and 8:EBT, Start of Green
Natural Cycle: 60
Control Type: Prelimed
# 95th Percentile Volume Exceeds Capacity, Queue May Be Longer.
Queue shown is maximum after two cycles.
m Volume for 95th Percentile Queue is Metered by Upstream Signal.

Splits and Phases: 124: Franklin Ave & Wall St.




Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Total Lost Time (s)	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0
Lane Util. Factor	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Fit	0.99	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Fit Protected	1.00	0.95	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Satd. Flow (prot)	1847	1770	1863	1847	1770	1863	1847	1770	1863	1847	1770	1863
Fit Permitted	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Satd. Flow (perm)	1847	1847	1847	1847	1847	1847	1847	1847	1847	1847	1847	1847
Volume (vph)	0	465	30	175	390	0	0	0	0	235	510	280
Peak-hour factor, PHF	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Adtl. Flow (vph)	0	505	33	190	424	0	0	0	0	255	554	304
RTOR Reduction (vph)	0	3	0	0	0	0	0	0	0	0	0	194
Lane Group Flow (vph)	0	535	0	190	424	0	0	0	0	0	809	110
Turn Type			pm+pt									
Protected Phases	8		7		4						6	6
Permitted Phases			4		4						6	6
Actuated Green, G (s)	27.0		43.0		43.0						29.0	29.0
Effective Green, g (s)	27.0		43.0		43.0						29.0	29.0
Actuated g/c Ratio	0.34		0.54		0.54						0.36	0.36
Clearance Time (s)	4.0		4.0		4.0						4.0	4.0
Lane Grp Cap (vph)	623		359		1001						1263	574
v/s Ratio Prot	c0.29		c0.08		0.23							
v/s Ratio Perm			0.21		0.42						0.23	0.07
v/c Ratio	0.86		0.53		0.42						0.64	0.19
Uniform Delay, d1	24.7		13.6		11.1						21.2	17.5
Progression Factor	1.00		1.46		0.15						1.02	2.32
Incremental Delay, d2	14.4		2.8		0.7						1.4	0.4
Delay (s)	39.1		22.7		2.4						22.9	40.9
Level of Service	D		C		A						C	D
Approach Delay (s)	39.1				8.7						27.8	
Approach LOS	D				A						C	

**Intersection Summary**

HCM Average Control Delay	25.3	HCM Level of Service	C
HCM Volume to Capacity ratio	0.71		
Actuated Cycle Length (s)	80.0	Sum of lost time (s)	12.0
Intersection Capacity Utilization	71.8%	ICU Level of Service	C
Analysis Period (min)	15		
c Critical Lane Group			

Lane Group	EBL	EBT	WBT	WBR	NBT	NBR
Lane Configurations	260	435	505	115	690	285
Volume (vph)	283	473	549	125	815	310
Lane Group Flow (vph)	custom Perm					
Turn Type	pm+pt					
Protected Phases	3	8	4	8	2	2
Permitted Phases	8	8	4	8	2	2
Detector Phases	3	8	4	8	2	2
Minimum Initial (s)	4.0	4.0	4.0	4.0	4.0	4.0
Minimum (s)	8.5	20.5	20.5	20.5	20.5	20.5
Total Split (s)	13.0	44.0	31.0	44.0	36.0	36.0
Total Split (%)	16.3%	55.0%	38.8%	55.0%	45.0%	45.0%
Yellow Time (s)	4.0	4.0	4.0	4.0	4.0	4.0
All-Red Time (s)	0.0	0.0	0.0	0.0	0.0	0.0
Lead/Lag Optimizer?	Yes	Yes	Yes	Yes	Yes	Yes
Recall Mode	Max	Max	Max	Max	Max	Max
v/c Ratio	0.97	0.27	0.87	0.15	0.58	0.38
Control Delay	62.0	21.2	42.0	4.5	20.8	3.5
Queue Delay	0.0	0.0	0.0	0.0	0.0	0.0
Total Delay	62.0	21.2	42.0	4.5	20.8	3.5
Queue Length 50th (ft)	134	114	254	8	162	0
Queue Length 95th (ft)	m#176	#436	34	219	46	
Internal Link Dist (ft)	308 596 574					
Turn Bay Length (ft)	292 1770 629 837 1410 819					
Base Capacity (vph)	0	0	0	0	0	0
Starvation Cap Reductn	0	0	0	0	0	0
Spillback Cap Reductn	0	0	0	0	0	0
Storage Cap Reductn	0	0	0	0	0	0
Reduced v/c Ratio	0.97	0.27	0.87	0.15	0.58	0.38

**Intersection Summary**  
 Cycle Length: 80  
 Actuated Cycle Length: 80  
 Offset: 59 (74%), Referenced to phase 4:WBT and 8:EBTL, Start of Green  
 Natural Cycle: 55  
 Control Type: Pretimed  
 # 95th Percentile Volume Exceeds Capacity, Queue may be longer.  
 Queue shown is maximum after two cycles.  
 m Volume for 95th percentile queue is metered by upstream signal.



Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Ideal Flow (vphpl)	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0
Total Lost time (s)	1.00	0.95	1.00	1.00	1.00	0.95	1.00	0.95	1.00	1.00	0.85	1.00
Lane Util. Factor	1.00	1.00	1.00	1.00	1.00	0.85	1.00	0.85	1.00	1.00	0.85	1.00
Fit Protected	0.95	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Satd. Flow (prot)	1770	3539	1770	1770	1770	1863	1583	1863	1583	1770	3539	1770
Fit Permitted	0.13	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Satd. Flow (perm)	240	3539	240	3539	240	1863	1583	240	3539	240	3539	240
Volume (vph)	260	435	0	0	505	115	60	690	285	0	0	0
Peak-hour factor, PHF	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Adj. Flow (vph)	283	473	0	0	549	125	65	750	310	0	0	0
RTOR Reduction (vph)	0	0	0	0	45	0	186	0	0	0	0	0
Lane Group Flow (vph)	283	473	0	0	549	80	815	124	0	0	0	0
Turn Type	pm+pt	8	8	8	8	8	8	8	8	8	8	8
Protected Phases	3	8	8	8	8	8	8	8	8	8	8	8
Permitted Phases	8	8	8	8	8	8	8	8	8	8	8	8
Actuated Green, G (s)	40.0	40.0	40.0	40.0	40.0	40.0	40.0	40.0	40.0	40.0	40.0	40.0
Effective Green, g (s)	40.0	40.0	40.0	40.0	40.0	40.0	40.0	40.0	40.0	40.0	40.0	40.0
Actuated g/C Ratio	0.50	0.50	0.50	0.50	0.50	0.50	0.50	0.50	0.50	0.50	0.50	0.50
Clearance Time (s)	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0
Lane Grp Cap (vph)	292	1770	629	792	1410	633	292	1770	629	792	1410	633
v/s Ratio Prot	60.11	0.13	0.29	0.29	0.29	0.29	0.29	0.29	0.29	0.29	0.29	0.29
v/s Ratio Perm	60.37	0.27	0.87	0.10	0.58	0.20	0.87	0.10	0.58	0.20	0.87	0.10
v/c Ratio	0.97	0.27	0.87	0.10	0.58	0.20	0.97	0.27	0.87	0.10	0.58	0.20
Uniform Delay, d1	19.4	11.5	24.9	10.5	18.7	15.6	19.4	11.5	24.9	10.5	18.7	15.6
Progression Factor	1.61	1.80	1.00	1.00	1.00	1.00	1.61	1.80	1.00	1.00	1.00	1.00
Incremental Delay, d2	33.6	0.2	15.5	0.3	1.7	0.7	33.6	0.2	15.5	0.3	1.7	0.7
Delay (s)	64.9	21.0	40.3	10.8	20.5	16.3	64.9	21.0	40.3	10.8	20.5	16.3
Level of Service	E	C	D	B	C	B	E	C	D	B	C	B
Approach Delay (s)	37.4	34.9	34.9	34.9	34.9	34.9	37.4	34.9	34.9	34.9	34.9	34.9
Approach LOS	D	D	C	C	C	B	D	D	C	C	C	B

**Intersection Summary**  
 HCM Average Control Delay: 28.8  
 HCM Volume to Capacity ratio: 0.78  
 Actuated Cycle Length (s): 80.0  
 Intersection Capacity Utilization: 71.8%  
 Analysis Period (min): 15  
 Critical Lane Group: c



Lane Group	EBL	EBT	EBR	WBL	WBT	NBL	NBT	SBL	SBT
Lane Configurations	345	640	115	180	415	175	1035	105	1045
Volume (vph)	345	640	115	180	415	175	1035	105	1045
Lane Group Flow (vph)	375	696	125	196	527	190	1174	114	1272
Turn Type	Prot	Perm	Prot						
Protected Phases	7	4	4	3	8	1	6	5	2
Permitted Phases	7	4	4	3	8	1	6	5	2
Detector Phases	5.0	5.0	5.0	5.0	5.0	5.0	10.0	5.0	10.0
Minimum Initial (s)	9.0	26.0	26.0	9.0	26.0	9.0	24.0	9.0	24.0
Minimum Split (s)	22.0	40.0	40.0	10.0	28.0	17.0	58.0	12.0	53.0
Total Split (s)	18.3%	33.3%	33.3%	8.3%	23.3%	14.2%	48.3%	10.0%	44.2%
Yellow Time (s)	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0
All-Red Time (s)	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Lead/Lag Optimizer?	Lead	Lag	Lag	Lead	Lead	Lead	Lag	Lag	Lag
Lead/Lag Optimizer?	Yes								
Recall Mode	Max								
v/c Ratio	1.41	0.66	0.22	2.20	0.75	0.99	0.74	0.97	0.89
Control Delay	243.4	40.1	6.4	602.4	51.5	116.2	30.6	91.6	23.9
Queue Delay	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Delay	243.4	40.1	6.4	602.4	51.5	116.2	30.6	91.6	23.9
Queue Length 50th (ft)	~390	246	0	~245	198	149	384	94	525
Queue Length 95th (ft)	#562	314	44	#396	282	#302	470	m#111	m412
Internal Link Dist (ft)	1152			410		1273			665
Turn Bay Length (ft)									
Base Capacity (vph)	266	1062	562	89	703	192	1586	118	1430
Starvation Cap Reductn	0	0	0	0	0	0	0	0	0
Spillback Cap Reductn	0	0	0	0	0	0	0	0	0
Storage Cap Reductn	0	0	0	0	0	0	0	0	0
Reduced v/c Ratio	1.41	0.66	0.22	2.20	0.75	0.99	0.74	0.97	0.89



C:\Documents and Settings\prester.000\Desktop\Bend Synchro\Existing sy7  
Parametrix, Inc. Synchro 6 Report  
1/19/2007

Movement	EBL	EBT	EBR	WBL	WBT	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Total Lost time (s)	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0
Lane Util. Factor	1.00	0.95	1.00	1.00	0.95	1.00	0.95	1.00	0.95	1.00	0.95
Fit	1.00	1.00	0.85	1.00	0.98	1.00	0.99	1.00	0.98	1.00	0.98
Fit Protected	0.95	1.00	1.00	0.95	1.00	0.95	1.00	0.95	1.00	1.00	0.95
Satd. Flow (prot)	1770	3539	1583	1770	3463	1770	3517	1770	3482	1770	3482
Fit Permitted	0.95	1.00	1.00	0.95	1.00	0.95	1.00	0.95	1.00	1.00	0.95
Satd. Flow (perm)	1770	3539	1583	1770	3463	1770	3517	1770	3482	1770	3482
Volume (vph)	345	640	115	180	415	175	1035	105	1045	125	125
Peak-hour factor, PHF	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Adtl. Flow (vph)	375	696	125	196	527	190	1125	114	1272	136	136
RTOR Reduction (vph)	0	0	88	0	11	0	0	0	0	8	8
Lane Group Flow (vph)	375	696	38	196	516	0	190	1171	0	114	1264
Turn Type	Prot	Perm	Prot	Prot	Prot	Prot	Prot	Prot	Prot	Prot	Prot
Protected Phases	7	4	4	3	8	1	6	5	2	2	2
Permitted Phases	7	4	4	3	8	1	6	5	2	2	2
Actuated Green, G (s)	18.0	36.0	36.0	6.0	24.0	13.0	54.0	8.0	49.0	8.0	49.0
Effective Green, g (s)	18.0	36.0	36.0	6.0	24.0	13.0	54.0	8.0	49.0	8.0	49.0
Actuated g/c Ratio	0.15	0.30	0.30	0.05	0.20	0.11	0.45	0.07	0.41	0.07	0.41
Clearance Time (s)	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0
Lane Grp Cap (vph)	266	1062	475	89	693	192	1583	118	1422	118	1422
v/s Ratio Prot	c0.21	0.20		c0.11	c0.15		c0.11	0.33	0.06	c0.36	
v/s Ratio Perm	1.41	0.66	0.08	2.20	0.74	0.99	0.74	0.97	0.89	0.97	0.89
v/c Ratio	1.41	0.66	0.08	2.20	0.74	0.99	0.74	0.97	0.89	0.97	0.89
Uniform Delay, d1	51.0	36.6	30.1	57.0	45.1	53.4	27.2	55.9	33.0	55.9	33.0
Progression Factor	1.00	1.00	1.00	1.00	1.00	1.00	1.00	0.76	0.59	0.76	0.59
Incremental Delay, d2	205.3	3.2	0.3	575.8	7.1	62.3	3.1	46.5	4.1	46.5	4.1
Delay (s)	256.3	39.8	30.4	632.8	52.2	115.7	30.4	88.8	23.4	88.8	23.4
Level of Service	F	D	C	D	F	D	F	C	F	C	C
Approach Delay (s)	106.7							209.6			288.7
Approach LOS	F							F			C



C:\Documents and Settings\prester.000\Desktop\Bend Synchro\Existing sy7  
Parametrix, Inc. Synchro 6 Report  
1/19/2007

HCM Unsignalized Intersection Capacity Analysis  
127: Franklin Ave & 4th St

Baseline  
2007 PM Peak Hour

Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations	Free	Free	Free	Free	Free	Free	Stop	Stop	Stop	Stop	Stop	Stop
Sign Control	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%
Volume (veh/h)	70	660	45	25	470	15	25	25	45	15	15	145
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Hourly flow rate (vph)	76	717	49	27	511	16	27	27	49	16	16	158
Pedestrians												
Lane Width (ft)												
Walking Speed (ft/s)												
Percent Blockage												
Right turn flare (veh)												
Median storage (veh)												
Upstream signal (ft)		490										
PX, platoon unblocked			0.84				0.84	0.84	0.84	0.84		
VC, conflicting volume	527		766				1370	1476	383	1147	1492	264
VC1, stage 1 conf vol												
VC2, stage 2 conf vol	527		533				1250	1376	77	985	1396	264
VCU, unblocked vol	4.1		4.1				7.5	6.5	6.9	7.5	6.5	6.9
IC, 2 stage (s)												
IF (s)	2.2		2.2				3.5	4.0	3.3	3.5	4.0	3.3
p0 queue free %	93		97				61	75	94	86	85	79
CM capacity (veh/h)	1036		867				69	109	814	119	106	735
Direction, Lane #	EB 1	EB 2	EB 3	WB 1	WB 2	WB 3	NB 1	NB 1	SB 1	SB 1	SB 1	SB 1
Volume Total	76	478	288	27	341	187	103	103	190			
Volume Left	76	0	0	0	27	0	0	27	16			
Volume Right	0	0	49	0	0	16	49	158				
CSH	1036	1700	1700	867	1700	147	376					
Volume to Capacity	0.07	0.28	0.17	0.03	0.20	0.11	0.70	0.51				
Queue Length 95th (ft)	6	0	0	2	0	0	101	69				
Control Delay (s)	8.8	0.0	0.0	9.3	0.0	0.0	72.9	23.9				
Lane LOS	A			A			F	C				
Approach Delay (s)	0.8			0.5			72.9	23.9				
Approach LOS							F	C				
<b>Intersection Summary</b>												
Average Delay	7.7											
Intersection Capacity Utilization	44.8%											
ICU Level of Service	A											
Analysis Period (min)	15											


HCM Unsignalized Intersection Capacity Analysis  
128: Tumalo Ave & Riverside Dr

Baseline  
2007 PM Peak Hour

Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations	Stop	Stop	Stop	Stop	Stop	Stop	Stop	Stop	Stop	Stop	Stop	Stop
Sign Control	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%
Volume (vph)	315	205	30	0	210	5	50	5	15	30	570	
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	
Hourly flow rate (vph)	342	223	33	0	228	5	54	5	16	33	620	
Direction, Lane #	EB 1	WB 1	NB 1	SB 1	SB 2							
Volume Total (vph)	598	234	65	49	620							
Volume Left (vph)	342	0	54	16	0							
Volume Right (vph)	33	5	5	0	620							
Hadl (s)	0.12	0.02	0.15	0.20	-0.67							
Departure Headway (s)	6.7	7.4	8.4	7.4	6.5							
Degree Utilization, x	1.12	0.48	0.15	0.10	1.12							
Capacity (veh/h)	540	480	406	476	555							
Control Delay (s)	99.8	17.0	13.0	10.0	100.1							
Approach Delay (s)	99.8	17.0	13.0	93.6								
Approach LOS	F	C	B	F								
<b>Intersection Summary</b>												
Delay	81.1											
HCM Level of Service	F											
Intersection Capacity Utilization	61.4%											
ICU Level of Service	B											
Analysis Period (min)	15											

Lane Group	WBT	SBT
<b>Lane Configurations</b>	4T	4T
Volume (vph)	615	485
Lane Group Flow (vph)	793	701
Turn Type		
Protected Phases	6	4
Detector Phases	6	4
Minimum Initial (s)	4.0	4.0
Minimum Split (s)	20.5	20.5
Total Split (s)	32.0	28.0
Total Split (%)	53.3%	46.7%
Yellow Time (s)	4.0	4.0
All-Red Time (s)	0.0	0.0
Lead-Lag Optimizer?		
Recall Mode	Max	Max
v/c Ratio	0.51	0.53
Control Delay	4.7	13.5
Queue Delay	0.1	0.0
Total Delay	4.8	13.5
Queue Length 50th (ft)	20	83
Queue Length 95th (ft)	26	128
Internal Link Dist (ft)	229	1179
Turn Bay Length (ft)		
Base Capacity (vph)	1561	1331
Starvation Cap Reducin	161	0
Spillback Cap Reducin	0	0
Storage Cap Reducin	0	0
Reduced v/c Ratio	0.57	0.53

**Intersection Summary**  
 Cycle Length: 60  
 Actuated Cycle Length: 60  
 Offset: 10 (17%), Referenced to phase 6:WBT\_L, Start of Green  
 Natural Cycle: 45  
 Control Type: Prelimed




Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
<b>Lane Configurations</b>					4T						4T	
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Total Lost time (s)					4.0						4.0	
Lane Util. Factor					0.95						0.95	
Fit					1.00						0.96	
Fit Protected					0.99						1.00	
Satd. Flow (prot)					3292						3194	
Fit Permitted					0.99						1.00	
Satd. Flow (perm)					3292						3194	
Volume (vph)	0	0	0	115	615	0	0	0	0	0	485	160
Peak-hour factor, PHF	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Adj. Flow (vph)	0	0	0	125	668	0	0	0	0	0	527	174
RTOR Reduction (vph)	0	0	0	0	26	0	0	0	0	0	53	0
Lane Group Flow (vph)	0	0	0	0	767	0	0	0	0	0	648	0
Parking (#/hr)					5					5		5
Turn Type					Perm						Perm	
Protected Phases					6						6	4
Actuated Green, G (s)					28.0						24.0	
Effective Green, g (s)					28.0						24.0	
Actuated g/C Ratio					0.47						0.40	
Clearance Time (s)					4.0						4.0	
Lane Grp Cap (vph)					1536						1278	
v/s Ratio Prot					0.23						0.20	
v/c Ratio Perm					0.50						0.51	
Uniform Delay, d1					11.1						13.5	
Progression Factor					0.35						1.00	
Incremental Delay, d2					1.0						1.4	
Level of Service					A						B	
Approach Delay (s)					0.0						4.8	0.0
Approach LOS					A						A	B

**Intersection Summary**  
 HCM Average Control Delay: 9.6 HCM Level of Service: A  
 HCM Volume to Capacity ratio: 0.50  
 Actuated Cycle Length (s): 60.0 Sum of lost time (s): 8.0  
 Intersection Capacity Utilization: 45.5% ICU Level of Service: A  
 Analysis Period (min): 15  
 Critical Lane Group: c

Lane Group	WBT	NBT
<b>Lane Configurations</b>	↕↕	↕↕
Volume (vph)	640	740
Lane Group Flow (vph)	854	891
Turn Type		
Protected Phases	6	8
Detector Phases	6	8
Minimum Initial (s)	4.0	4.0
Minimum (s)	20.0	20.0
Total Split (s)	32.0	28.0
Total Split (%)	53.3%	46.7%
Yellow Time (s)	3.5	3.5
All-Red Time (s)	0.5	0.5
Lead-Lag Optimizer?		
Recall Mode	Max	Max
v/c Ratio	0.56	0.68
Control Delay	12.4	17.3
Queue Delay	0.0	0.7
Total Delay	12.4	17.9
Queue Length 50th (ft)	101	123
Queue Length 95th (ft)	150	m167
Internal Link Dist (ft)	1497	225
Turn Bay Length (ft)		
Base Capacity (vph)	1517	1317
Starvation Cap Reducin	0	155
Spillback Cap Reducin	0	0
Storage Cap Reducin	0	0
Reduced v/c Ratio	0.56	0.77

**Intersection Summary**

Cycle Length: 60  
 Actuated Cycle Length: 60  
 Offset: 0.0(0%). Referenced to phase 6(WBT, Start of Green)  
 Natural Cycle: 40  
 Control Type: Pretimed  
 m Volume for 95th percentile queue is metered by upstream signal.



Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
<b>Lane Configurations</b>					↕↕			↕↕				
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Total Lost time (s)					4.0			4.0				
Lane Util. Factor					0.95			0.95				
Fit					0.97			1.00				
Fit Protected					1.00			1.00				
Satd. Flow (prot)					3183			3258				
Fit Permitted					1.00			1.00				
Satd. Flow (perm)					3183			3258				
Volume (vph)	0	0	0	0	640	145	80	740	0	0	0	0
Peak-hour factor, PHF	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Adj. Flow (vph)	0	0	0	0	696	158	87	804	0	0	0	0
RTOR Reduction (vph)	0	0	0	0	33	0	0	14	0	0	0	0
Lane Group Flow (vph)	0	0	0	0	821	0	0	877	0	0	0	0
Parking (#/hr)					10	10	10	10				
Turn Type					Perm			Perm				
Protected Phases					6			8				
Actuated Green, G (s)					28.0			24.0				
Effective Green, g (s)					28.0			24.0				
Actuated g/C Ratio					0.47			0.40				
Clearance Time (s)					4.0			4.0				
Lane Grp Cap (vph)					1485			1303				
v/s Ratio Prot					60.26			0.27				
v/s Ratio Perm					0.55			0.67				
v/c Ratio					11.5			14.8				
Uniform Delay, d1					1.00			1.04				
Progression Factor					1.5			1.9				
Incremental Delay, d2					13.0			17.3				
Delay (s)					13.0			17.3				
Level of Service					B			B				
Approach Delay (s)		0.0			13.0			17.3				
Approach LOS		A			B			B				


**Intersection Summary**

HCM Average Control Delay: 15.2 HCM Level of Service: B  
 HCM Volume to Capacity ratio: 0.61  
 Actuated Cycle Length (s): 60.0 Sum of lost time (s): 8.0  
 Intersection Capacity Utilization: 51.8% ICU Level of Service: A  
 Analysis Period (min): 15  
 Critical Lane Group: c

Lane Group	EBT	SBT
<b>Lane Configurations</b>	↕↕	↕↕
Volume (vph)	1170	390
Lane Group Flow (vph)	1299	653
Turn Type		
Protected Phases	2	4
Detector Phases	2	4
Minimum Initial (s)	4.0	4.0
Minimum (s)	20.5	20.5
Total Split (s)	34.0	26.0
Total Split (%)	56.7%	43.3%
Yellow Time (s)	4.0	4.0
All-Red Time (s)	0.0	0.0
Lead-Lag Optimizer?		
Recall Mode	Max	Max
v/c Ratio	0.78	0.55
Control Delay	11.5	9.2
Queue Delay	26.8	0.1
Total Delay	38.3	9.3
Queue Length 50th (ft)	103	34
Queue Length 95th (ft)	132	45
Internal Link Dist (ft)	228	224
Turn Bay Length (ft)		
Base Capacity (vph)	1657	1201
Starvation Cap Reducin	0	53
Spillback Cap Reducin	415	2
Storage Cap Reducin	0	0
Reduced v/c Ratio	1.05	0.58

**Intersection Summary**

Cycle Length: 60  
 Actuated Cycle Length: 60  
 Offset: 17 (28%), Referenced to phase 2:EBT, Start of Green  
 Natural Cycle: 55  
 Control Type: Prelimed




Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
<b>Lane Configurations</b>		↕↕									↕↕	
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Total Lost time (s)		4.0									4.0	
Lane Util. Factor		0.95									0.95	
Fit		1.00									1.00	
Fit Protected		1.00									0.98	
Satd. Flow (prot)		3308									3216	
Fit Permitted		1.00									0.98	
Satd. Flow (perm)		3308									3216	
Volume (vph)	0	1170	25	0	0	0	0	0	0	220	390	0
Peak-hour factor, PHF	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Adj. Flow (vph)	0	1272	27	0	0	0	0	0	0	239	424	0
RTOR Reduction (vph)	0	3	0	0	0	0	0	0	0	0	22	0
Lane Group Flow (vph)	0	1297	0	0	0	0	0	0	0	0	641	0
Parking (#/hr)			5							10	10	10
Turn Type										Perm		
Protected Phases		2									4	
Actuated Green, G (s)		30.0									22.0	
Effective Green, g (s)		30.0									22.0	
Actuated g/C Ratio		0.50									0.37	
Clearance Time (s)		4.0									4.0	
Lane Grp Cap (vph)		1654									1179	
v/s Ratio Prot		0.039									0.20	
v/s Ratio Perm											0.54	
v/c Ratio		0.78									0.54	
Uniform Delay, d1		12.3									15.0	
Progression Factor		0.62									0.52	
Incremental Delay, d2		3.7									1.6	
Delay (s)		11.3									9.4	
Level of Service		B									A	
Approach Delay (s)		11.3								0.0	0.0	9.4
Approach LOS		B								A	A	A

**Intersection Summary**

HCM Average Control Delay: 10.7 HCM Level of Service: B  
 HCM Volume to Capacity ratio: 0.68 Sum of lost time (s): 8.0  
 Actuated Cycle Length (s): 60.0 ICU Level of Service: B  
 Intersection Capacity Utilization: 57.0% Analysis Period (min): 15  
 Critical Lane Group: c

Lane Group	EBT	NBT
Lane Configurations	4↑	4↑
Volume (vph)	990	430
Lane Group Flow (vph)	1500	641
Turn Type		
Protected Phases	2	8
Detector Phases	2	8
Minimum Initial (s)	4.0	4.0
Minimum Split (s)	20.5	20.5
Total Split (s)	34.0	26.0
Total Split (%)	56.7%	43.3%
Yellow Time (s)	4.0	4.0
All-Red Time (s)	0.0	0.0
Lead/Lag Optimizer?		
Recall Mode	Max	Max
v/c Ratio	0.93	0.54
Control Delay	18.5	15.5
Queue Delay	17.4	0.0
Total Delay	35.9	15.5
Queue Length 50th (ft)	298	83
Queue Length 95th (ft)	#422	128
Internal Link Dist (ft)	217	324
Turn Bay Length (ft)		
Base Capacity (vph)	1614	1190
Starvation Cap Reductn	157	0
Spillback Cap Reductn	6	0
Storage Cap Reductn	0	0
Reduced v/c Ratio	1.03	0.54

**Intersection Summary**  
 Cycle Length: 60  
 Actuated Cycle Length: 60  
 Offset: 28 (47%), Referenced to phase 2:EBTL, Start of Green  
 Natural Cycle: 60  
 Control Type: Pre-timed  
 # 95th Percentile volume exceeds capacity, queue may be longer.  
 Queue shown is maximum after two cycles.



Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		4↑						4↑				
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Total Lost time (s)		4.0						4.0				
Lane Util. Factor		0.95						0.95				
Fit		1.00						0.96				
Fit Protected		0.99						1.00				
Satd. Flow (prot)		3228						3140				
Fit Permitted		0.99						1.00				
Satd. Flow (perm)		3228						3140				
Volume (vph)	390	990	0	0	0	0	0	430	160	0	0	0
Peak-hour factor, PHF	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Adj. Flow (vph)	424	1076	0	0	0	0	0	467	174	0	0	0
RTOR Reduction (vph)	0	0	0	0	0	0	0	39	0	0	0	0
Lane Group Flow (vph)	0	1500	0	0	0	0	0	602	0	0	0	0
Parking (#/hr)	10	10	10	10	10	10	10	10	10	10	10	10
Turn Type	Perm											
Protected Phases		2						8				
Actuated Green, G (s)		30.0						22.0				
Effective Green, g (s)		30.0						22.0				
Actuated g/C Ratio		0.50						0.37				
Clearance Time (s)		4.0						4.0				
Lane Grp Cap (vph)		1614						1151				
v/s Ratio Prot		0.46						0.19				
v/s Ratio Perm		0.93						0.52				
v/c Ratio		0.93						0.52				
Uniform Delay, d1		14.0						14.9				
Progression Factor		0.63						1.00				
Incremental Delay, d2		7.6						1.7				
Delay (s)		16.5						16.6				
Level of Service		B						B				
Approach Delay (s)		16.5						16.6				
Approach LOS		B						A				

**Intersection Summary**  
 HCM Average Control Delay: 16.5 HCM Level of Service: B  
 HCM Volume to Capacity ratio: 0.76 Sum of lost time (s): 8.0  
 Actuated Cycle Length (s): 60.0 ICU Level of Service: B  
 Intersection Capacity Utilization: 62.4% Analysis Period (min): 15  
 Critical Lane Group: c

Lane Group	WBT	NBT	NBR	SBL	SBR
Lane Configurations	400	205	930	95	345
Volume (vph)	511	234	1011	103	375
Lane Group Flow (vph)	custom D.P+P custom				
Turn Type	custom				
Protected Phases	8	6	6	8	2
Permitted Phases	8	6	6	8	2
Detector Phases	8	6	6	8	2
Minimum Initial (s)	4.0	4.0	4.0	4.0	4.0
Minimum (s)	29.0	27.0	24.0	24.0	24.0
Total Split (s)	29.0	27.0	56.0	24.0	24.0
Total Split (%)	36.3% 33.8% 70.0% 30.0% 30.0%				
Yellow Time (s)	4.0	4.0	4.0	4.0	4.0
All-Red Time (s)	0.0	0.0	0.0	0.0	0.0
Lead-Lag Optimizer?	None				
Recall Mode	0.86	0.54	0.79	0.15	0.38
v/c Ratio	40.4	29.2	7.5	8.1	5.7
Control Delay	0.0	0.0	0.0	0.0	0.0
Queue Delay	40.4	29.2	7.5	8.1	5.7
Queue Length 50th (ft)	219	95	40	21	43
Queue Length 95th (ft)	#416	160	156	41	89
Internal Link Dist (ft)	738 1505				
Turn Bay Length (ft)	623 545 1304 706 975				
Starvation Cap Reductn	0	0	0	0	0
Spillback Cap Reductn	0	0	0	0	0
Storage Cap Reductn	0	0	0	0	0
Reduced v/c Ratio	0.82	0.43	0.78	0.15	0.38
<b>Intersection Summary</b>					
Cycle Length: 80					
Actuated Cycle Length: 73.1					
Natural Cycle: 80					
Control Type: Actuated-Uncoordinated					
# 95th Percentile Volume Exceeds Capacity: Queue may be longer.					
Queue shown is maximum after two cycles.					

Splits and Phases: 133: Colorado Ave & Bend Pkwy SB Ramp  
 24 s 27 s 23 s 24 s 23 s

Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR			
Lane Configurations	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900			
Ideal Flow (vphpl)	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0			
Total Lost time (s)	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00			
Lane Util. Factor	0.98	1.00	0.85	1.00	0.98	1.00	0.85	1.00	0.95	1.00	0.95	1.00			
Fit Protected	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00			
Satd. Flow (prot)	1827	1827	1583	1770	1827	1827	1583	1770	1583	1827	1827	1583			
Fit Permitted	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00			
Satd. Flow (perm)	1827	1827	1583	1770	1827	1827	1583	1770	1583	1827	1827	1583			
Volume (vph)	0	0	0	5	400	65	10	205	930	95	0	345			
Peak-hour factor, PHF	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92			
Adj. Flow (vph)	0	0	0	5	435	71	11	223	1011	103	0	375			
RTOR Reduction (vph)	0	0	0	0	7	0	0	305	0	0	0	86			
Lane Group Flow (vph)	0	0	0	0	504	0	0	234	706	103	0	289			
Turn Type	custom														
Protected Phases	8			8			6			6			6		
Permitted Phases	8			8			6			6			6		
Actuated Green, G (s)	23.5			17.2			44.7			37.5			37.5		
Effective Green, g (s)	23.5			17.2			44.7			37.5			37.5		
Actuated g/C Ratio	0.32			0.24			0.61			0.51			0.51		
Clearance Time (s)	4.0			4.0			4.0			4.0			4.0		
Vehicle Extension (s)	3.0			3.0			3.0			3.0			3.0		
Lane Grp Cap (vph)	588			438			969			693			900		
v/s Ratio Prot	60.28			0.13			60.45			0.04			60.09		
v/s Ratio Perm	0.86			0.53			0.73			0.15			0.32		
v/c Ratio	23.2			24.4			9.9			9.3			10.3		
Uniform Delay, d1	1.00			1.00			1.00			1.00			1.00		
Progression Factor	11.7			1.3			2.8			0.1			0.2		
Incremental Delay, d2	34.9			25.7			12.7			9.4			10.5		
Level of Service	C			C			B			A			B		
Approach Delay (s)	0.0			34.9			15.1			10.3			B		
Approach LOS	A			C			B			B			B		
<b>Intersection Summary</b>															
HCM Average Control Delay	18.6			HCM Level of Service			B			B			B		
HCM Volume to Capacity ratio	0.67			Sum of lost time (s)			12.0			C			C		
Actuated Cycle Length (s)	73.0			ICU Level of Service			15			C			C		
Intersection Capacity Utilization	69.5%			Analysis Period (min)			15			C			C		
Critical Lane Group	c			c			c			c			c		

Splits and Phases: 133: Colorado Ave & Bend Pkwy SB Ramp  
 24 s 27 s 23 s 24 s 23 s

HCM Unsignalized Intersection Capacity Analysis  
 134: Colorado Ave & Bend Pkwy NB Ramp

Baseline  
 2007 PM Peak Hour



Movement	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations	Free	Free	Free	Stop	Stop	Free
Sign Control	0%	0%	0%	0%	0%	0%
Grade	7.95	2.30	2.30	4.75	1.5	2.40
Volume (veh/h)	0.92	0.92	0.92	0.92	0.92	0.92
Peak Hour Factor	864	250	250	516	16	261
Hourly flow rate (vph)						
Pedestrians						
Lane Width (ft)						
Walking Speed (ft/s)						
Percent Blockage						
Right turn flare (veh)						
Median type				None		
Median storage (veh)						
Upstream signal (ft)		818				
pX, platoon unblocked						
VC, conflicting volume		766		2486		508
VC1, stage 1 conf vol						
VC2, stage 2 conf vol						
VCU, unblocked vol		766		2486		508
TC, single (s)		4.1		6.4		6.2
TC, 2 stage (s)						
IF (s)		2.2		3.5		3.3
p0 queue free %		0		0		54
cm capacity (veh/h)		847		0		565
Direction, Lane #	EB 1	EB 2	WB 1	SB 1	SB 2	
Volume Total	864	250	766	16	261	
Volume Left	864	0	0	16	0	
Volume Right	0	0	516	0	261	
CSH	847	1700	1700	0	565	
Volume to Capacity	1.02	0.15	0.45	Err	0.46	
Queue Length 95th (ft)	4.77	0	0	Err	61	
Control Delay (s)	58.2	0.0	0.0	Err	16.7	
Lane LOS	F			F	C	
Approach Delay (s)	45.1		0.0	Err		
Approach LOS				F		
<b>Intersection Summary</b>						
Average Delay			Err			
Intersection Capacity Utilization		98.7%		ICU Level of Service		F
Analysis Period (min)		15				