



MINOR ENCROACHMENT INTO THE RPZ WILL BE CONSIDERED WHERE IDENTIFIED IN AND APPROVED DURING PERMIT REVIEW.

1. PROTECTION FENCING MUST:
 - 1.1. BE INSTALLED PRIOR TO ANY GRADING AND/OR SITE IMPROVEMENTS. FENCING TO BE MAINTAINED UNTIL THE GRADING PERMIT / SITE PERMIT IS COMPLETE.
 - 1.2. TREE PROTECTION METHODS MUST BE CONSISTENT WITH INTERNATIONAL SOCIETY OF ARBORICULTURE (ISA) BEST MANAGEMENT PRACTICES.
 - 1.3. PROTECTION FENCING MUST BE INSTALLED AT THE EDGE OF THE ROOT PROJECTION ZONE AND PERMISSIBLE ENCROACHMENT AREA. EXISTING STRUCTURES AND/OR SECURE FENCING AT LEAST 3.5 FEET TALL CAN SERVE AS THE REQUIRED PROTECTION FENCING.
 - 1.4. SIGNAGE DESIGNATING THE PROTECTION ZONE AND PENALTIES FOR VIOLATIONS MUST BE SECURED ON EACH FENCE AS REQUIRED BY THE BDC.
 - 1.5. FENCING IS TO BE INSPECTED WEEKLY OR AFTER HIGH WINDS. REPAIR AS NEEDED TO ENSURE CONFORMANCE.
2. ANY LANDSCAPING OR IRRIGATION APPROVED WITHIN THE ROOT PROTECTION ZONE MAY BE INSTALLED BEFORE OR AFTER THE REMOVAL OF THE PROTECTION FENCING AND MUST NOT DISTURB EXISTING TREES, INCLUDING ROOTS, WITHIN THE ROOT PROTECTION ZONE.
3. NO EQUIPMENT SHALL OPERATE INSIDE THE PROTECTION FENCING. AREA WITHIN THE FENCING WILL NOT BE USED FOR STAGING OR STORAGE.

DRAWN CJH	DIV EROSION	CITY OF BEND		SCALE NTS
REV	DATE			DATE 11/01/2024
				APPR
				STD DWG E-3
CITY OF BEND		TREE/VEGETATION PROTECTION FENCING		
710 NW WALL ST., BEND, OREGON 97701				