

if shown

E-LA

if shown

ON

E-LA

W-2

D

ONLY

Start of break in line for intersection

15'

15'

15'

15'

Start of W-2

LANE USE ARROW PLACEMENT ($L \leq 400'$)

DETAIL "A"

Start of break in line for intersection

if shown

E-LA

ON

E-RA

E-LA

W-2

W

DLL-2

ONLY

LANE USE ARROW PLACEMENT - TRAP LANE

DETAIL "B"

TWO-WAY LEFT TURN LANE ARROW MARKING PLACEMENT

DETAIL "C"

General Notes:

- 1.) Center pavement marking legends within the lane.
- 2.) Placement of lane use arrows with respect to the 8" wide white line (W-2) channelization shown in details "A", "B" and "C" apply to both left and right turn lanes.
- 3.) When used for a short turn lane ($<40'$), the 2nd (downstream) arrow may be omitted.
- 4.) An ONLY symbol is only required where a through lane approaching an intersection becomes a mandatory turn lane.

** When L is greater than 200', install 3rd lane use arrow at the midpoint of the turn lane.

To be accompanied by Standard Dwg. Nos. R-40 thru R-43

DRAWN	AJD
DIV	ROADWAY
REV	DATE



CITY OF BEND

CITY OF BEND

STANDARD DRAWING

710 NW WALL ST., BEND, OREGON 97701

SCALE NTS

DATE 01/31/2022

APPR

STD DWG R-44

TURN LANE MARKING LAYOUT