

Technical drawing of a mechanical assembly, showing two views: a top view and a side view. The drawing includes dimensions in inches.


Top View Dimensions:

- Overall width: $24 \frac{3}{4}"$
- Overall height: $2 \frac{1}{2}"$
- Distance from left edge to first vertical slot: $2"$
- Width of first vertical slot: $3 \frac{3}{4}"$
- Distance between first and second vertical slots: $3 \frac{3}{4}"$
- Width of second vertical slot: $2"$
- Distance from second vertical slot to right edge: $1 \frac{1}{2}"$
- Distance from left edge to first horizontal slot: $1 \frac{1}{4}"$
- Width of first horizontal slot: $3 \frac{3}{4}"$
- Distance between first and second horizontal slots: $6"$
- Width of second horizontal slot: $3 \frac{3}{4}"$
- Distance from second horizontal slot to right edge: $1 \frac{1}{2}"$

Side View Dimensions:

- Overall width: $25"$
- Overall height: $6"$
- Distance from left edge to first vertical slot: $1"$
- Width of first vertical slot: $23"$
- Distance from second vertical slot to right edge: $3 \frac{1}{4}"$
- Distance from left edge to first horizontal slot: $1 \frac{1}{2}"$
- Width of first horizontal slot: $3 \frac{3}{4}"$
- Distance between first and second horizontal slots: $6"$
- Width of second horizontal slot: $3 \frac{3}{4}"$
- Distance from second horizontal slot to right edge: $1 \frac{1}{2}"$

1. MANHOLE LID ONLY TO BE USED ON CITY OF BEND PUBLIC DRYWELLS AND SEDIMENTATION MANHOLES. PRIVATELY OWNED DRYWELLS AND SEDIMENT MANHOLES SHALL NOT USE A CITY OF BEND MANHOLE LID.
2. HINGED MANHOLE LIDS ARE NOT PERMITTED UNLESS OTHERWISE APPROVED BY THE CITY ENGINEER.
3. ALL MANHOLE LIDS SHALL BE PLACED OUTSIDE THE PATH OF TRAVEL OF SIDEWALKS AND DRIVEWAY APRONS.

DRAWN AJD			<p align="center">CITY OF BEND</p> <p align="center">STANDARD DRAWING</p> <p align="center">710 NW WALL ST., BEND, OREGON 97701</p>	SCALE NTS
DIV STORM				DATE 01/31/2022
REV	DATE			APPR
		CITY OF BEND	STORMWATER MANHOLE LID DETAIL	STD DWG STRM-8